

automatic water softeners

water softeners with control

Autotrol 255/440 (timer)



1



2

Technical data:

throughput: 1500 l/h
operating pressure: 2-8bar
water temperature: 6-25°C
supply: 230V AC

fig.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt amount/ regeneration (kg)	salt tank/capacity	capacity at 20°e (l)	ø x width x height (mm)
4	530131	½"	MINI	12	9	1.5	35	1680	310x430x660
5	530132	¾"	MAXI	26	15	2.7	80	3360	310x430x1100

water softeners with control

Autotrol 255/440 (volumetric)



1



2

Technical data:

throughput: 1500 l/h
operating pressure: 2-8bar
water temperature: 6-25°C
supply: 230V AC

fig.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt amount/ regeneration (kg)	salt tank/capacity	capacity at 20°e (l)	ø x width x height (mm)
1	530133	¾"	MINI	12	9	1.5	35	1680	310x430x660
2	530134	¾"	MAXI	26	15	2.7	80	3360	310x430x1100

water softeners with control

Autotrol LOGIX 255/740 (Timer)



1



2



3

Technical data:

throughput: 1500 l/h
operating pressure: 2-8bar
water temperature: 6-25°C
supply: 230V AC

fig.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt amount/ regeneration (kg)	salt tank/capacity	capacity at 20°e (l)	ø x width x height (mm)
1	530808	½"	GIX 5	5	4	0.5	10	700	225x355x535
2	530809	½"	GIX 8	8	5	1	20	1120	245x480x560
3	530824	¾"	GIX 12	12	8	1.5	25	1680	290x400x665

water softeners with control Autotrol 255/740 (timer)



fig.	part no.	connection	type	tank capacity (l)	resin amount (kg)	salt amount/ regeneration (l)	capacity at 20°e (l)	width x height (mm)
1	530828	¾"	RG 12 AT	12	9	1.5	1500	185x660
2	530829	¾"	RG 16 AT	16	12	2.0	2100	185x760
3	530830	¾"	RG 20 AT	20	16	3.5	2900	185x1060

fig.	part no.	description	length x width x height (mm)	fig.	part no.	description	length x width x height (mm)
4	530360	salt tank 35kg	320x320x440mm	5	530363	salt tank 70kg	320x320x890mm

water softeners with control Autotrol 366/604 (timer)



fig.	part no.	connection	type	tank capacity (l)	resin amount (kg)	salt amount/ regeneration (l)	salt tank/capacity	capacity at 20°e (l)	ø x width x height (mm)
1	530825	½"	ISI 5	5	4	0.5	10	700	225x350x415
2	530826	½"	ISI 8	8	5	1	20	1120	245x450x440
3	530827	¾"	ISI 12	12	8	1.5	25	1680	285x400x550

water softeners with control DM (timer), with mix valve



ATTENTION:
Install with pre-filter only (530178, page 1563)

Technical data:

throughput: 900 l/h
operating pressure: 2-8bar
water temperature: 8-15°C
supply: 230V AC

no.	part no.	connection	type	tank capacity (l)	resin amount (l)	salt amount/ regeneration (kg)	salt tank/capacity	capacity at 20°e (l)	ø x width x height (mm)
1	530158	¾"	DM	8	5.6	1	10	1000	250x480x480