
Professionale pentru echipamente profesionale





heating elements


heating elements for bain maries




heating elements for fryers







heating elements for griddles



heating elements for pasta cookers





heating elements for pizza ovens



















immersion heating elements


































heating elements for convection





































1		D	
No.	418931	Ref. No.	RC126
description	heating element 4000W 230V heating circuits 1 L 1130mm W 80mm connection M4 tube ø 10mm thread M14x1.25 2 hole fixing convection heating element convection oven mounting distance 70mm		





accessories sealing washers O-rings No. 505092 Ref. No. JOIN057 description O-ring EPDM thickness 5.34mm ID ø 43.82mm Qty 1 pcs















thermostats

control and safety thermostats

EGO

description

control thermostats

55.10/19_ series



No. 375468 Ref. No. THER3014

thermostat t.max. 180°C temperature range 80-180°C 1-pole 1NO
16A probe ø 6mm probe L 135mm capillary pipe 900mm capillary
pipe isolatednm gland nut M9x1 shaft ø 6x4.6mm shaft L 23mm
shaft position upper rotation 270°



thermostat $t.max. 320^{\circ}C$ temperature range 55-320 $^{\circ}C$ 1-pole 1NO 16A probe ø 3.1mm probe L 226mm capillary pipe 870mm capillary


pipe isolated 850mm gland nut shaft L 23mm shaft position upper

55.13_ series E-G-O

No. 375154 Ref. No. THER019

thermostat t.max. 250°C temperature range 50-250°C 1-pole 1NO
16A probe ø 3.1mm probe L 201mm capillary pipe 2970mm capillary pipe isolatedmm gland nut shaft L 23mm shaft position upper rotation 270° probe material SS













thermostat t.max. 300°C temperature range 50-300°C 3-pole 3NO 16A probe ø 6mm probe L 79mm capillary pipe 1740mm capillary description pipe isolated 800mm gland nut shaft ø ø6x4.6mm shaft L 23mm shaft position upper rotation 270°

110123

accessories for 375038


knob thermostat t.max. 300°C ø 50mm shaft ø 6x4.6mm shaft flat upper black temperature range 50-300°C rotation 270°

Ref. No.

safety thermostats

No.

55.13 series



IMIT / TEMPOMATIC / ARTHERMO


probe connection male faston 6.3mm


control thermostats



No.	390186	Ref. No.	REGU010
description		obe L 95mm capilla	range fixed 52°C 1-pole 1CO 16A ry pipe 1000mm capillary pipe n contacts 1CO

CAEM safety thermostats THER3004 375996 Ref. No. No. safety thermostat switch-off temp. 225°C 1-pole 1NC 16A probe ø 5mm probe L 80mm capillary pipe 900mm capillary pipe isolated 410mm gland nut M10 probe SS 250V description





switches and momentary switches

rocker/momentary rocker switches

30x22mm



1					
No.	301004	Ref. No.		INT006	
description	16A connection	rocker switch mounting measurements 30x22mm black 2CO 250V 16A connection male faston 6.3mm ambient temperature max. 125/55°C protection IP40			
accessories for	301004	301004			
1	No.	301036	Ref. No.	_	
	protective cover internal size 30x22mm for rocker switch mounting measurementsmm				





301165 Ref. No. No. INT006 rocker switch mounting measurements 30x22mm black 2CO 250V description 16A connection male faston 6.3mm ambient temperature max. 125/55°C protection IP65 with cover cap 301165 accessories for No. 301036 protective cover internal size 30x22mm for rocker switch mounting measurementsmm

No.	301228	Ref. No.	IN	T006
description	rocker switch mounting measurements 30x22mm black 2CO 250V 16A I-II connection male faston 6.3mm ambient temperature max. 125/55°C protection IP65 with cover cap			
accessories for	301228			
1	No.	301036	Ref. No.	_
	protective cover internal size 30x22mm for rocker switch mounting measurementsmm			

push/momentary push switches

ø12mm



l	No.	347567	Ref. No.	INT003
	description	/ /		12mm white 1NO 250V 4A ent temperature max. 85°C


microswitches

roller-lever actuated

non-standard



No.	345902	Ref. No.	INT103
description	microswitch with faston ambient ter		h 250V 16A connection male C



cam switches


4 operating positions



I			
No.	300077	Ref. No.	COMU004
description			O sequence 0-1-2-3 16A shaft ø

magnetic switches

M12x1





control equipment

SCHNEIDER ELECTRIC

rotary switches



No.	347951	Ref. No.	INT037
description	rotary selector mo		ents ø22mm green sequence 0-1

TELEMECANIQUE (EFA)

XB2 series



No	o.	345905	Ref. No.	INT201
descripti	on	contact block 1NO		

signal element



1			
No.	345397	Ref. No.	VOY103
description	signal element m	ounting measureme	ents ø22mm red




No.	359770	Ref. No.	VOY102	
description	signal element, mounting measurements ø22mm vellow			

rotary switches



'			
No.	345222	Ref. No.	INT202
description	rotary selector mounting measurements ø22mm black latching sequence 0-1		



ZB2 series

switch blocks



No.	347566	Ref. No.	INT036		
description	contact block 2NO illuminated				

ZB4 series

rotary switches



No.	347951	Ref. No.	INT037
description	rotary selector mo latching illuminate	•	ents ø22mm green sequence 0-

miscellaneous



No.	345904	Ref. No.	VOY101
description	indicator socket s	ocket Ba9s	



1			
No.	345903	Ref. No.	INT204
description push button black			



lamps

indicator lights

indicator lights 2-piece (lens and indicator lamp)

indicator light lenses

ø12mm (type SDY-3)



No.	359261	Ref. No.	VOT060 VOY060	
escription	indicator light housings mounting measurements ø12mm red round			

indicator lights 3-piece (housing, lens and bulb)

lamps

light bulbs



No.	359772	Ref. No.	VOY202
description	light bulb		


indicator lights (complete)

ø13mm

with plug-in socket



ļ !			
No.	359045	Ref. No.	VOY062
description	indicator light ø 1. tempresist. 120°C		nnection male faston 6.3mm



screw-on/push-on fit

light bulbs

for indicator lights



No.	359772	Ref. No.	VOY202
description	light bulb		

halogen lamp

for socket G4 / G6.35 / G9



No.	357193	Ref. No.	LAMP050
description	halogen lamp socket G4 12V 20W tempresist. 300°C OSRAM HALOSTAR OVEN		

fluorescent lamps

fluorescent lamps

G23



No.	359933	Ref. No.	LAMP030
description	fluorescent lamp	socket G23 L 237mr	m 11W 230V

accessories

covers



1					
No.	551118	Ref. No.	JOIN012		
description	protection cap for	fluorescent lamps	L 33mm W 18mm H 29mm		



oven lamps

producer-specific oven lamps

BOURGEOIS



No.	511690	Ref. No.	JOIN075 JOIN109
description	gasket L 78mm W 3mm for lamp	42mm silicone hole	e distance 66.5mm thickness

1	>		
No.	360530	Ref. No.	HUBL009
description	lamp glass L 47.4mm W 32.8mm glas thickness 3.2mm		



lamps

halogen lamps

for socket G4 / G6.35 / G9



No.	357193	Ref. No.	LAMP050
description	halogen lamp soci	ket G4 12V 20W ter	npresist. 300°C OSRAM

sockets

G4 / G5,3 / G6,35



timers

programme timers




No.	360251	Ref. No.	05224C MOT010	
description	gear motor CROUZET chambers 1 operation time 230V 50Hz shal ømm shaft Lmm H 78mm L 116mm W 55mm type 88256462 shaf 5/6mm			

mechanical timers




No.	350168	Ref. No.	MIN300
description		I 6A permanent pos	min impulse mechanical sition no shaft 6x4.6mm shaft L nection lateral



alarm devices

buzzers







contactors

ISKRA (FANAL)

power contactors



No.	380204	Ref. No.	REL610
description	contacts 3NO auxi		30VAC (AC3/400V) 9A/4kW main connection screw connection

TELEMECANIQUE (Schneider Electric)

power contactors



No.	380479	Ref. No.	REL1607
description		auxiliary contacts	30VAC (AC3/400V) 9A/4kW 1NO/1NC connection screw







auxiliary contactors



No.	381139	Ref. No.	REL622	
description	auxiliary contactor 230VAC AC1 10A type CA2KN407M7 connection male faston 2.8mm/6.3mm contacts 4NO			


auxiliary contacts




No.	381140	Ref. No.	REL464
description	auxiliary contact of GVAN11	ontacts 1NO/1NC A	AC15 6A connection screw type












solid state relays






relays

level relays



time relays








transformers

toroidal core transformers



encapsulated transformers

with screw connection



No.	400800	Ref. No.	TRAN601
description	transformer		

electronic controllers

LOREME

analogue





No.	379744	Ref. No.	REGU050
description	electronic controller LOREME type Dsl 94 mounting measurements 66x32mm 230V voltage ACTC/J 0-250°C display without display relay		
	outputs 2 front measurements 70x34mm built-in depth 95mm		

1					
No.	379745	Ref. No.	REC	EGU012 GU008 GU011	
description	electronic controller kit LOREME type Dsl 94 mounting measurements 66x32mm 230V voltage AC TC/J 0-250°C display without display relay outputs 2 front measurements 70x34mm built-in depth 95mm cable length 2530mm probe L 20mm probe ø 4mm with probe and fastening material				
spare parts for	379745				
All and a second	No.	379744	Ref. No.	REGU050	
	electronic controller LOREME type DsI 94 mounting measurements 66x32mm 230V voltage AC TC/J 0-250°C display without display relay outputs 2 front measurements 70x34mm built-in depth 95mm				

probes


producer-specific probes







electronics

PCBs





















keypads

keypad units



solenoid valves

solenoid valves (water)

ROBERTSHAW/INVENSYS

90℃ 90℃ 60℃ medium temperature: 60℃ 25℃ 60℃ ambient temperature: duty cycle: 40% 100% 100%


solenoid valves with reducers

2-fold




des


No.	372001	Ref. No.	06245
scription	duty cycle 100% E/	ATON (INVENSYS) p gulating valve outl	C inlet 3/4" outlet 11.5mm lastic output A 1.2l/min output et A dark blue flow regulating non-return valve






electric components







electrodes









1—4					
No.	400804	Ref. No.	NIV602		
description	level electrode 3/8" total length 75mm probe L 48mm insulated probe length 47mm conical connection M4				


fans

axial fans




with ball bearing

hot air motors







No.	601805	Ref. No.	MOT050 MOT2012	
description	fan motor 230V 1 phase 50/60Hz 0.185kW 1400/1680rpm speeds. L1 130mm L2 27mm L3 37mm D1 ø 17mm D2 ø 13.5mm 1A suitab capacitor 5μF/450V Cos(fi) 0.93 type 1079GA2350			
accessories for	601805			

No. 511605 Ref. No. JOIN222

shaft seal








hot air fans








No.	601808	Ref. No.	MOT2023
			2mm L3mm L4 87mm fan 12-3030LH-197 ebm-papst





motors





pumps







booster pumps II

accessories







4

condensators & interference suppression filters

operating capacitors

plastic No. 365150 Ref. No. MOT2008 operating capacitor capacity 20µF 425V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 40mm L 70mm M8 plastic connection male faston 6.3mm 416.10.25 protection



filters

line filters


with housing




No.	365040	Ref. No.	ELEC050
description	/ /	aston 6.3mm L 65m	50/60Hz conductor 2 with E nm ømm H 19mm W 35mm

fuses

fine fuses







electric accessories

terminals

terminal blocks



No.	550232	Ref. No.	BAR001
description	lustre terminal tempresist. 15	•	2.5mm² max. 32A max 450V


rail-mounted terminals

WIELAND

rail-mounted terminals type 9700A





•			
No.	550374	Ref. No.	BORN101
description	rail-mounted term	,,	9700A/10 S35 1.5-16mm² top-












accessorie	S			
15				
No.	550370	Ref. No.	BORN211	
description	terminal block end bracket clampsmm²			


electronic components

differential pressure transmitters

1						
			06762			
No.	402988	Ref. No.	20924			
			20946			
description	differential pressure transmitter for combi-steamer conversion kit					

miscellaneous





gas taps

PEL 22S/O series



No.	106384	Ref. No.	R	OB3001		
description	nozzle ø 0mm connection <i>N</i>	gas tap PEL type 22S/O gas inlet M20x1.5 (tube ø 12mm) bypass nozzle ø 0mm gas outlet M20x1.5 (tube ø 12/10mm) thermocouple connection M9x1 pilot connection M10x1 shaft ø 10x8mm shaft L 25/17mm shaft flat lower				
pare parts for	106384					
	No.	101058	Ref. No.	_		
Of Other Park	magnet unit EGA24197 sta		mm D2 ø 13.5mm	suitable for PEL22		
The state of the s	No.	101231	Ref. No.	_		
	thermocouple nut T1: M9x1 T2: M18x1					
	No.	106191	Ref. No.	_		
	bypass nozzle type PEL22 bore ø 0mm thread M6x0.5					
accessories for	106384					
	No.	101248	Ref. No.	_		
S. T.	olive for pipe ø 12mm Qty 1 pcs suitable for PEL					
	No.	101249	Ref. No.	_		
	olive for pipe ø 10mm Qty 1 pcs					
0	No.	101250	Ref. No.			
3	union nut thi	read M20x1.5 for p	oipe ø 10mm			



ignition parts

pilot burners

SIT

100 series

accessorie

pilot burner nozzle



No.	100245	Ref. No.	INJ3007
description	pilot burner nozzle M8x0.75	LPG code 20 bore	ø 0.2mm Qty 1 pcs thread

1) dans				
No.	100246	Ref. No.	INJ3006		
description	pilot burner r	pilot burner nozzle natural gas bore ø 0.35mm Qty 1 pcs thread			

ignition electrodes 6 18 09 3 07 23 1 02,4 No. 100707 Ref. No. ALLU3000 description ignition electrode D1 ø 7mm D2 ø 9mm connection ø2.4mm L1 14mm L2 6mm BL1 18mm BL2 3mm BL3 23mm to clip Qty 1 pcs


Oxipilot 9000 series

pilot burners



'						
No.	106388	Ref. No.	BRU	JL3002		
description	' ''	pilot burner type Oxipilot 9000 series 2 flames natural gas nozzle no. 33 nozzle ø 0.33mm gas connection 6mm without ignation electrode bore ø 0.33mm				
accessories for	106388					
0	No.	100904	Ref. No.	_		
6	locking screw M10x1 for pipe ø 4mm Qty 1 pcs					
	No.	100905	Ref. No.	_		
6	locking screw M	10x1 for pipe ø 6n	nm Qty 1 pcs			
Sa	No.	100907	Ref. No.	_		
	screw connection thermocouple	n thread M10x1 C	ty 1 pcs type SEF	1 ømm for		






producer-specific pilot burners

BOURGEOIS




1				
No.	106387	Ref. No.	BRU	L3004
description	pilot burner 1 flame gas connection 6mm without nozzle			
accessories for	106387			
-	No.	106385	Ref. No.	INJ3008
	pilot burner nozzle LPG code 22 bore ø 0.22mm thread M5x0.75 Qty 1 pcs brass			
-	No.	106386	Ref. No.	INJ3000
	pilot burner nozzle natural gas code 40 bore ø 0.4mm thread M5x0.75 Qty 1 pcs brass			







gas components




electrodes








ignition units



thermocouples plug-in thermocouples plug-in thermocouples standard thermocouples SIT ø 6 17.5-33.5 42,5 1 52.5 107614 Ref. No. THER3006 No. description thermocouple SIT M9x1 L 1500mm plug connection ø6.0(6.5)mm












gas burners

hob burners accessories pan supports

Ref. No.

pan support W 320mm L 320mm

GRIL3001




bar burners

No.


description


210025











gas nozzles

main nozzles

gas nozzles 3/8"



No.	106535	Ref. No.	INJ3009
description	gas injector thread	d 3/8" WS 17 bore ø	1.3mm



No.	106537	Ref. No.	INJ3014
description	gas injector thread 3/8" WS 17 bore ø 1.5mm		1.5mm

pilot burner nozzles

pilot burner nozzles AEM



No.	106385	Ref. No.	INJ3008
description	pilot burner nozzle 1 pcs brass	LPG code 22 bore	ø 0.22mm thread M5x0.75 Qty


pilot burner nozzles SIT



1	China China		
No.	100245	Ref. No.	INJ3007
description	pilot burner nozzle M8x0.75	LPG code 20 bore	ø 0.2mm Qty 1 pcs thread








pilot burner nozzles (other)

SOLYMAC/CAPIC



'			
No.	106385	Ref. No.	INJ3008
description	pilot burner nozzle 1 pcs brass	e LPG code 22 bore	ø 0.22mm thread M5x0.75 Qty



auxiliary gas parts

gas ball valves

miscellaneous



	No.	520586	Ref. No.	ROB3006
descrip	otion	ball valve IT 1/2" L 73mm handle ø 23	,	handle angled W 28mm H N 331

equipment-specific units

for ice-cube maker


Tor ree ease maker				
hoses				
formed h	formed hoses			
straight				
silicone ho	ses			
1				
No.	530063	Ref. No.	TUY1824	
description	silicone hose ID ø 18mm ED ø 25mm L 1m t.max. 200°C transparent			

for convection ovens/combi-steamers spare parts and accessories No. 541859 Ref. No. DECO3016 description bush ID Ø 14.5mm ext. Ø 18/22 thickness 5.5mm






















door mechanics accessories No. 694537 Ref. No. CHAR203 base plate L 51mm W 22mm for catch plastic mounting distance









knobs

universal knobs





producer-specific knobs







locks

handle latches

universal

inside fixing

locks



No.	694054	Ref. No.	CHA	AR2006	
description	door handle for	or headed units L 14 Inner black	5mm W 40mm H (52mm spring	
spare parts for	694054				
^	No.	514390	Ref. No.	_	
	spring for doo	r handle ø 6mm L 54	łmm W 27.5mm		
	No.	694675	Ref. No.	_	
A Pa	door catch L8 ting distance 6	8mm W 40mm H 37 0mm	mm spring length	33mm moun-	
	No.	694734	Ref. No.	_	
	door handle L 165mm W 40mm H 25mm black				
	No.	694735	Ref. No.	_	
	cap ø 32mm black				
accessories for	694054				
	No.	691123	Ref. No.	_	
	duct for door opener				
•	No.	694055	Ref. No.	_	
1	door catch L 25mm W 14mm total length 54mm thread M8 thread L 29mm				
	No.	694066	Ref. No.		
C.S.O.	door catch with spigot 2-stage L 28mm W 14mm H 15mm H1 16mm total length 51mm thread M8 thread L 23mm stainless steel				
971	No.	694067	Ref. No.	CHAR2007	
0	door catch with spigot 1-stage L 26mm total length 51mm thread M8				

producer-specific

BOURGEOIS



1					
No.	694054	Ref. No.	CHA	AR2006	
description	door handle for headed units L 145mm W 40mm H 62mm spring length 33mm inner black			62mm spring	
spare parts for	694054				
^	No.	514390	Ref. No.	_	
	spring for door	handle ø 6mm L 5	4mm W 27.5mm		
- 10	No.	694675	Ref. No.	_	
- Pa	door catch L 881 ting distance 601	mm W 40mm H 37 mm	mm spring length	33mm moun-	
	No.	694734	Ref. No.	_	
	door handle L 165mm W 40mm H 25mm black				
	No.	694735	Ref. No.	_	
	cap ø 32mm bla	ck			
accessories for	694054				
	No.	691123	Ref. No.	_	
	duct for door opener				
	No.	694055	Ref. No.	_	
1	door catch L 25mm W 14mm total length 54mm thread M8 thread L 29mm				
1	No.	694066	Ref. No.	_	
-	door catch with spigot 2-stage L 28mm W 14mm H 15mm H1 16mm total length 51mm thread M8 thread L 23mm stainless steel				
970	No.	694067	Ref. No.	CHAR2007	
door catch with spigot 1-stage L 26mm total length 51mm t			51mm thread		




edgemount latches

push button latches

RAHRBACH


description

6196 DDESTO sorios



ted H 34mm W 28mm type PRESTO no. 6186

push button latch L 180mm mounting distance 121mm chrome-pla-



snap locks

universal





No.	700800	Ref. No.	CHAR150
			m mounting distance 50mm ed brass thickness 2.7mm


miscellaneous



1	-0		
No.	511613	Ref. No.	FERM003
description	door catch		
















hinges






oven hinges




door bearing





miscellaneous





shelves and shelf rails

chargrill grids








gaskets


gaskets for heated units

















































¹3-sided (short side open)













door seals with fixing hook					
1					
No.	900741	Ref. No.	JOIN1010		
description	door seal L 650mm W 575mm with 4 mounting clips plug size				





























sealing cords



shaft gaskets














springs


torsion springs




1——————————————————————————————————————				
	No.	514504	Ref. No.	RES3000
	description	torsion spring ø 30mm wire gauge ø 4.5mm L1 16mm L2 185mm L3 13mm mounting pos. right		


compression springs








miscellaneous



hoses





9

fittings, hose and pipe connectors

hose connectors

producer-specific



No.	511946	Ref. No.	RAC2011 RAC2021
description	T-piece plastic/SS connection 2: 8mn		/ 27mm 1/8" connection 1: 8

water cycle components

pressure reduction valves

pressure reduction valves

producer-specific



No.	520589	Ref. No.	ROB028
description	pressure reduction valve Norgren series R91 connection 1/4" default settingbar setting range 0.1-3bar p max 10bar t.max. 50°C brass		



non-return valves



fastening material

screws

grub screws

DIN 913/ISO 4026



No.	504733	Ref. No.	VIS317
description	grub screw threachexagon WS 2 Qty		ss steel DIN 913 intake internal

miscellaneous



No.	692200	Ref. No.	DECO366
description	grub screw thread	I M6 L 2.5mm SS int	ake slotted WS Qty 1 pcs

washers

washers

miscellaneous



No.	692198	Ref. No.	VIS276
description	plain washer ID ø	8.5mm ED ø 18mm	thickness 1.4mm SS Qty 1 pcs





consumables


sealants and adhesives

high temperature silicone



1			
No.	890059	Ref. No.	JOIN555
description	high temperature +265°C black cartr		P 300 neutral curing -40 up to
description	Is used for sealing chimneys, stack with the moistur hot air-resistance of loose parts ai necessary, be giv soap s Highly refracto	expansion joints o s, etc. The sealant is e in the air and is ch . The adhesive surfa nd in the case of po yen a first coat of pro plution must take p	ridge 310ml - black on heating flues, ovens, reactors, a neutrally cross-linking, reacts haracterised by extremely good aces must be dry, clean and free rous substrates they should, if imer. Post-smoothing e.g. with lace before skinning. vater/colour/hot-air resistant .50°C to +250°C

fuses fine fuses No. 358532 Ref. No. FUSI003 description fine fuse size ø5x20mm 2A fast-acting rated 250V Qty 10 pcs



fine fuse holders				
1				
No.	358010	Ref. No.	FUSI613	
description	fuse holder suitab F4.8	le fuse ø6.3x32mm	10A rated 250V connection	

