

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

C.P.E. S.R.L.

heating elements

radiation heaters

1-circuit



No.	490150	Ref. No.	10.73631.004
description	radiation heater ø 250mm 2500W 230V heating circuits 1 energy regulation with temperature signalization with heating coil connections 2+2 connection type male faston 6.3mm EGO		
For models:	015-D4S		



No.	490000	Ref. No.	I2.02501.047
description	radiation heater round ø 250mm 2500W 230V heating circuits 1 energy regulation with temperature signalization with heating coil connections 2+2 connection type with porcelain clamp and cable length 500mm		


energy regulators

EGO

1-circuit



No.	380015	Ref. No.	50.17021.000 50.57021.010
description	energy regulator 230V 13A single-circuit turn direction right shaft ø 6x4.6mm shaft L 23mm mounting thread M4 power release 6-100% no. 50.57021.010		
For models:	015-D4S, 051-C		



No.	380857	Ref. No.	I2.02501.044
description	energy regulator 230V 13A single-circuit turn direction right shaft ø 6x4.6mm shaft L 23mm with porcelain clamp and cable		

accessories

knobs



No.	112561	Ref. No.	524046
description	knob energy regulator 1-3 t.max.°C ø 42mm shaft ø 6x4.6mm shaft flat upper		
For models:	015-D4S, 051-C, 330		

thermostats

control and safety thermostats

EGO

control thermostats

55.10/19_ series



No.	375457	Ref. No.	55.19219.823
description	thermostat t.max. 82°C 1-pole capillary pipe isolatedmm gland nut		
For models:	415IX		

55.14_ series



No.	375481	Ref. No.	55.14022.800
description	thermostat t.max. 140°C temperature range 30-140°C 1-pole 1NO 16A probe ø 3mm probe L 156mm capillary pipe 900mm capillary pipe isolated 900mm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position left rotation 270°		
For models:	330, 361		



TECASA

safety thermostats




No.	390802	Ref. No.	SP-011ZS
description	safety thermostat switch-off temp. 210°C 1-pole 16A probe ø 3mm probe L 130mm capillary pipe 850mm capillary pipe isolated 760mm		
For models:	415IX		

switches and momentary switches

cam switches

on/off




No.	300151	Ref. No.	49.22015.705
description	cam switch 2 operating positions 2NO sequence 0-1 16A shaft ø 6x4.6mm shaft L 23mm connection screw ceramic		
For models:	410-RA		

4-position




No.	300245	Ref. No.	R4944015713
description	cam switch 4 operating positions sequence 0-1-2-3 shaft ø 6x4.6mm shaft L 23mm connection screw clamp 4-pole at 250V 16A		

7-position




No.	300244	Ref. No.	R43.27232.800
description	cam switch 7-position 3-pole + signal contact 32A shaft ø 6x4.6mm shaft L 23mm connection screw clamp 3-pole ambient temperature max. 150°C shaft position lower		

2 operating positions



No.	300228	Ref. No.	R49.22015.704old
description	cam switch 4 operating positions sequence 0-1-0-2 shaft ø 6x4.6mm shaft L 23mm connection male faston 6.3mm 2-pole		

4 operating positions



No.	300246	Ref. No.	R4922015704
description	cam switch 4 operating positions sequence 0-1-0-2 shaft ø 6x4.6mm shaft L 23mm connection male faston 6.3mm 2-pole		

lamps

indicator lights

indicator lights (complete)

ø 6mm



No.	359009	Ref. No.	I0.65015.000 R1065015000
description	indicator light ø 6mm 230V red cable length 400mm with series resistor		
For models:	015-D4S, 050A, 051-C, 220-B, 330, 410-RA, 415IX		



1

No.	357122	Ref. No.	R1065015004
description	indicator light ø 6mm 400V red cable length 210mm temp.-resist. 120°C		

residual heat indicators



1

No.	357121	Ref. No.	R1065015009
description	residual heat indicator single 240V connection male faston 6.3mm mounting ø 18mm		

electric accessories

terminals

connection boxes



1

No.	550488	Ref. No.	I0.65000.021
description	power terminal block 3-pole		
For models:	015-D4S, 330, 361, 361-IR, 410-RA, 415IX, 461-N		

equipment-specific units for pyroceram ranges

ceramic hobs

ceramic glass plates



1

No.	691837	Ref. No.	I0.63002.010
description	ceramic plate L 360mm W 360mm thickness 4mm		
For models:	015-D4S		



1

No.	691838	Ref. No.	I0.63002.002
description	ceramic plate ø 260mm thickness 4mm		
For models:	461-N		

knobs

universal knobs



1

No.	112560	Ref. No.	524098
description	knob thermostat 1-12 t.max.°C ø 50mm shaft ø 6x4.6mm shaft flat upper		



1

No.	112561	Ref. No.	524046
description	knob energy regulator 1-3 t.max.°C ø 42mm shaft ø 6x4.6mm shaft flat upper		
For models:	015-D4S, 051-C, 330		



1

No.	110932	Ref. No.	524060
description	knob switch zero mark t.max.°C ø 42mm shaft ø 6x4.6mm shaft flat upper black		
For models:	410-RA, 415IX		

producer-specific knobs

CPE



1

No.	112561	Ref. No.	524046
description	knob energy regulator 1-3 t.max.°C ø 42mm shaft ø 6x4.6mm shaft flat upper		
For models:	015-D4S, 051-C, 330		



1

No.	110932	Ref. No.	524060
description	knob switch zero mark t.max.°C ø 42mm shaft ø 6x4.6mm shaft flat upper black		
For models:	410-RA, 415IX		



1

No.	112560	Ref. No.	524098
description	knob thermostat 1-12 t.max.°C ø 50mm shaft ø 6x4.6mm shaft flat upper		

equipment feet and end caps

screw-in feet



1

No.	691836	Ref. No.	I0.62600.000
description	equipment foot thread M8 thread L 49mm ø 31mm H 11mm Qty 1 pcs		
For models:	015-D4S, 330, 361, 361-IR, 410-RA, 415IX, 461-N		

consumables

sealants and adhesives

high temperature silicone



1

No.	890060	Ref. No.	I0.62420.000
description	adhesive PACTAN 6076 310ml 250°C anthracite		
description	PACTAN 6076 - cartridge 310ml - anthracite 1-component silicone-based product for specific gluing and sealing purposes that require a high temperature resistance. The material is used for bonding and sealing of parts with high temperature load e.g. inner door of oven as well as for other bonding and sealing purposes especially on ovens and ranges. The product is fast to light, resistant to ageing and ozone and reveals a very good chemical resistance. Temperature resistance up to 250°C		
For models:	415IX		