

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS




TOOLS

Spare parts suitable for

CAPITO


heating elements



heating elements for bain maries

			
1			
No.	418250	Ref. No.	63857
description	heating element 1500W 230V heating circuits 1 L 265mm W 244mm connection M4 tube ø 8mm 2 hole fixing thread M14x1.25 immersion heater W1 57mm W2 130mm H 25mm mounting distance 122mm		







heating elements for fryers

2 hole fixing


			
1			
No.	415740	Ref. No.	63852
description	heating element 3000W 230V heating circuits 1 L 305mm W 145mm H 280mm L1 65mm L2 240mm thread M14x1.5 mounting distance 131mm tube ø 8.5mm windings 3 2 hole fixing connection M4 fryer heaters		
spare parts for	415740		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
accessories for	415740		
	No.	510420	Ref. No. —
gasket copper ED ø 19.9mm ID ø 14.3mm thickness 2mm Qty 1 pcs			
	No.	520228	Ref. No. —
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	No.	520230	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	521103	Ref. No. —
nut thread M4 H 3mm WS 7 brass Qty 20 pcs			
	No.	521104	Ref. No. —
washer ID ø 4.3mm ED ø 8mm thickness 0.5mm brass Qty 20 pcs for thread M4			
	No.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			

accessories for	415740		
	No.	560111	Ref. No. —
plain washer ID ø 4.3mm ED ø 9mm thickness 0.8mm SS Qty 20 pcs DIN 125A for thread M4			
	No.	560131	Ref. No. —
hexagonal nut thread M4 H 3.2mm WS 7 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 20 pcs			

heating elements for griddles



			
1			
No.	418268	Ref. No.	63853
description	heating element 2000W 230V heating circuits 1 L 396mm W 123mm H 38mm tube ø 8.5mm 2 hole fixing thread M14x1.5 cable length 1000mm mounting distance 115mm connection length 22mm for griddle dry heating element		
spare parts for	418268		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
accessories for	418268		
	No.	520228	Ref. No. —
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	No.	520230	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			

heating elements for chargrills


			
1			
No.	418261	Ref. No.	63854
description	heating element 330W 230V L 425mm dry heating element rectangular flange tube ø 6.3mm flange length 34mm flange width 15mm		

ceramic heaters



245x60mm

			
1			
No.	415104	Ref. No.	63850
description	ceramic emitter 1000W 230V cable beaded cord L 245mm W 60mm H 35mm		
spare parts for	415104		
	No.	415109	Ref. No. —
spring clip			



accessories for		415104		
	No.	415110	Ref. No.	—
	reflector L 245mm W 95mm H 31mm thickness 0.75mm hole ø 15x40mm			

1

No.	415102	Ref. No.	63851
description	ceramic emitter 400W 230V cable beaded cord L 245mm W 60mm H 35mm		
spare parts for	415102		
	No.	415109	Ref. No. —
spring clip			
accessories for	415102		
	No.	415110	Ref. No. —
reflector L 245mm W 95mm H 31mm thickness 0.75mm hole ø 15x40mm			

hot plates

square & rectangular

with radiused edge




1			
No.	490065	Ref. No.	63887
description	hot plate dimensions 220x220mm 2000W 230V with spill ring connection 4 screw clamps protector no square		

E.G.O.

1

No.	490066 ¹	Ref. No.	63886
description	hot plate dimensions 220x220mm 2600W 230V with spill ring connection 4 screw clamps protector yes square		

¹incl. protector

1

No.

490054¹

Ref. No.

63885

description

hot plate dimensions 300x300mm 2500W 230V with spill ring connection 4 screw clamps protector yes

¹incl. protector

1

No.

490074¹

Ref. No.

63884

description



hot plate dimensions 300x300mm 4000W 400V with spill ring connection 4 screw clamps protector yes square

¹incl. protector


round

with radiused edge

for domestic and commercial kitchens

1			
No.	490014	Ref. No.	63889
description	hot plate ø 180mm 1500W 230V connection 4 screw clamps with 8mm spill ring		

<div><div>1</div></div>			
No.	490018	Ref. No.	63890
description	hot plate ø 220mm 2000W 230V connection 4 screw clamps with 8mm spill ring		

energy regulators

EGO

1-circuit



No.	380015	Ref. No.	63867
description	energy regulator 230V 13A single-circuit turn direction right shaft ø 6x4.6mm shaft L 23mm mounting thread M4 power release 6-100% no. 50.57021.010		

thermostats

control and safety thermostats

EGO

control thermostats

55.13_ series



No.	375713	Ref. No.	63859
description	thermostat temperature range 113-171°C 3-pole 3NO 16A probe ø 6.5mm probe L 219mm capillary pipe 880mm capillary pipe isolated-mm gland nut		

safety thermostats


55.31_ series







No.	375700	Ref. No.	63860 63864
description	safety thermostat switch-off temp. 232°C 3-pole 20A probe ø 6.5mm probe L 219mm capillary pipe 830mm capillary pipe isolated 800mm gland nut probe		

control thermostats with operation switch

55.13_ series



No.	375406	Ref. No.	63892
description	thermostat t.max. 110°C temperature range 30-110°C 1-pole 1CO 16A probe ø 6mm probe L 113mm capillary pipe 2380mm capillary pipe isolated 1700mm gland nut M9x1 shaft ø 6x4.6mm shaft L 18mm shaft position upper rotation 270° outer switch 2NO		
accessories for	375406		
	No.	110545	Ref. No. —
	knob dial plate silver thermostat t.max. 110°C 30-110°C rotation 310° ED ø 59mm ID ø 45.5mm		
	No.	112173	Ref. No. —
	knob universal ø 62mm black without adaptor/dial plate		
	No.	112311	Ref. No. —
	knob adapter shaft ø 6x4.6mm L 0mm with spring		




No.	375701	Ref. No.	63863
description	thermostat t.max. 173°C temperature range 120-173°C 1-pole 1NO 16A probe ø 6.5mm probe L 119mm capillary pipe 870mm capillary pipe isolated 800mm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 245° outer switch 2NO		

switches and momentary switches

rocker/momentary rocker switches

30x22mm



No.	301003	Ref. No.	63871
description	rocker switch mounting measurements 30x22mm green 2NO 250V 16A illuminated 0-I connection male faston 6.3mm ambient temperature max. 125/55°C protection IP65		
accessories for	301003		
	No.	301036	Ref. No. —
	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		



microswitches


lever actuated





No.	345107	Ref. No.	63875
description	microswitch with lever 250V 16A 1CO connection male faston 6.3mm L 98mm ambient temperature max. 125°C mounting distance 22mm actuating force: 30g lever length 90mm		

cam switches

on/off



No.	300020	Ref. No.	63870
description	cam switch 4 operating positions 2NO sequence 0-1-0-1 16A shaft ø 6x4.6mm shaft L 23mm connection screw ceramic		
accessories for	300020		
	No.	110135	Ref. No. —
rosette knob up to ø 52mm			
	No.	110231	Ref. No. —
knob switch 0-1-0-1 t.max.°C ø 50mm shaft ø 6x4.6mm shaft flat upper black			






No.	300021	Ref. No.	63869
description	cam switch 4 operating positions 4NO sequence 0-1-0-1 16A shaft ø 6x4.6mm shaft L 23mm connection screw ceramic		



No.	300102	Ref. No.	63868
description	cam switch 4 operating positions 4NO sequence 0-1-0-1 32A shaft ø 6x4.6mm shaft L 23mm connection screw ceramic		

7-position



No.	300025	Ref. No.	63873
description	cam switch 7 operating positions 1NO/2CO sequence 0-1-2-3-4-5-6 16A shaft ø 6x4.6mm shaft L 23mm connection screw 7-position ceramic		
accessories for	300025		
	No.	112172	Ref. No. —
knob universal ø 70mm black without adaptor/dial plate			
	No.	112213	Ref. No. —
knob dial plate silver switch 7-position t.max.°C ED ø 63mm ID ø 45.5mm			
	No.	112311	Ref. No. —
knob adapter shaft ø 6x4.6mm L 0mm with spring			



No.	300106	Ref. No.	63872
description	cam switch 7 operating positions 1NO/2CO sequence 0-1-2-3-4-5-6 32A shaft ø 6x4.6mm shaft L 23mm connection screw 7-position shaft flat upper		

fans



cross flow fans

cross flow fan with heater battery

roller diameter ø60mm



1

No.	601027	Ref. No.	63905
description	cross flow fan roller length 180mm roller ø 60mm motor position right 230V 50Hz 17W heat output 2000W bearing silicone cable length 200mm with temperature limiter 125°C		
spare parts for	601027		
	No.	375095	Ref. No. —
	bi-metal thermostat hole distance 18mm switch-off temp. 105°C 1NC 1-pole 16A connection F6.3 2 hole fixing		
	No.	375911	Ref. No. —
	bi-metal thermostat switch-off temp. 125°C 1NC 1-pole for cross flow fan		

electric accessories

plug connectors



1

No.	550171	Ref. No.	32D0140
description	plug connector 10-pole STV 2/10		

baskets

fryer baskets

CAPITO



1

No.	970442	Ref. No.	63877
description	fryer basket L1 275mm W1 165mm H1 120mm		