

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

GMG

heating elements

heating elements for contact grills



1

No.	420254	Ref. No.	KL-052 KO-B108 KO-B108-150
description	heating element 1000W 220V heating circuits 1 L 194mm W 274mm H 37mm connection distance 40mm tube ø 8.5mm windings 4 connection M4 mounting pos. upper dry heating element for contact grill		



1

No.	420266	Ref. No.	KL-057 KO-B113 KO-B113-150 WF-B108 WF-B108-150
description	heating element 1000W 220V heating circuits 1 L 200mm W 220mm H 34mm connection distance 34mm tube ø 8.5mm windings 1 connection M4 mounting pos. lower dry heating element for contact grill/waffle iron		



1

No.	420222	Ref. No.	WF-B109 WF-B109-150
description	heating element 1100W 220V L 208mm W 210mm H 35mm tube ø 6.5mm connection M4 connection distance 139mm for contact grill windings 4 with fixing sheet		



1

No.	420264	Ref. No.	KL-063 WF-B105 WF-B105-105
description	heating element 1100W 230V heating circuits 1 L 185mm W 215mm H 41mm connection distance 12mm tube ø 8.5mm windings 3 connection M4 mounting pos. upper dry heating element for waffle iron		



1

No.	420263	Ref. No.	WF-B107 WF-B107-150
description	heating element 1100W 230V heating circuits 1 L 207mm W 219mm H 34mm connection distance 141mm tube ø 6.5mm windings 4 connection M4 mounting pos. lower dry heating element for waffle iron		



1

No.	417642	Ref. No.	KL-066 KL-067
description	heating element 1100W 230V L 245mm W 205mm H 35mm tube ø 6.5mm connection distance 133mm cable lengthmm waffle iron		


			
No.	420252	Ref. No.	KL-054 KO-B109 KO-B109-150
description	heating element 1250W 220V heating circuits 1 L 185mm W 395mm H 28mm connection distance 37mm tube ø 8.3mm windings 4 connection M4 mounting pos. upper dry heating element for contact grill		

			
No.	420253	Ref. No.	KG2735DEG-09 KL-053 KO-B111 KO-B111-150
description	heating element 1500W 220V heating circuits 1 L 225mm W 278mm H 37mm connection distance 32mm tube ø 8.5mm windings 4 connection M4 mounting pos. lower dry heating element for contact grill		

			
No.	420248	Ref. No.	KL-055 KO-B112 KO-B112-150
description	heating element 2000W 220V heating circuits 2 L 240mm W 383mm H 33mm connection distance 32mm tube ø 8.5mm windings 6 connection M4 mounting pos. lower dry heating element for contact grill		

			
No.	420265	Ref. No.	KL-056 KO-B110 KO-B110-150 WF-B106 WF-B106-150
description	heating element 650W 220V heating circuits 1 L 160mm W 210mm H 28mm connection distance 38mm tube ø 8.5mm windings 1 connection M4 mounting pos. upper dry heating element for contact grill/waffle iron		

heating elements for pizza ovens

			
No.	420250	Ref. No.	PI-B107 PI-B107-150 PI-B114 PI-B114-150 PI-B116 PI-B116-150
description	heating element 1250W 220V L 613mm W 218mm flange length 245mm flange width 25mm hole distance 120mm connection M4 tube ø 8.3mm heating circuits 1 flange connection hole ø 4.5mm dry heating element for pizza oven		

			
No.	420249	Ref. No.	PI-B109 PI-B109-150 PI-B112 PI-B112-150 PI-B113 PI-B113-150
description	heating element 1250W 220V L 688mm W 250mm flange length 270mm flange width 25mm hole distance 131mm connection M4 tube ø 8.3mm heating circuits 1 flange connection hole ø 4.5mm dry heating element for pizza oven		

			
No.	420251	Ref. No.	PI-B115 PI-B115-150 PI-B117 PI-B117-150
description	heating element 1500W 220V heating circuits 1 L 610mm W 350mm flange length 355mm flange width 25mm hole distance 173mm tube ø 8.5mm connection M4 flange connection hole ø 5mm dry heating element for pizza oven		

thermostats

control and safety thermostats

EGO


control thermostats

55.10/19_ series



No.	375253	Ref. No.	PF4040E-21 PF5050DE4-21 PF6262E-21 PI-B148 PI-B148-150
description			
thermostat t.max. 455°C temperature range 85-455°C 1-pole 1NO 16A probe ø 3.9mm probe L 228mm capillary pipe 870mm capillary pipe isolated 660mm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270°			

55.17_ series



No.	390821	Ref. No.	CR-B118 KG2735DEG-24 KL-010 KO-B118 WF-B112 WF-B112-150
description			
thermostat t.max. 310°C temperature range 50-310°C 1-pole 1NO 16A probe ø 4mm probe L 111mm capillary pipe 1000mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 16mm shaft position° shaft position rotation 270°			

switches and momentary switches

rocker/momentary rocker switches

30x11mm



No.	347350	Ref. No.	PI-B100 PI-B100-150
description			
rocker switch mounting measurements 30x11mm black 1CO 250V 16A I O connection male faston 6.3mm ambient temperature max. 90°C protection IP40			

cam switches

2 operating positions



No.	300112	Ref. No.	CR-B105 DT-B102 GP-B102 KL-007 KO-B102 KO-B102-150 WF-B103 WF-B103-150
description			
cam switch 1NO sequence 0-1 10A shaft ø 6x4.6mm shaft L 23mm connection screw ON-OFF			

rotary switches

miscellaneous



No.	347734	Ref. No.	PF7070E-21A PF-B121A PI-B101 PI-B101-150
description			
rotary switch sets of contacts 2 2 0-1 type CA20A201 690V 25A shaft ø 5.8mm shaft L 27mm shaft star-shaped complete connection screw			

lamps

indicator lights

indicator lights (complete)

ø10mm

with screw socket



No.	359400	Ref. No.	CR-B117 DT-B106 GP-B106 KL-006 KO-B119 KO-B119-150 PI-B118 PI-B118-150 WF-B113 WF-B113-150
description			
indicator light ø 10mm 230V green			



1

No.	359401	Ref. No.	CR-B101 CR-B104 DT-B101 GP-B101 KL-005 KO-B101 KO-B101-150 WF-B101 WF-B101-150
description		indicator light ø 10mm 230V red	

screw-on/push-on fit

light bulbs

for ovens



1

No.	359612	Ref. No.	PF7070E-15 PI-B102 PI-B102-150 PI-B103 PI-B103-150
description		light bulb t.max. 300°C socket E14 25W 230V ø 25mm L 56mm lens L 30mm for oven lamp type Philips	

oven lamps

universal oven lamps

mounting diameter 35.5mm



1

No.	359934	Ref. No.	PF5050DE3-15A PI-B102B PI-B102B-150
description		oven lamp mounting ø 35.5mm 230V 25W socket E14 temp.-resist. 300°C connection male faston 6.3mm hard glas	



1

No.	359942	Ref. No.	PF9262DE-15C PI-B102A
description		oven lamp glass thr.ø 33.5mm ø 41mm hard glas temp.-resist. 350°C	

55x70mm



1

No.	359659	Ref. No.	PI-B103B-150
description		oven lamp complete 230V 25W socket E14 L 70mm W 55mm mounting measurements 55x70mm temp.-resist. 300°C connection male faston 6.3mm	



1

No.	357159	Ref. No.	PI-B103B
description		lamp socket socket E14 mounting measurements 55x70mm connection male faston 6.3mm Qty 1 pcs	



1

No.	359937	Ref. No.	PI-B103A PI-B103A-150
description		lamp glass L 80mm W 65mm mounting measurements 52x67mm	



1

No.	359937	Ref. No.	PI-B103A PI-B103A-150
description		lamp glass L 80mm W 65mm mounting measurements 52x67mm	



1

No.	357159	Ref. No.	PI-B103B
description		lamp socket socket E14 mounting measurements 55x70mm connection male faston 6.3mm Qty 1 pcs	

lamps

light bulbs



1			
No.	359612	Ref. No.	PF7070E-15 PI-B102 PI-B102-150 PI-B103 PI-B103-150
description		light bulb t.max. 300°C socket E14 25W 230V ø 25mm L 56mm lens L 30mm for oven lamp type Philips	



1			
No.	696483	Ref. No.	KL-021 KO-B158 KO-B158-150 KO-B302 KO-B302-150
description		grease collecting tray L 535mm W 27mm H 29mm	

equipment-specific units

for grills

sumps



1			
No.	696481	Ref. No.	KL-019 KO-B131 KO-B131-150 KO-B300 KO-B300-150
description		grease collecting tray L 290mm W 26mm H 32mm	



1			
No.	696482	Ref. No.	KL-020 KO-B150 KO-B150-150 KO-B301 KO-B301-150
description		grease collecting tray L 489mm W 26mm H 32mm	

for pizza ovens

glass panels

1			
No.	694525	Ref. No.	PF6262E-08 PI-B138
description		glass panel L 420mm W 95mm thickness 6mm for pizza oven	

1			
No.	694528	Ref. No.	PI-B133 PI-B145
description		glass panel L 660mm W 105mm thickness 5mm	

1			
No.	694565	Ref. No.	PI-B143 PI-B143-150
description		glass panel L 715mm W 105mm thickness 5mm for pizza oven Qty 1 pcs	

firebricks

1			
No.	850116	Ref. No.	PI-B123-150 PI-B124 PI-B132
description		firebrick L 615mm W 610mm H 18mm delivery freight forwarding company only	

			
1			
No.	850117	Ref. No.	PI-B127 PI-B127-150
description	firebrick L 695mm W 350mm H 14mm delivery freight forwarding company only		

knoobs

universal knobs

			
1			
No.	112687	Ref. No.	CR-B113 DT-B103 GP-B103 KL-008 KO-B103 KO-B103-150 WF-B102 WF-B102-150
description	knob zero mark t.max.°C ø 38mm shaft ø 6x4.6mm shaft flat lower black		

producer-specific knobs

GMG

			
1			
No.	112691	Ref. No.	CR-B115 DT-B107 GP-B107 KL-011 KO-B120 KO-B120-150 PI-B149 PI-B149-150 WF-B114 WF-B114-150
description	knob zero mark ø 54mm shaft ø 6x4.6mm shaft flat upper black		

			
1			
No.	112687	Ref. No.	CR-B113 DT-B103 GP-B103 KL-008 KO-B103 KO-B103-150 WF-B102 WF-B102-150
description	knob zero mark t.max.°C ø 38mm shaft ø 6x4.6mm shaft flat lower black		

handles and hand wheels

cone handles

			
1			
No.	111480	Ref. No.	KL-001 KO-B100 KO-B100-150 WF-B100 WF-B100-150
description	cone handle thread M6 ø 29mm L 37.5mm plastic black		

folding grill handles

			
1			
No.	111483	Ref. No.	KL-002 KL-B121 KO-B107 KO-B107-150
description	cone handle ø 26mm bore ø 12mm L 155mm plastic black for contact grill		

			
1			
No.	111484	Ref. No.	WF-B104 WF-B104-150
description	cone handle ø 26mm bore ø 12mm L 155mm plastic red for waffle iron		

equipment feet and end caps

screw-in feet

			
1			
No.	696484	Ref. No.	CR-B112 DT-B104 GP-B104 KL-012 KO-B117 KO-B117-150 WF-B111 WF-B111-150
description		equipment foot thread 3/8" Whitworth thread L 24mm ø 43mm H 24mm Qty 1 pcs	

springs

torsion springs

			
1			
No.	692336	Ref. No.	KL-016 KO-B104-AD KO-B106 KO-B106-150
description		torsion spring ø 20mm L1 98mm L2 57mm wire gauge ø 3.5mm for contact grill	

			
1			
No.	692335	Ref. No.	KL-014 KO-B104 KO-B104-150
description		torsion spring ø 21.5mm L1 160mm L2 76mm wire gauge ø 4mm for contact grill	

			
1			
No.	692334	Ref. No.	KL-015 KO-B105 KO-B105-150
description		torsion spring ø 21.6mm L1 205mm L2 76mm wire gauge ø 4mm for contact grill	

measuring equipment

thermometers

built-in thermometers

ø60mm

			
1			
No.	541879	Ref. No.	PF-B131 PI-B147 PI-B147-150
description		thermometer mounting ø 60mm 0 up to +500°C probe ø 8mm probe L 155mm capillary pipe 1000mm	