

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

KREFFT

heating elements

heating elements for ovens

1			
No.	415995	Ref. No.	49-182322
description	heating element 1500W 400V heating circuits 1 L 460mm W 484mm L1 107mm L2 360mm W1 211mm W2 62mm flange length 104mm flange width 32mm hole distance 96/39mm hole ø 4mm tube ø 6.4mm connection male faston 6.3mm connection length 51mm tilt flange dry heating element		
For models:	GEH6030, GEH6050		





1			
No.	415795	Ref. No.	49-182325
description	heating element 2000W 400V heating circuits 1 L 490mm W 575mm L1 40mm L2 450mm W1 257mm W2 60mm flange length 105mm flange width 34mm hole distance 38mm hole ø 4mm tube ø 6.5mm connection male faston 6.3mm tilt flange dry heating element oven		


1			
No.	417605	Ref. No.	49-160631
description	heating element 2100W 400V L 465mm W 480mm H 10mm tube ø 6.5mm heating circuits 1 oven		

heating elements for bain maries


1			
No.	415608	Ref. No.	49-182403
description	heating element 2000W 230V heating circuits 1 L 430mm W 135mm connection length 20mm connection male faston 6.3mm tube ø 6.3mm 2 hole fixing thread M14x1.5 dry heating element L1 50mm L2 380mm W1 100mm W2 38mm mounting distance 32mm		
spare parts for	415608		
		No. 510417	Ref. No. —
accessories for	415608		
		No. 520228	Ref. No. 76-30041405
		No. 520230	Ref. No. 76-30041406
		No. 521101	Ref. No. —
		No. 550262	Ref. No. —







1			
No.	415609	Ref. No.	49-182404
description	heating element 2000W 400V heating circuits 1 L 430mm W 135mm connection male faston 6.3mm tube ø 6.5mm 2 hole fixing thread M14x1.5 immersion heater L1 50mm L2 380mm W1 100mm W2 38mm mounting distance 32mm		
accessories for	415609		
		No. 510417	Ref. No. —
		No. 520228	Ref. No. 76-30041405
		No. 520230	Ref. No. 76-30041406
		No. 521101	Ref. No. —
		No. 550262	Ref. No. —

			
No.	415988	Ref. No.	49-182328
description	heating element 3000W 230V heating circuits 1 L 420mm W 330mm L1 36mm L2 383mm W1 147mm W2 30mm flange length 70mm flange width 23mm hole distance 56mm connection male faston 6.3mm tube ø 6.5mm rectangular flange mounting thread M3 dry heating element		
accessories for	415988		
	No.	527169	Ref. No. —
hexagonal nut thread M3 H 2.8mm WS 5.5 brass Qty 1 pcs			
	No.	560110	Ref. No. —
plain washer ID ø 3.2mm ED ø 7mm thickness 0.5mm SS Qty 20 pcs DIN 125A for thread M3			
	No.	560130	Ref. No. —
hexagonal nut thread M3 H 2.4mm WS 5.5 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 20 pcs			

			
No.	415589	Ref. No.	49-182327
description	heating element 3000W 400V heating circuits 1 L 420mm W 330mm flange length 70mm flange width 22mm hole distance 57mm connection male faston 6.3mm tube ø 6.3mm flange 70 x 22mm dry heating element L1 41mm L2 383mm W1 149mm W2 31mm		

heating elements for fryers

			
No.	415490	Ref. No.	01-214567
description	heating element 5100W 230/400V heating circuits 3 L 345mm W 168mm H 246mm L1 70mm L2 275mm H1 229mm H2 17mm W1 21mm W2 104mm windings 6 flange ø 39mm connection cable rotation flange immersion heater		

2 hole fixing			
			
No.	415591	Ref. No.	49-182651
description	heating element 2000W 230V heating circuits 1 L 285mm W 40mm H 240mm H1 200mm H2 40mm mounting pos. 20 thread M14x1.5 tube ø 8.5mm mounting distance 20mm windings 3 2 hole fixing connection male faston 6.3mm immersion heater		
spare parts for	415591		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
accessories for	415591		
	No.	520228	Ref. No. 76-30041405
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	No.	520230	Ref. No. 76-30041406
nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			










			
No.	415978	Ref. No.	49-182652
description	heating element 3000W 230V heating circuits 1 L 288mm W 48mm H 243mm H1 205mm H2 38mm thread M14x1.5 tube ø 8.5mm windings 3 2 hole fixing connection male faston 6.3mm		
spare parts for	415978		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
accessories for	415978		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
	No.	520228	Ref. No. 76-30041405
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			


Table continues overleaf

accessories for 415978				
	No.	520230	Ref. No.	76-30041406
	nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No.	—
	nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	550262	Ref. No.	—
	flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			


heating elements for griddles


				
1	No.	415593	Ref. No.	49-182330
	description heating element 2565W 230V L 554mm W 125mm H 30mm connection male faston 6.3mm dry heating element heating circuits 1 tube ø 8.5mm W1 40mm W2 45mm rectangular flange hole distance 56mm flange length 70mm flange width 22mm hole ø 5mm connection length 34mm			

				
1	No.	415594	Ref. No.	49-182329
	description heating element 2565W 400V L 556mm W 126mm H 33mm connection male faston 6.3mm dry heating element heating circuits 1 tube ø 6.3mm W1 48mm W2 30mm rectangular flange hole distance 56mm flange length 70mm flange width 22mm mounting thread M4			


				
1	No.	415479	Ref. No.	01-214338
	description heating element 750W 230V heating circuits 1 L 471mm W 30mm Hmm tube ø 6.35mm rectangular flange connection male faston 6.3mm hole distance 36mm flange length 44mm flange width 20mm hole ø 4.5mm connection length 30mm dry heating element			


heating elements for tilting bratt pan

				
1	No.	415593	Ref. No.	49-182330
	description heating element 2565W 230V L 554mm W 125mm H 30mm connection male faston 6.3mm dry heating element heating circuits 1 tube ø 8.5mm W1 40mm W2 45mm rectangular flange hole distance 56mm flange length 70mm flange width 22mm hole ø 5mm connection length 34mm			


				
1	No.	415594	Ref. No.	49-182329
	description heating element 2565W 400V L 556mm W 126mm H 33mm connection male faston 6.3mm dry heating element heating circuits 1 tube ø 6.3mm W1 48mm W2 30mm rectangular flange hole distance 56mm flange length 70mm flange width 22mm mounting thread M4			


heating elements for chargrills

				
1	No.	415595	Ref. No.	49-182332
	description heating element 1900W 400V L 410mm W 125mm H 28mm hole distance 56mm windings 3 W1 45mm W2 31mm flange length 70mm flange width 22mm connection male faston 6.3mm heating circuits 1 tube ø 6.3mm mounting thread M4 rectangular flange dry heating element			

				
1	No.	415592	Ref. No.	49-182653
	description heating element 2000W 230V L 400mm W 142mm H 64mm thread M14x1.5 mounting distance 94mm tube ø 8.5mm connection male faston 6.3mm windings 3 heating circuits 1 connection length 39mm 2 hole fixing dry heating element W1 21mm W2 102mm			

heating elements for salamanders/toast-

				
1	No.	416653	Ref. No.	75-3804
	description heating element 2000W 230V L 225mm W 283mm L1 15mm L2 210mm W1 110mm W2 63mm hole distance 96mm connection M4 tube ø 8.5mm flange length 106mm flange width 32mm heating circuits 1 hole ø 5mm tilt flange dry heating element H 8.5mm			

				
1	No.	415621	Ref. No.	75-3706
	description heating element 2000W 230V heating circuits 1 L 228mm W 230mm L1 29mm L2 228mm W1 84mm W2 62mm flange length 116mm flange width 32mm hole distance 96mm tube ø 8.5mm connection length 17mm dry heating element connection M4 rectangular flange hole ø 5mm H 8.5mm			



pilot heating elements



1

No.	415460	Ref. No.	01-214610
description	heating element 1000W 230V heating circuits 1 flange 70x18mm L 230mm W 65mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange connection length 20mm silicone TD ø 8mm		
accessories for	415460		
	No.	375044	Ref. No.
			—



1

No.	415607	Ref. No.	49-181729
description	heating element 500W 230V heating circuits 1 thread 3/4" L 295mm W 20mm H 19mm length thermostat sleeves 235mm thermostat sleeves ø 6mm number of thermostat sleeves 1 thermostat sleeve clinging tube ø 6.5mm immersion heater flange with thread connection length 50mm pilot heating element		
spare parts for	415607		
	No.	510403	Ref. No.
			—
accessories for	415607		
	No.	510421	Ref. No.
			—
	No.	520234	Ref. No.
			—

immersion heating elements

3 hole flange ø47.5mm











1

No.	415069	Ref. No.	49-182521
description	heating element 4500W 220V mounting ø 47.5mm heating circuits 3 L 310mm W 30.5mm H 29mm tube ø 6.3mm connection male faston 6.3mm 3 hole flange immersion heater		
accessories for	415069		
	No.	510408	Ref. No.
			—
	No.	520235	Ref. No.
			—



accessories for	415069		
	No.	520236	Ref. No.
			—
	No.	521012	Ref. No.
			—
	No.	550002	Ref. No.
			—
	No.	550362	Ref. No.
			—

No.	416240	Ref. No.	62-230083
description	heating element 6545W 230/400V mounting ø 48mm heating circuits 3 L 355mm W 31mm H 37mm number of thermostat sleeves 1 thermostat sleeves ø 7mm length thermostat sleeves 175mm thermostat sleeve upper centre not clinging tube ø 6.5mm hole distance 63mm hole ø 10mm connection M4 3 hole flange immersion heater		
accessories for	416240		
	No.	510408	Ref. No.
			—
	No.	510562	Ref. No.
			—




No.	415668	Ref. No.	62-230090
description	heating element 2625W 230V mounting ø 47.5mm heating circuits 1 L 190mm W 41mm H 54mm number of thermostat sleeves 1 thermostat sleeves ø 7mm length thermostat sleeves 170mm thermostat sleeve eccentric, non clinging tube ø 6.3mm hole distance 62mm hole ø 8mm connection M4 3 hole flange immersion heater		
spare parts for	415668		
	No.	510408	Ref. No.
			—
accessories for	415668		
	No.	510562	Ref. No.
			—

 			
No.	415002	Ref. No.	62-230005
description	heating element 3000W 230V mounting Ø 47.5mm heating circuits 1 L 198mm W 35mm H 44mm number of thermostat sleeves 1 thermostat sleeves Ø 7mm length thermostat sleeves 175mm thermostat sleeve not clinging tube Ø 6.3mm hole distance 64mm hole Ø 8mm connection M4 3 hole flange immersion heater		
accessories for	415002		
	No.	510408	Ref. No. —
	O-ring EPDM thickness 5.34mm ID Ø 47mm Qty 1 pcs		
	No.	510562	Ref. No. —
	O-ring silicone thickness 5.34mm ID Ø 47mm Qty 1 pcs		
	No.	521103	Ref. No. —
	nut thread M4 H 3mm WS 7 brass Qty 20 pcs		
	No.	521104	Ref. No. —
	washer ID Ø 4.3mm ED Ø 8mm thickness 0.5mm brass Qty 20 pcs for thread M4		
	No.	560111	Ref. No. —
	plain washer ID Ø 4.3mm ED Ø 9mm thickness 0.8mm SS Qty 20 pcs DIN 125A for thread M4		
	No.	560131	Ref. No. —
	hexagonal nut thread M4 H 3.2mm WS 7 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 20 pcs		



3 hole flange Ø57.5mm


 			
No.	420159	Ref. No.	63-110392
description	heating element 14000W 230/400V mounting Ø 57.5mm heating circuits 3 L 500mm W 36mm H 43mm number of thermostat sleeves 1 thermostat sleeves Ø 7.5mm length thermostat sleeves 290mm thermostat sleeve eccentric, non clinging tube Ø 8.3mm hole distance 73mm hole Ø 10mm connection length 26mm connection M5 3 hole flange		


with compression flange 70 x 26mm


 			
No.	415009	Ref. No.	62-230087
description	heating element 2500W 230V heating circuits 1 flange 70x26mm L 280mm W 51mm H mm tube Ø 6.3mm connection M4 immersion heater compression flange		
accessories for	415009		
	No.	521128	Ref. No. —
	gasket L 66mm W 21mm Ø mm for heating element ELETTOBAR, WOLK		


with expansion flange 70 x 18mm


			
No.	415460	Ref. No.	01-214610
description	heating element 1000W 230V heating circuits 1 flange 70x18mm L 230mm W 65mm connection male faston 6.3mm tube Ø 8.5mm immersion heater expansion flange connection length 20mm silicone TD Ø 8mm		
accessories for	415460		
	No.	375044	Ref. No. —
	safety thermostat switch-off temp. 178°C 1-pole 16A probe Ø 4mm probe L 91mm capillary pipe 1730mm capillary pipe isolated 1600mm gland nut probe with sealing sleeve screw connection M8x1 sealing sleeve 8.6x32mm		

			
No.	417684	Ref. No.	76-30043506 76-30044103 76-30044306
description	heating element 3000W 230V heating circuits 2 flange 70x18mm L 365mm W 65mm connection male faston 6.3mm tube Ø 8.5mm immersion heater expansion flange		

			
No.	417685	Ref. No.	76-30044303
description	heating element 3000W 400V heating circuits 2 flange 70x18mm L 365mm W 64mm connection male faston 6.3mm tube Ø 8.5mm immersion heater expansion flange		

			
No.	415557	Ref. No.	01-214087
description	heating element 5600W 400V heating circuits 2 L 272mm W 64mm tube Ø 8.5mm connection male faston 6.3mm immersion heater expansion flange 70x18mm		

			
No.	417672	Ref. No.	76-30043516 76-30044105 76-30044108 76-30044307
description	heating element 6000W 230V flange 70x18mm L 355mm		

			
No.	417687	Ref. No.	76-30043505 76-30043523 76-30044102 76-30044106 76-30044305
description	heating element 6000W 230V heating circuits 2 flange 70x18mm L 365mm W 65mm connection male faston 6.3mm tube Ø 8.5mm immersion heater expansion flange connection length 32mm		



No.	417699	Ref. No.	76-30044155 76-30044156
description	heating element 6000W 230V heating circuits 2 flange 70x18mm L 375mm W 65mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange thermostat sleeves ø 2.5mm length thermostat sleeves 105mm number of thermostat sleeves 1		



No.	417673	Ref. No.	76-30043518 76-30044304
description	heating element 6000W 400V flange 70x18mm number of thermostat sleeves 1		



No.	417686	Ref. No.	76-30043508 76-30044302
description	heating element 6000W 400V heating circuits 2 flange 70x18mm L 365mm W 65mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange		



No.	417688	Ref. No.	76-30044157 76-30044158
description	heating element 6000W 400V heating circuits 2 flange 70x18mm L 370mm W 65mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange thermostat sleeves ø 3mm length thermostat sleeves 134mm number of thermostat sleeves 1		



No.	415464	Ref. No.	01-214608
description	heating element 6000W 400V heating circuits 2 flange 70x18mm L 380mm W 65mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange		






No.	418639	Ref. No.	76-30044159
description	heating element 6000W 440V heating circuits 2 flange 70x18mm L 370mm W 68mm connection male faston 6.3mm tube ø 8.5mm immersion heater expansion flange thermostat sleeves ø 2.5mm length thermostat sleeves 115mm thermostat sleeve clinging number of thermostat sleeves 1		

with round flange ø47.5mm










1









No.	415512	Ref. No.	026233 400229
description	heating element 2790W 230V heating circuits 3 mounting ø 47.5mm L 375mm W 130mm H 23mm tube ø 6.3mm round flange with thread bolt connection male faston immersion heater connection length 17mm		
accessories for	415512		
	No.	510408	Ref. No. —
O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	510562	Ref. No. —
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	550002	Ref. No. —
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			

















No.	415513	Ref. No.	026227 400222	
description	heating element 2800W 230V heating circuits 2 mounting ø 47.5mm L 345mm W 35mm H 28mm round flange connection male faston 6.3mm immersion heater tube ø 6.3mm thermostat sleeves ø 9mm number of thermostat sleeves 1 length thermostat sleeves 235mm thermostat sleeve not clinging			
accessories for	415513			
	No.	510562	Ref. No.	—
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs				
	No.	520235	Ref. No.	—
3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm				
	No.	520236	Ref. No.	—
flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes				
	No.	521012	Ref. No.	—
gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs				
	No.	550002	Ref. No.	—
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element				
	No.	550362	Ref. No.	—
blind flange ø 64mm mounting ø 47.5mm				

			
1			
No.	415508	Ref. No.	023235 400245
description	heating element 3000W 230V heating circuits 3 mounting ø 47.5mm L 380mm W 125mm H 25mm tube ø 6.3mm round flange with thread bolt connection male faston 6.3mm immersion heater connection length 30mm H1 15mm		
accessories for	415508		
	No.	510562	Ref. No. —
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	521012	Ref. No. —
gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs			
	No.	550002	Ref. No. —
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			



			
1			
No.	415511	Ref. No.	026231 400244
description	heating element 6000W 220V heating circuits 3 mounting ø 47.5mm L 355mm W 35mm H 113mm round flange connection male faston 6.3mm immersion heater tube ø 6.3mm thermostat sleeves ø 7mm number of thermostat sleeves 1 length thermostat sleeves 235mm thermostat sleeve not clinging		
accessories for	415511		
	No.	510562	Ref. No. —
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	520235	Ref. No. —
3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			
	No.	520236	Ref. No. —
flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes			
	No.	521012	Ref. No. —
gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs			
	No.	550002	Ref. No. —
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			
	No.	550362	Ref. No. —
blind flange ø 64mm mounting ø 47.5mm			


			
1			
No.	415599	Ref. No.	49-182656
description	heating element 6000W 230V heating circuits 3 L 385mm W 31mm H 36mm tube ø 8.5mm thermostat sleeves ø 6.5mm length thermostat sleeves 180mm number of thermostat sleeves 1 thermostat sleeve centre connection male faston 6.3mm immersion heater round flange mounting ø 47.5mm		
spare parts for	415599		
	No.	510408	Ref. No. —
O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs			
accessories for	415599		
	No.	510408	Ref. No. —
O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	510562	Ref. No. —
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	520235	Ref. No. —
3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			
	No.	520236	Ref. No. —
flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes			
	No.	550002	Ref. No. —
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			
	No.	550362	Ref. No. —
blind flange ø 64mm mounting ø 47.5mm			







			
1			
No.	415405	Ref. No.	49-182416
description	heating element 6000W 230V heating circuits 3 L 465mm W 38mm H 24mm tube ø 6.3mm connection male faston 6.3mm immersion heater round flange mounting ø 47.5mm		
spare parts for	415405		
	No.	504148	Ref. No. —
boiler			
accessories for	415405		
	No.	520235	Ref. No. —
3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			
	No.	520236	Ref. No. —
flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes			
	No.	521012	Ref. No. —
gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs			
	No.	550002	Ref. No. —
tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			
	No.	550362	Ref. No. —
blind flange ø 64mm mounting ø 47.5mm			








			
No.	415416	Ref. No.	49-182539
description	heating element 7500W 230V heating circuits 3 L 460mm W 37mm H 26mm tube ø 6.3mm thermostat sleeves ø 7mm length thermostat sleeves 200mm number of thermostat sleeves 1 thermostat sleeve eccentric, non clinging connection male faston 6.3mm immersion heater round flange mounting ø 47.5mm		
spare parts for	415416		
		No. 510408	Ref. No. —
	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs		
accessories for	415416		
		No. 520235	Ref. No. —
	3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm		
		No. 520236	Ref. No. —
	flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes		
		No. 521012	Ref. No. —
	gasket graphite ED ø 15mm ID ø 5mm thickness 1.2mm Qty 1 pcs		
		No. 550002	Ref. No. —
	tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element		
		No. 550362	Ref. No. —
	blind flange ø 64mm mounting ø 47.5mm		









miscellaneous


			
No.	417695	Ref. No.	76-32011000 76-32011004 76-32011009
description	heating element 9000W 230V heating circuits 3 L 205mm W 38mm H 70mm number of thermostat sleeves 1 thermostat sleeves ø 2.5mm length thermostat sleeves 120mm thermostat sleeve eccentric, clinging tube ø 6.3mm hole distance 64mm hole ø 8mm connection male faston 6.3mm 4 hole flange immersion heater flange width 82mm flange length 82mm		
accessories for	417695		
		No. 512482	Ref. No. 76-51101003
	gasket rubber L 82mm W 82mm thickness 4mm hole ø 9mm hole distance 64mm for heating element suitable for RATIONAL 4 holes		

			
No.	417696	Ref. No.	76-32011200
description	heating element 9000W 230V heating circuits 3 L 232mm W 76mm H 38mm number of thermostat sleeves 1 thermostat sleeves ø 2.5mm length thermostat sleeves 235mm thermostat sleeve eccentric, clinging tube ø 6.5mm hole distance 64mm hole ø 8mm connection length 41mm connection male faston 6.3mm rectangular flange immersion heater flange width 72mm flange length 82mm		


			
No.	415256	Ref. No.	43-0101493
description	heating element 7500W 230V heating circuits 3 L 480mm W 34mm H 32mm tube ø 6.3mm thermostat sleeves ø 7mm length thermostat sleeves 310mm number of thermostat sleeves 1 thermostat sleeve not clinging connection male faston 6.3mm connection length 52mm immersion heater flange with thread thread 1½"		
spare parts for	415256		
		No. 510406	Ref. No. —
	flat gasket fibre ED ø 60mm ID ø 48mm thickness 3mm for thread 1½" Qty 1 pcs		
accessories for	415256		
		No. 510424	Ref. No. —
	gasket copper ED ø 55mm ID ø 48mm thickness 2.2mm Centellen for thread 1½"		
		No. 520211	Ref. No. —
	reducer thread 2" ET - 1½" IT brass		
		No. 520212	Ref. No. —
	hexagonal nut thread 1½" brass WS 60 H 8mm		
		No. 550361	Ref. No. —
	blind flange ø 58mm thread 1½"		



			
No.	415664	Ref. No.	62-230085
description	heating element 2250W 230V heating circuits 1 L 300mm W 90mm H 25mm thread 1/8" mounting distance 64mm tube ø 6.3mm connection M4 immersion heater 2 hole fixing		
accessories for	415664		
		No. 510893	Ref. No. —
	O-ring EPDM thickness 2.62mm ID ø 9.92mm Qty 1 pcs		
		No. 521103	Ref. No. —
	nut thread M4 H 3mm WS 7 brass Qty 20 pcs		
		No. 521104	Ref. No. —
	washer ID ø 4.3mm ED ø 8mm thickness 0.5mm brass Qty 20 pcs for thread M4		
		No. 521129	Ref. No. —
	nut thread M10 H 6mm SS WS 17 Qty 1 pcs DIN/ISO DIN 439		
		No. 560111	Ref. No. —
	plain washer ID ø 4.3mm ED ø 9mm thickness 0.8mm SS Qty 20 pcs DIN 125A for thread M4		
		No. 560131	Ref. No. —
	hexagonal nut thread M4 H 3.2mm WS 7 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 20 pcs		


			
1			
No.	415665	Ref. No.	62-230086
description	heating element 2750/3250W 220/240V heating circuits 1 L 380mm W 110mm H 30mm thread M10x1 mounting distance 75mm tube ø 6.5mm connection M4 immersion heater 2 hole fixing		
spare parts for	415665		
	No.	510893	Ref. No. —
	 O-ring EPDM thickness 2.62mm ID ø 9.92mm Qty 1 pcs		
accessories for	415665		
	No.	510416	Ref. No. —
	 flat gasket fibre ED ø 19mm ID ø 10.5mm thickness 1.5mm for thread M10 Qty 1 pcs		
	No.	520231	Ref. No. —
	 nut thread M10x1 H 6mm WS 14 zinc-coated steel Qty 1 pcs		
	No.	521103	Ref. No. —
	 nut thread M4 H 3mm WS 7 brass Qty 20 pcs		
	No.	521104	Ref. No. —
	 washer ID ø 4.3mm ED ø 8mm thickness 0.5mm brass Qty 20 pcs for thread M4		
	No.	521129	Ref. No. —
	 nut thread M10 H 6mm SS WS 17 Qty 1 pcs DIN/ISO DIN 439		
	No.	560111	Ref. No. —
	 plain washer ID ø 4.3mm ED ø 9mm thickness 0.8mm SS Qty 20 pcs DIN 125A for thread M4		
	No.	560131	Ref. No. —
	 hexagonal nut thread M4 H 3.2mm WS 7 SS DIN/ISO DIN 934 / ISO 4032/8673 Qty 20 pcs		


			
1			
No.	418795	Ref. No.	602034
description	heating element 3000W 230V heating circuits 1 L 300mm W 70mm H 23mm thread M14x1.5 mounting distance 63mm tube ø 6.4mm		


heating elements for convection

			
1			
No.	693548	Ref. No.	76-21501005
description	flange suitable for convection heating element W 23mm mounting pos. outer length 210		

			
1			
No.	417675	Ref. No.	76-32001003
description	heating element 15000W 230V heating circuits 6 ID ø 635mm ED ø 650mm L 696mm H 200mm L1 23mm W1 156mm H1 35mm H2 165mm flange length 210mm flange width 24mm hole distance 31mm connection male faston 6.3mm connection length 80mm tube ø 6.3mm convection heating element hole ø 7mm mounting pos. outer rectangular flange		
spare parts for	417675		
	No.	512484	Ref. No. 76-51101009
	 gasket L 210mm W 24mm thickness 2mm for heating element		

			
1			
No.	417671	Ref. No.	76-30043519
description	heating element 18000W 230V heating circuits 6 ID ø 385mm ED ø 440mm L 460mm H 140mm L1 20mm W1 163mm H1 30mm H2 110mm thread M14x1.5 12 hole fixing connection male faston 6.3mm tube ø 6.3mm convection heating element		


			
1			
No.	417674	Ref. No.	76-30043520
description	heating element 18000W 400V heating circuits 6 thread M14x1.5 12 hole fixing connection male faston 6.3mm convection heating element		

			
1			
No.	415602	Ref. No.	49-182662
description	heating element 4800W 400V heating circuits 2 ID ø 183mm ED ø 213mm L 265mm H 33mm L1 50mm W1 31mm H1 13mm H2 20mm flange length 70mm flange width 22mm hole distance 56mm connection male faston 6.3mm connection length 28mm tube ø 6.3mm convection heating element mounting thread M5 rectangular flange with thread bolt		





1

No.	415601	Ref. No.	49-182522
description	heating element 6000W 400V heating circuits 1 ID ø 175mm ED ø 210mm L 240mm H 46mm L1 65mm W1 30mm H1 43mm H2 3mm flange length 70mm flange width 22mm hole distance 55mm connection male faston 6.3mm connection length 20mm tube ø 6.5mm convection heating element hole ø 5mm rectangular flange		
spare parts for	415601		
	No.	510368	Ref. No. —
	gasket L 70mm W 23.5mm hole ø 5mm hole distance 56mm FIBER thickness 2mm for heating element		




1

No.	415829	Ref. No.	72-65011540
description	heating element 7500W 230V heating circuits 3 ID ø 248mm ED ø 260mm L 287mm H 88mm L1 20mm W1 105mm H1 23mm H2 65mm flange length 142mm flange width 25mm hole distance 64mm connection M4 connection length 78mm convection heating element hole ø 5mm rectangular flange		
accessories for	415829		
	No.	531270	Ref. No. —
	gasket L 141mm W 22mm D1 ø 10mm D2 ø 9mm 9 holes graphite thickness 1mm suitable for UNOX		




1

No.	417689	Ref. No.	76-30043529
description	heating element 9000W 230V heating circuits 3 ID ø 385mm ED ø 400mm L 420mm H 125mm L1 20mm W1 160mm H1 20mm H2 105mm thread M14x1.5 6 hole fixing connection male faston 6.3mm tube ø 6.3mm mounting pos. inner convection heating element		





1

No.	417691	Ref. No.	76-30043528
description	heating element 9000W 230V heating circuits 3 ID ø 440mm ED ø 453mm L 470mm H 140mm L1 20mm W1 163mm H1 30mm H2 110mm thread M14x1.5 screw mounting connection male faston 6.3mm tube ø 6.5mm mounting pos. outer convection heating element		




1


No.	417692	Ref. No.	76-32001000
description	heating element 9000W 230V heating circuits 3 ID ø 445mm ED ø 458mm L 474mm H 130mm W1 156mm H1 33mm H2 97mm flange length 210mm flange width 25mm hole distance 31mm connection male faston 6.3mm connection length 80mm tube ø 6.5mm dry heating element hole ø 7.5mm mounting pos. inner rectangular flange		
accessories for	417692		
	No.	512484	Ref. No. 76-51101009
	gasket L 210mm W 24mm thickness 2mm for heating element		








1


No.	417693	Ref. No.	76-32001001
description	heating element 9000W 230V heating circuits 3 ID ø 504mm ED ø 516mm L 535mm H 130mm W1 156mm H1 35mm H2 95mm flange length 210mm flange width 25mm hole distance 31mm connection male faston 6.3mm connection length 80mm tube ø 6.5mm dry heating element hole ø 7.5mm mounting pos. outer rectangular flange L1 19mm		

			
1			
No.	417697	Ref. No.	76-30043507 76-30043524
description	heating element 9000W 230V heating circuits 4 ID ø 310mm ED ø 333mm L 410mm H 115mm L1 77mm W1 75mm H1 15mm H2 100mm thread M14x1.5 8 hole fixing connection male faston 6.3mm tube ø 8.5mm convection heating element		


			
1			
No.	417698	Ref. No.	76-30043531
description	heating element 9000W 400V heating circuits 3 ID ø 385mm ED ø 400mm L 402mm H 112mm L1 30mm W1 170mm H1 15mm H2 107mm thread M14x1.5 6 hole fixing connection male faston 6.3mm tube ø 6.5mm mounting pos. inner convection heating element		





1


No.	415239	Ref. No.	76-30043530
description	heating element 9000W 400V heating circuits 3 ID ø 440mm ED ø 453mm L 465mm H 140mm L1 15mm W1 150mm H1 30mm H2 110mm thread M14x1.5 6 hole fixing connection male faston 6.3mm tube ø 6.3mm mounting pos. outer convection heating element		
accessories for	415239		
	No.	510417	Ref. No. —
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs			
	No.	520228	Ref. No. 76-30041405
tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	No.	520230	Ref. No. 76-30041406
nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No. —
nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	550262	Ref. No. —
flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			


			
1			
No.	417679	Ref. No.	76-30041403
description	heating element 2000W 220V heating circuits 1 L 95mm W 520mm connection length 24mm connection male faston 6.3mm tube ø 6.3mm thread M14x1.5 2 hole fixing convection heating element mounting distance 514mm		

1



No.	415556	Ref. No.	76-30044300	
description	heating element 2000W 400V heating circuits 1 L 85mm W 530mm connection male faston 6.3mm tube ø 6.5mm thread M14x1.5 2 hole fixing convection heating element mounting distance 525mm			
accessories for	415556			
	No.	520228	Ref. No.	76-30041405
	tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14			
	No.	520230	Ref. No.	76-30041406
	nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs			
	No.	521101	Ref. No.	—
	nut thread M14x1.5 H 5mm WS 19 SS Qty 1 pcs			
	No.	550262	Ref. No.	—
	flat gasket copper ED ø 20mm ID ø 14mm thickness 2mm			

			
1			
No.	417681	Ref. No.	76-30041001 76-30041004
description	heating element 2500W 230V heating circuits 1 L 148mm W 534mm connection male faston 6.3mm tube ø 6.3mm thread M14x1.5 2 hole fixing convection heating element mounting distance 528mm		

			
1			
No.	417682	Ref. No.	76-30044301
description	heating element 2500W 400V heating circuits 1 L 148mm W 545mm connection male faston 6.3mm tube ø 6.3mm thread M14x1.5 2 hole fixing convection heating element mounting distance 539mm		



energy regulators

EGO

1-circuit





No.	380015	Ref. No.	49-183149
description	energy regulator 230V 13A single-circuit turn direction right shaft ø 6x4.6mm shaft L 23mm mounting thread M4 power release 6-100% no. 50.57021.010		

thermostats

bi-metal thermostats

safety bi-metal thermostats



No.	390233	Ref. No.	62-236039
description	bi-metal safety thermostat hole distance 24mm switch-off temp. 110°C 1NC 1-pole 16A connection F6.3 2 hole fixing without holder		
accessories for	390233		
	No.	504736	Ref. No. —
	bracket for contact thermostat		
	No.	550388	Ref. No. —
	bracket for contact thermostat mounting distance 24.5mm mounting ø 3.8		

bi-metal thermostats



No.	375160	Ref. No.	76-30140325
description	bi-metal thermostat hole distance mm switch-off temp. 110°C 1NC 1-pole 16A connection F6.3 M4		

control and safety thermostats

EGO

control thermostats

55.10/19_ series



No.	375548	Ref. No.	42-5061609772
description	thermostat t.max. 142°C temperature range fixed 142°C 1-pole 1CO 16A probe ø 4mm probe L 157mm capillary pipe 870mm capillary pipe isolated 870mm gland nut shaft ø 6x4.6mm shaft Lmm shaft position		



No.	390307	Ref. No.	62-236025 62-236037
description	thermostat t.max. 86°C temperature range 30-82°C 1-pole 1CO 16A probe ø 3mm probe L 156mm capillary pipe 600mm capillary pipe isolated 600mm gland nut shaft ø 6x4.6mm shaft L 8.5mm shaft position left rotation 180° outer switch eccentric 1/2"-3/4" contacts 1CO		



No.	390065	Ref. No.	62-236002
description	thermostat t.max. 90°C temperature range 30-90°C 1-pole 1CO 16A probe ø 11mm probe L 28mm capillary pipe 1000mm capillary pipe isolated 1000mm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper° rotation 270° screw-in probe probe thread M14x1		


55.13_series



No.	375086	Ref. No.	76-30140314
description	thermostat t.max. 180°C temperature range 60-180°C 1-pole 1CO 16A probe ø 6mm probe L 90mm capillary pipe 2400mm capillary pipe isolated 2300mm gland nut shaft ø 6x4.6mm shaft L 25mm shaft position upper rotation 270° probe material SS		



No.	390146	Ref. No.	49-176168
description	thermostat t.max. 280°C temperature range 50-280°C 1-pole 1NO 16A probe ø 3.1mm probe L 160mm capillary pipe 1230mm capillary pipe isolated 800mm gland nut shaft L 23mm shaft position upper rotation 270°		




No.	375087	Ref. No.	76-30140311
description	thermostat t.max. 300°C temperature range 50-300°C 1-pole 1CO 16A probe ø 3.03mm probe L 160mm capillary pipe 1130mm capillary pipe isolated 1103mm gland nut shaft L 23mm shaft position upper rotation 270°		



No.	375066	Ref. No.	76-30140166
description	thermostat t.max. 300°C temperature range 60-300°C 1-pole 1CO 16A probe ø 4mm probe L 98mm capillary pipe 1450mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 25mm shaft position upper special probe		



No.	375088	Ref. No.	76-30140318
description	thermostat t.max. 300°C temperature range 60-300°C 1-pole 1NO 16A probe ø 4mm probe L 100mm capillary pipe 830mm capillary pipe isolated 800mm gland nut shaft L 15mm shaft position upper rotation 270°		



No.	375145	Ref. No.	602865
description	thermostat t.max. 85°C temperature range 30-85°C 1-pole 1CO 16A probe ø 6mm probe L 113mm capillary pipe 2930mm capillary pipe isolated 500/300mm gland nut shaft L 23mm shaft position upper rotation 270°		

E-G-O



No.	375085	Ref. No.	76-30140312
description	thermostat t.max. 90°C temperature range 0-90°C 1-pole 1CO 16A probe ø 3.1mm probe L 247mm capillary pipe 1430mm capillary pipe isolated 1400mm gland nut shaft ø 6x4.6mm shaft L 18mm shaft position upper probe material SS		

55.34_series

E-G-O



No.	375097	Ref. No.	49-355637
description	thermostat t.max. 195°C temperature range 95-195°C 3-pole 3NO 16A probe ø 6mm probe L 117mm capillary pipe 1780mm capillary pipe isolated 1400mm gland nut M9x1 shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270°		

E-G-O



No.	375043	Ref. No.	01-214840
description	thermostat t.max. 200°C temperature range 65-200°C 3-pole 3NO 16A probe ø 6mm probe L 77mm capillary pipe 880mm capillary pipe isolated 800mm gland nut M9x1 shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270°		

E-G-O



No.	375144	Ref. No.	026213 602959
description	thermostat t.max. 52°C temperature range fixed 45/52°C 2-pole 2CO 16A probe ø 15mm probe L 22.5mm capillary pipe 2280mm capillary pipe isolatedmm gland nut shaft Lmm with knob probe		
For models:	B1100X, B650X		
accessories for	375144		
	No.	510165	Ref. No. —
	gasket for thermostat ED ø 27mm ID ø 11mm thickness 8.5mm		

E-G-O



No.	375161	Ref. No.	602715
description	thermostat t.max. 85°C temperature range 15-60/15-85°C 2-pole 2CO 16A probe ø 6mm probe L 113mm capillary pipe 2980mm capillary pipe isolated 300/300mm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270°		
For models:	B1100X, B650X		

safety thermostats

51._series

E-G-O



No.	375074	Ref. No.	76-30140322
description	safety thermostat switch-off temp. 365°C 2-pole 16A probe ø 4mm probe L 116mm capillary pipe 1170mm capillary pipe isolated 1100mm gland nut probe with special screwing screw connection M14x1		

E·G·O




1

No.	375090	Ref. No.	76-30140310
description	safety thermostat switch-off temp. 365°C 2-pole 16A probe ø 4mm probe L 120mm capillary pipe 1170mm capillary pipe isolated 1100mm gland nut probe SS		

55.12_ series

E·G·O



1

No.	375084	Ref. No.	76-30140300
description	safety thermostat switch-off temp. 135°C 1-pole 10A probe ø 6mm probe L 83mm capillary pipe 1440mm capillary pipe isolated 1360mm gland nut probe SS		

E·G·O




1

No.	375776	Ref. No.	76-30140300
description	safety thermostat switch-off temp. 135°C 1-pole 10A probe ø 6mm probe L 87mm capillary pipe 1440mm capillary pipe isolated 1400mm gland nut probe SS		

55.13_ series

E·G·O




1

No.	375149	Ref. No.	025836 602864
description	safety thermostat switch-off temp. 110°C 1-pole 16A probe ø 6mm probe L 98mm capillary pipe 2930mm capillary pipe isolated 500/500mm gland nut probe SS		
For models:	B1100X, B650X		

55.31_ series

E·G·O



1

No.	375102	Ref. No.	49-176174
description	safety thermostat switch-off temp. 230°C 3-pole 20A probe ø 6mm probe L 219mm capillary pipe 1730mm capillary pipe isolated 1400mm gland nut probe SS		

55.32_ series

E·G·O




1

No.	375045	Ref. No.	99-213149
description	safety thermostat switch-off temp. 315°C 3-pole 3NC 20A probe ø 6mm probe L 77mm capillary pipe 1490mm capillary pipe isolated 1100mm gland nut M9x1 probe SS		

56._ series

E-G-O







No.	375159	Ref. No.	76-30140326
description	safety thermostat switch-off temp. 365°C 1-pole 16A probe ø 4mm probe L 96mm capillary pipe 1160mm capillary pipe isolated 1100mm gland nut probe with special screwing screw connection M14x1		

control thermostats with operation switch


55.13._ series

E-G-O



No.	375406	Ref. No.	49-355693	
description	thermostat t.max. 110°C temperature range 30-110°C 1-pole 1CO 16A probe ø 6mm probe L 113mm capillary pipe 2380mm capillary pipe isolated 1700mm gland nut M9x1 shaft ø 6x4.6mm shaft L 18mm shaft position upper rotation 270° outer switch 2NO			
accessories for	375406			
	No.	110545	Ref. No.	—
knob dial plate silver thermostat t.max. 110°C 30-110°C rotation 310° ED ø 59mm ID ø 45.5mm				
	No.	112173	Ref. No.	—
knob universal ø 62mm black without adaptor/dial plate				
	No.	112311	Ref. No.	—
knob adapter shaft ø 6x4.6mm L 0mm with spring				

E-G-O



No.	375408	Ref. No.	49-174677
description	thermostat t.max. 320°C temperature range 50-320°C 1-pole 1NO 16A probe ø 3.03mm probe L 160mm capillary pipe 1150mm capillary pipe isolatedmm gland nut shaft ø 6x4.6mm shaft L 23mm shaft position upper rotation 270° outer switch 2NO		

IMIT / TEMPOMATIC / ARTHERMO

control thermostats





No.	390914	Ref. No.	63-120515
description	bi-metal thermostat t.max. 90°C temperature range 0-90°C 1-pole 1CO 10A probe ø 6.5mm probe L 97mm capillary pipe 1000mm capillary pipe isolated 950mm gland nut shaft ø 6x4.6mm shaft L 12mm shaft position upper rotation 270° with housing 250V		

CAEM

control thermostats



	No.	390672	Ref. No.	62-236042
description	thermostat t.max. 53°C temperature range fixed 53°C 1-pole 1CO 16A probe ø 9.5mm probe L 30mm capillary pipe 600mm capillary pipe isolated 540mm gland nut shaft Lmm screw-in probe probe thread M14x1			
spare parts for	390672			
	No.	510417	Ref. No.	—
flat gasket fibre ED ø 20mm ID ø 14mm thickness 2mm Qty 1 pcs				
	No.	550261	Ref. No.	—
nut thread M14x1 H 4mm WS 19 SS Qty 1 pcs				



No.	390686	Ref. No.	62-236043
description	thermostat t.max. 83°C temperature range°C 1-pole 1CO 20A probe ø 6mm probe L 90mm capillary pipe 630mm capillary pipe isolated 550mm gland nut shaft ømm shaft Lmm shaft position rotation 270° probe material copper		

TECASA

control thermostats



No.	376071	Ref. No.	42-5061633536
description	thermostat t.max. 300°C temperature range 30-300°C 1-pole 1NO 16A probe ø 4mm probe L 105mm capillary pipe 1600mm capillary pipe isolated 1250mm gland nut shaft ø 6x4.6mm shaft position° shaft position upper		

switches and momentary switches

rocker/momentary rocker switches

30x22mm



No.	301036	Ref. No.	026043
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

push/momentary push switches

30x22mm



No.	347178	Ref. No.	76-30161430
description	push switch mounting measurements 30x22mm black 2NO 250V 16A non-illuminated connection male faston 6.3mm ambient temperature max. 85/55°C protection IP40		



No.	301036	Ref. No.	026043
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

ø18.2mm



No.	346508	Ref. No.	76-30161352
description	momentary push switch mounting ø 18.2mm black 1NC/1NO 250V 2A connection screw ambient temperature max. 85°C protection IP40		

2 hole fixing



No.	345136	Ref. No.	76-30161405
description	switch combination triple green 240V 16A connection male faston 6.3mm ambient temperature max. 125°C protection IP44		

microswitches

lever actuated



No.	345257	Ref. No.	62-218002
description	microswitch with lever 250V 16A 1CO connection male faston 6.3mm L 29mm L1 33mm ambient temperature max. 120°C mounting distance 22mm actuating force: 130g lever length 31.5mm		



No.	345125	Ref. No.	76-30403011
description	microswitch with lever 250V 16A 1CO connection male faston 6.3mm ambient temperature max. 85°C mounting distance 25mm type C99ZP3 actuating force: 25g lever length 63.5mm		

roller-lever actuated

microswitches




No.	345216	Ref. No.	76-30160101
description	microswitch 250V 16A 1CO connection male faston 6.3mm ambient temperature max. 125°C mounting distance 22mm with handle with a switch blue/black		



pin-plunger actuated

M16



No.	345047	Ref. No.	76-30161400 76-30161403
description	microswitch with plunger thread M16x1 thread L 27mm 250V 5A 1NO connection cable stroke 5mm ambient temperature max. 85°C with cable type 837333 actuating force: 400g		
accessories for	345047		
	No.	698490	Ref. No. —
cover ED ø 17mm suitable for 345047			

position switches

ABB/FANAL

extended plungers



No.	345548	Ref. No.	026036
description	position switch		

MOELLER/EATON

extendable with actuators

extended plungers



No.	345549	Ref. No.	026034
description	position switch plastic 2NO 230V 3A L 75mm W 31mm H 33mm protection IP66 actuating force: 700g screw connection M20 mounting distance 22mm marking LS-S20A		
For models:	B1100X, B650X		

PIZZATO

FR series



No.	346624	Ref. No.	026035
description	position switch 2NO		

system switches (ROLD)



No.	345612	Ref. No.	62-480059
description	blank size 23x23mm black		



No.	345602	Ref. No.	62-226073
description	element holder double mounting measurements 28.5x52.6mm black for push buttons 23x23mm		



No.	345601	Ref. No.	62-299035
description	indicator lamp holder V ø 11mm		




No.	345606	Ref. No.	62-226071
description	momentary switch unit 2CO 250V 16A connection male faston 6.3mm		




No.	345613	Ref. No.	62-227030
description	push button size 23x23mm black drain pump		




No.	345607	Ref. No.	62-227025
description	push button size 23x23mm black main switch with lens		



			
1			
No.	345615	Ref. No.	62-227033
description	push button size 23x23mm black programme		

			
1			
No.	345609	Ref. No.	62-227027
description	push button size 23x23mm black START		

			
1			
No.	345608	Ref. No.	62-409001
description	rotary disc green/black disc ø 20.6mm		


			
1			
No.	345605	Ref. No.	62-208010
description	switch 2CO 250V 16A connection male faston 6.3mm		

float switches


			
1			
No.	400023	Ref. No.	76-30020407 76-30161201 76-84241202
description	float switch thread 3/8" 1CO ø 30mm L 170mm mounting ø 3/8"mm 250V 0.5A cable cable length 2000mm		
accessories for	400023		
	No.	506024	Ref. No.
	nut thread 3/8" H 6mm SS WS 22 Qty 1 pcs		

cam switches


2 operating positions

			
1			
No.	300240	Ref. No.	081629 840044
description	cam switch 2 operating positions 16A shaft ø 6x4.6mm shaft L 23mm 3-pole		


4 operating positions

			
1			
No.	300046	Ref. No.	76-30161600 76-30161630
description	cam switch 4 operating positions 5NO sequence 0-1-2-3 16A shaft ø 6x4.6mm shaft L 27mm connection male faston 6.3mm		

6 operating positions

			
1			
No.	300051	Ref. No.	76-30161631
description	cam switch 6 operating positions 2NO sequence 1-0-2-3-4-5 6A shaft ø 6x4.6mm shaft L 33mm connection male faston 6.3mm plastic		

operation switches

			
1			
No.	300361	Ref. No.	42-50609100223
description	cam switch 3 operating positions 4NO 16A sequence 0-1-2 shaft ø 6x4.6mm shaft L 23mm connection screw operation switch ceramic		

rotary switches

KRAUS & NAIMER

rotary switches



1

No.	347807	Ref. No.	151205
description	rotary switch 3 momentary switch-1-2 sets of contacts 4 type CA10-AT13F623 400V 20A shaft \varnothing 6x4.6mm shaft L 21mm connection screw marking 22/000100 D-47V4*02		

TELEMECANIQUE (Schneider Electric)



1

No.	300052	Ref. No.	76-30161500
description	rotary switch 2 1-2 sets of contacts 4 type D1155N 400V 12A connection screw		



1


No.	300047	Ref. No.	76-30161300
description	rotary switch 4 operating positions 9-pole		

magnetic switches

29x19mm



1




No.	345217	Ref. No.	76-30161415
description	magnetic switch L 29mm W 19mm 1NO 125V 0.5A P max. 10W connection cable cable length 2000mm		

32x15mm




1





No.	345109	Ref. No.	76-30161415
description	magnetic switch L 32mm W 15mm 1NO 250V 1A P max. 40W connection cable cable length 2000mm		

36x13mm



1



No.	345118 ¹	Ref. No.	62-211002
description	magnetic switch L 36mm W 13mm 1NO 250V 1A P max. 50W connection cable length 980mm		
accessories for	345118		
	No.	345399	Ref. No. —
magnet ø 3.3mm L 40mm H 8mm W 13mm hole distance 30mm M3			

¹with coded connector

accessories

magnets



1

No.	346514	Ref. No.	76-30161409
description	magnet ø 10mm L 40mm Hmm Wmm		



1

No.	345110	Ref. No.	76-30161412
description	magnet ømm L 25mm H 9mm W 15mm		

control equipment

JKN (Square D)

push buttons



1

No.	345174	Ref. No.	76-30161354
description	push button mounting measurements ø22mm clear reset		




1

No.	345173	Ref. No.	76-30161353
description	push button mounting measurements ø22mm white reset		

rotary switches



1

No.	110260	Ref. No.	76-30161310
description	rotary selector mounting measurements ø22mm		
accessories for	110260		
	No.	110261	Ref. No. —
rotary selector			

encoders and potentiometers




1


No.	300196	Ref. No.	76-30350600
description	potentiometer 0-150		




1

No.	300000	Ref. No.	76-30400268
description	potentiometer 5.2KOhm rotation 300° shaft ø 6x4.6mm with switch shaft L 18mm thread M10x0.75		

			
1			
No.	300058	Ref. No.	76-30400150
description	potentiometer 5KOhm rotation 270° shaft ø 6mm shaft L 27mm		

			
1			
No.	300059	Ref. No.	76-30400151
description	potentiometer 5KOhm rotation 310° shaft ø 6mm with switch shaft L 35mm		

			
1			
No.	400106	Ref. No.	76-88171303
description	pulser KOhm rotation 360° shaft ø 6mm type CPC		


lamps



indicator lights


indicator lights 2-piece (lens and indicator lamp)

indicator light lenses


ø10mm (type SRZ-3)

			
1			
No.	359125	Ref. No.	602401
description	indicator light housings mounting measurements ø10mm red round Qty 1 pcs		

indicator lamps for socket type SQ			
			
1			
No.	347476	Ref. No.	63-130196
description	indicator light 5V green connection cable 170mm		
accessories for	347476		
			
	No.	Ref. No.	
	359806		—
indicator light lens clear Qty 1 pcs ø 6mm			


indicator lamps for socket type SRZ / SDK / SDY / SFK			
			
1			
No.	359130	Ref. No.	62-216006
description	indicator lamp 230V clear connection male faston 6.3mm ø 8mm		


indicator lights 3-piece (housing, lens and bulb)


ø19.2mm			
			
1			
No.	359107	Ref. No.	01-212570
description	indicator light ø 19.2mm yellow socket E14		

lamps

light bulbs

			
1			
No.	359598	Ref. No.	76-30240300 76-30250306
description	light bulb socket Ba15d 230V 5-7W ø 16mm L 35mm		

			
1			
No.	359608	Ref. No.	76-30250304
description	light bulb socket E14 10/15W 230V ø 16mm L 51mm lens L 31mm Qty 1 pcs		

			
1			
No.	359597	Ref. No.	76-30240210
description	light bulb socket T10 24V 2W ø 10mm L 28mm		

neon light bulbs









			
1			
No.	359600	Ref. No.	76-30240300
description	neon light bulb socket E10 220V 0.35W clear ø 10mm L 28mm		
accessories for	359600		
			
	No.	Ref. No.	
	359060		—
lamp socket mounting measurements ø16.2mm socket E10 connection screw			
			
	No.	Ref. No.	
	359063		—
lamp socket mounting measurements ø19.2mm socket E14 connection screw			



Table continues overleaf

accessories for 359600				
	No.	359064	Ref. No.	—
lamp socket mounting measurements ø22.3mm socket E14 connection screw 250/380V ambient temperature at 1W 100°C ambient temperature at 2W 85°C				
	No.	359685	Ref. No.	—
lamp socket mounting measurements ø16.2mm socket E10				
	No.	359832	Ref. No.	—
lamp socket mounting measurements ø16.2mm socket Ba9s connection male faston 6.3mm				
	No.	359853	Ref. No.	—
lamp socket mounting measurements ø18.2mm socket Ba9s connection male faston 6.3mm				
	No.	359988	Ref. No.	—
lamp socket mounting measurements ø30.5mm 250V connection F6.3 temp.-resist. 55°C E14				


indicator lights (complete)


ø16mm


with screw socket

	No.	359835	Ref. No.	49-184120
description indicator light ø 16mm 230V green connection male faston 6.3mm				
accessories for 359835				
	No.	550559	Ref. No.	—
nut thread M16x1 H 5.5mm WS 19				


with plug-in socket


	No.	359166	Ref. No.	49-184118
description indicator light ø 16mm 230V white				

	No.	359197	Ref. No.	49-184124
description indicator light ø 16mm 400V red				


	No.	359198	Ref. No.	49-184125
description indicator light ø 16mm 400V white				


28.5x28.5mm


	No.	345610	Ref. No.	62-207007
description indicator light lens 23x23 orange operating				


	No.	345614	Ref. No.	62-410008
description indicator light lens orange heating				


miscellaneous


	No.	359886	Ref. No.	76-84307110
description indicator light 230V 15W socket Ba15d triple				

	No.	359066	Ref. No.	76-30240309
description indicator light mounting measurements 30x21mm green 230V				

	No.	359883	Ref. No.	76-30240309
description indicator light mounting measurements 30x21mm green 230V				

	No.	359884	Ref. No.	76-30240310
description indicator light mounting measurements 30x21mm red 230V				

	No.	359065	Ref. No.	76-30240310
description indicator light mounting measurements 30x21mm white 230V				

	No.	359887	Ref. No.	76-30230300
description lamp socket socket E10 mounting measurements ø21mm				



screw-on/push-on fit

neon light bulbs

1



No.	359600	Ref. No.	76-30240300
description	neon light bulb socket E10 220V 0.35W clear ø 10mm L 28mm		
accessories for	359600		
	No.	359060	Ref. No. —
	No.	359063	Ref. No. —
	No.	359064	Ref. No. —
	No.	359685	Ref. No. —
	No.	359832	Ref. No. —
	No.	359853	Ref. No. —
	No.	359988	Ref. No. —

light bulbs

for ovens

1



No.	359610	Ref. No.	76-30240200
description	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 47mm lens L 20mm for oven lamp type Philips		

for indicator lights

1



No.	359598	Ref. No.	76-30240300 76-30250306
description	light bulb socket Ba15d 230V 5-7W ø 16mm L 35mm		

1



No.	359608	Ref. No.	76-30250304
description	light bulb socket E14 10/15W 230V ø 16mm L 51mm lens L 31mm Qty 1 pcs		

1



No.	359597	Ref. No.	76-30240210
description	light bulb socket T10 24V 2W ø 10mm L 28mm		

halogen lamp

for socket G4 / G6.35 / G9

1



No.	359596	Ref. No.	76-30240201
description	halogen lamp socket G4 12V 10W temp.-resist. 500°C		

oven lamps

universal oven lamps

mounting diameter 35.5mm

1



No.	359720	Ref. No.	76-30230501
description	oven lamp mounting ø 35.5mm 230V 15W socket E14 temp.-resist. 300°C connection male faston 6.3mm hard glas		
spare parts for	359720		



No.	359701	Ref. No.	76-30230502 76-30230506
-----	--------	----------	----------------------------








No.	359705	Ref. No.	—
-----	--------	----------	---






No.	359721	Ref. No.	76-30250003 76-50120509 76-50120535
-----	--------	----------	---



No.	359740	Ref. No.	—
-----	--------	----------	---


			
No.	359701	Ref. No.	76-30230502 76-30230506
description	lamp socket socket E14 220-230V mounting ø 35.5mm connection male faston 6.3mm 15W		
accessories for	359701		
	No.	359705	Ref. No. —
oven lamp glass thr.ø 33.5mm ø 52mm hard glas temp.-resist. 350°C			
	No.	359709	Ref. No. —
oven lamp glass thr.ø 33.5mm ø 42mm hard glas temp.-resist. 350°C			
	No.	359721	Ref. No. 76-30250003 76-50120509 76-50120535
gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs			
	No.	359942	Ref. No. —
oven lamp glass thr.ø 33.5mm ø 41mm hard glas temp.-resist. 350°C			

			
No.	359723	Ref. No.	76-30250002 76-30250004
description	oven lamp glass thr.ø 33.5mm ø 51mm borosilicate glass temp.-resist. 550°C		
accessories for	359723		
	No.	359721	Ref. No. 76-30250003 76-50120509 76-50120535
gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs			

			
No.	359721	Ref. No.	76-30250003 76-50120509 76-50120535
description	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		


lamps

light bulbs

			
No.	359610	Ref. No.	76-30240200
description	light bulb t.max. 300°C socket E14 15W 230V ø 22mm L 47mm lens L 20mm for oven lamp type Philips		



halogen lamps



for socket G4 / G6.35 / G9

			
No.	359596	Ref. No.	76-30240201
description	halogen lamp socket G4 12V 10W temp.-resist. 500°C		

timers



programme timers

			
No.	360349	Ref. No.	61-238053
description	timer CDC 11803 engines 1 chambers 3 operation time 150s 230V shaft ømm shaft Lmm manif. no. 11803F1BEE000.0010 motor type M48R ATS type 11803F1 / 238046		
spare parts for	360349		
	No.	360673	Ref. No. —
motor kit pinion ø 6.8mm teeth 15 230V voltage AC 50/60Hz turn direction clockwise motor ø 48mm H 18.5mm motor type UDS-40NE1RNZ165 cable length 150mm with holder			

			
No.	360047	Ref. No.	63-120268
description	timer CDC 4905DV engines 2 chambers 5 operation time 4s / 150s 230V shaft ømm shaft Lmm manif. no. 4905DV / 360047 motor type M48L ATS		
spare parts for	360047		
	No.	360083	Ref. No. —
motor CDC pinion ø 4.9mm teeth 10 230V turn direction left motor ø 47mm H 19.3mm motor type M48L ATS for timer			





1

No.	360133	Ref. No.	62-238066
description	timer CDC 7804DV engines 2 chambers 4 operation time 60s / 20min 230V shaft ømm shaft Lmm manif. no. 7804DV / 360133 motor type M37RN/M37LN		
spare parts for	360133		
	No.	360119	Ref. No. —
motor CDC pinion ø 5.4mm teeth 12 230V turn direction right motor ø 37mm motor type M37RN for timer			
	No.	360131	Ref. No. —
motor CDC pinion ø 5.4mm teeth 12 230V turn direction left motor ø 37mm motor type M37LN for timer			



1

No.	360046	Ref. No.	63-120267
description	timer FIBER P25 engines 2 chambers 6 operation time 60s / 85s / 120s 230V shaft ømm shaft Lmm manif. no. P255J06JD58 motor type M51BJ0R6400 / M51BJ0L6400		
spare parts for	360046		
	No.	360673	Ref. No. —
motor kit pinion ø 6.8mm teeth 15 230V voltage AC 50/60Hz turn direction clockwise motor ø 48mm H 18.5mm motor type UDS-40NE1RNZ165 cable length 150mm with holder			
	No.	360674	Ref. No. —
motor kit pinion ø 6.8mm teeth 15 230V voltage AC 50/60Hz turn direction counterclockwise motor ø 48mm H 18.5mm motor type UDS40NE1RNZ165 cable length 150mm with holder			

digital timers



1

No.	379260	Ref. No.	541590
description	timer TEMPOMATIC K-400-2M time range 0-99min 230VAC 16A mounting measurements 66x50mm 1NO connection rear 1-pole front measurements 71.5x55mm		

electric timers





1

No.	350001	Ref. No.	76-30130109
description	timer 2CO at 250V 16A permanent position yes impulse electric shaft ø 6x4.6mm shaft L 22mm mounting distance 28mm connection rear 2-pole operation time 120min		



1

No.	350015	Ref. No.	76-30130101 76-30130109
description	timer MS65 without bell operation time 120min time spreadmin 1CO/1NO at 250V 16A permanent position yes impulse electric shaft ø 6x4.6mm shaft L 23mm mounting distance 28mm connection lateral 2-pole		
accessories for	350015		
	No.	110366	Ref. No. —
knob switch zero mark t.max. °C ø 44mm shaft ø 6x4.6mm shaft flat upper black			
	No.	111206	Ref. No. —
dial plate graduation 120min permanent position no rotation 10-300° ø 60mm timers knob ø 45mm			

with time spread





1


No.	350074	Ref. No.	76-30130104
description	timer MS65 operation time 120min time spread 30min 1CO/2NO/1NC at 250V 16A permanent position yes impulse electric shaft ø 6x4.6mm shaft L 22mm mounting distance 28mm connection lateral Invensys 4-pole shaft position lower°		

alarm devices

buzzers

1 			
No.	350053	Ref. No.	76-30060107
description	buzzer 12VAC connection male faston 3.2mm screw mounting buzzer		


1 			
No.	350050	Ref. No.	76-30060101
description	buzzer 230VAC connection male faston 6.3mm screw mounting thread M4 60dB		


1 			
No.	350091	Ref. No.	76-30060103
description	buzzer 24VAC connection male faston 6.3mm push-in 63dB		


contactors

BENEDIKT & JÄGER

power contactors


1 			
No.	381501	Ref. No.	76-30280509
description	power contactor resistive load 32A 230VAC (AC3/400V) 17A/7.5kW main contacts 3NO auxiliary contacts 1NC connection screw connection		


1 			
No.	382001	Ref. No.	76-30280517
description	power contactor resistive load 32A 230VAC (AC3/400V) 17A/7.5kW main contacts 4NO auxiliary contacts connection screw connection		

1 			
No.	381173	Ref. No.	76-30280101 76-30280123 76-30280511
description	power contactor resistive load 50A 230VAC (AC3/400V) 24A/11kW main contacts 3NO auxiliary contacts 1NO connection torx type K3-24B00 50/60Hz		

GENERAL ELECTRIC (AEG)

power contactors

1 			
No.	380445	Ref. No.	76-30280103 76-30280504 76-30280507 76-30280550
description	contactor resistive load 25A connection screw connection set		

1 			
No.	380239	Ref. No.	76-30280103 76-30280504 76-30280507 76-30280550
description	power contactor resistive load 20A 230VAC (AC3/400V) 8.4A/4kW main contacts 3NO auxiliary contacts 1NC connection screw connection type LS05 01A type AEG LS05 01A type GE MC1A 301A		



1

No.	380238	Ref. No.	76-30280100 76-30280502 76-30280506 76-30280551
description	power contactor resistive load 20A 230VAC (AC3/400V) 8.4A/4kW main contacts 3NO auxiliary contacts 1NO connection screw connection type LS0510A type AEG LS0510A type GE MC1A 310A		



1

No.	380245	Ref. No.	76-30280103 76-30280504 76-30280507 76-30280550
description	power contactor resistive load 25A 230VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NC connection screw connection type AEG LS4K 01A type GE CL00A 301 H 85mm		



1

No.	380244	Ref. No.	76-30280100 76-30280502 76-30280506 76-30280551
description	power contactor resistive load 25A 230VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NO connection screw connection type AEG LS4K 10A type GE CL00A 310		



1

No.	380261	Ref. No.	76-30280552
description	power contactor resistive load 32A 230VAC (AC3/400V) 17A/7.5kW main contacts 3NO auxiliary contacts 1NO connection screw connection type AEG LS7K 10A type GE CL02A 310		



1

No.	380265	Ref. No.	76-30280512
description	power contactor resistive load 60A 230VAC (AC3/400V) 32A/16kW main contacts 3NO auxiliary contacts 1NO connection screw connection type AEG LS15K 00A type GE CL04A 310 H 98mm L 87mm W 55mm		



1

No.	380396	Ref. No.	76-30280102 76-30280117 76-30280513
description	power contactor resistive load 60A 230VAC main contacts 3NO auxiliary contacts 1NO		



1

No.	380266	Ref. No.	76-30280102 76-30280117 76-30280513
description	power contactor resistive load 90A 230VAC (AC3/400V) 22kW main contacts 3NO connection screw type AEG LS22K 00A type GE CL06A 300		

auxiliary contacts



1

No.	380268	Ref. No.	76-30280153
description	auxiliary contact contacts 1NO for contactors CL+LS_K connection screw AC-12 10A type AEG HS07K 10 type GE BCLF 10		

motor protection circuit breakers



1

No.	380169	Ref. No.	76-30310101
description	motor protection circuit breaker		



1

No.	380170	Ref. No.	76-30310103
description	motor protection circuit breaker		

ISKRA (FANAL)

power contactors



1

No.	380212	Ref. No.	63-120461
description	power contactor resistive load 20A 230VAC (AC3/400V) 8.5A/5.5kW main contacts 3NO auxiliary contacts 1NC connection screw connection type Fanal K07M 01 type ISKRA DSL7 01		

auxiliary contactors



1

No.	380208	Ref. No.	025991
description	auxiliary contactor AC1 16A 230VAC AC15 4A contacts 2NO/2NC connection male faston 6.3mm type Fanal DSL7 22/FG type ISKRA K07CF 22		

MOELLER/EATON

power contactors

1

No.	381224	Ref. No.	76-30280104
description	power contactor resistive load 16A main contacts 4NO type DIL04-40 230V		



1

No.	380515	Ref. No.	76-30280100
description	power contactor resistive load 20A 230VAC (AC3/400V) 4kW main contacts 4		



1

No.	380171	Ref. No.	76-30280118
description	power contactor resistive load 20A 230VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NO connection screw connection type DILEM 10		



1

No.	380497	Ref. No.	76-30280100 76-30280502 76-30280506 76-30280551
description	power contactor resistive load 20A 230VAC (AC3/400V) 9A/4kW main contacts 4NO auxiliary contacts connection screw connection type DILEM 4		



1

No.	380167	Ref. No.	76-30280102 76-30280117 76-30280513
description	power contactor resistive load 66A 230VAC (AC3/400V) 50A/22kW main contacts 3NO auxiliary contacts 1NO connection screw connection type DILM 50		

motor protection circuit breakers



1

No.	380163	Ref. No.	76-30310108
description	motor protection circuit breaker type PKZM		

auxiliary contacts



1

No.	380175	Ref. No.	76-30280151
description	auxiliary contact contacts 1NO/1NC connection screw		

ABL SURSUM

motor protection circuit breakers



1

No.	380300	Ref. No.	76-30310105 76-30310106
description	motor protection circuit breaker type Mbs25-016 setting range 1-1.6A (AC3/400V) 0.55kW		
accessories for	380300		
	No.	380305	Ref. No. 76-30310099 76-30310102
	auxiliary contact contacts 1NO/1NC HMS1		



1

No.	380301	Ref. No.	76-30310107
description	motor protection circuit breaker type Mbs25-025 setting range 1.6-2.5A (AC3/400V) 1.1kW		



1

No.	380304	Ref. No.	76-30310108
description	motor protection circuit breaker type MS25-10 setting range 6.3-10A (AC3/400V) 4kW		

accessories



1

No.	380305	Ref. No.	76-30310099 76-30310102
description	auxiliary contact contacts 1NO/1NC HMS11		

TRIPUS (Eichhoff)

small relay switches



1

No.	380397	Ref. No.	76-30280601
description	small relay switch 24V main contacts 1NO/1NC connection Faston 6.3mm resistive load 16A		

miscellaneous

accessories

1

No.	380841	Ref. No.	76-30281001
description	conversion kit for contactor		

power contactors

1



No.	380165	Ref. No.	76-30280502 76-30280506 76-30280551
description	power contactor		

1


No.	380168	Ref. No.	76-30280103 76-30280504 76-30280507 76-30280550
description	power contactor		

solid state relays

CELDUC

1



No.	400105	Ref. No.	76-30280533 76-4000453P	
description	solid state relay CELDUC 2 phase 65A 400V 24VDC L 58mm W 45mm plug-in connection screw type 40.00.453			
accessories for	400105			
	No.	401794	Ref. No.	—
	connecting cable L 1440mm 4-pole suitable for RATIONAL			

relays


power relays

with bracket mounting



1

No.	380312	Ref. No.	62-239023 62-239024
description	power relays FINDER 230VAC 10A 3CO connection male faston 4.8mm bracket mounting dimensions 52x32.2x36.5mm manuf. no. 60.63.8.230.0000		



1

No.	380311	Ref. No.	62-239030
description	power relays Italiana Relè 230VAC 20A 1NC/1NO connection F6.3 bracket mounting manuf. no. A1B-230AC-FA		

level relays

GICAR



1

No.	400018	Ref. No.	01-213810
description	level relay 230V voltage AC connection F6.3 type RL30/3ES/F/G		

time relays

time relays



1

No.	380281	Ref. No.	76-30350401
description	time relay FINDER 82.11.0.240 time range 0.05s-10h 24-240VAC/24-48VDC 5A 1CO		



1

No.	380283	Ref. No.	76-30350402
description	time relay FINDER 82.41.0.240 time range 0.05s-10h 24-240VAC/24-48VDC 5A		



1

No.	380319	Ref. No.	76-30350453
description	time relay pickup-delayed 0.06-150s		



1

No.	380280	Ref. No.	76-30350401
description	time relay WIELAND NGZ11 time range 1.5-30s 24-240V AC/DC 5A connection grip connection		



1

No.	380282	Ref. No.	76-30350402
description	time relay WIELAND NGZ310 time range 1.5-30s 24-240V AC/DC 5A connection grip connection		



1

No.	379260	Ref. No.	541590
description	timer TEMPOMATIC K-400-2M time range 0-99min 230VAC 16A mounting measurements 66x50mm 1NO connection rear 1-pole front measurements 71.5x55mm		

transformers

open transformers

with plug connection



1

No.	400101	Ref. No.	76-30370240
description	transformer primary 200-260VAC secondary 4.2/14.4/11.5VAC 68.4VA		


encapsulated transformers


multiple connections



1

No.	400117	Ref. No.	76-30370204
description	transformer primary 200-230V secondary 11.5V 20VA 50/60Hz temperature restriction 131°C ambient temperature max. 60°C		


			
1			
No.	400102	Ref. No.	76-30370205
description	transformer primary 230VAC secondary 11.5VAC 10VA		

			
1			
No.	400118	Ref. No.	76-30370203
description	transformer primary 230VAC secondary 21VAC 35VA		

electronic controllers

miscellaneous


universal controllers


			
1			
No.	379020	Ref. No.	76-30140113 76-30140114
description	electronic controller Pt100 steam control		


probes


producer-specific probes


probes


			
1			
No.	381428	Ref. No.	76-30140151
description	temperature probe Pt100 cable silicone probe -100 up to 450°C cable -50 up to +180°C connection 2-wire thread M6 probe ø4x100mm cable length 1.5m		


			
1			
No.	381429	Ref. No.	76-30140156
description	temperature probe Pt100 cable silicone probe -100 up to 450°C cable -50 up to +180°C connection 2-wire thread probe ø3.2x100mm cable length 2.6m		


			
1			
No.	381427	Ref. No.	76-30140120 76-30140150 76-30140152
description	temperature probe Pt100 cable silicone probe -50 up to +250°C cable -50 up to +180°C connection 2-wire thread probe ø4x75mm cable length 1.7m		


			
1			
No.	381431	Ref. No.	76-30140165
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø1.5x100mm cable length 1.8m		

			
1			
No.	381430	Ref. No.	76-30141000
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø2x100mm cable length 0.25m		


			
1			
No.	381433	Ref. No.	76-30141003 76-30141005
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø2x100mm cable length 2.2m		

			
1			
No.	381424	Ref. No.	76-30140160 76-87201003
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø2x100mm cable length 2m		

			
1			
No.	381432	Ref. No.	76-30140161 76-30140166 76-87201002
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø2x40mm cable length 2.6m		

			
1			
No.	379425	Ref. No.	76-30140157
description	temperature probe thermocouple K (NiCr-Ni) cable silicone probe -50 up to 1150°C cable -50 up to +180°C connection 2-wire thread probe ø3x280mm cable length 2m		



core probes

			
1			
No.	381425	Ref. No.	76-30350604 76-30350605 76-30350607 76-30350608 76-30350623 76-30350703
description	core temperature probe Pt100 cable PTFE probe -40 up to +250°C cable -40 up to +250°C connection 2-wire probe ø3.2x100mm thread M12 cable length 2.8m handle ø 10mm handle length 80mm		



No.	381426	Ref. No.	76-30350700 76-30350701 76-30350709 76-30350710 76-30350713
description	core temperature probe thermocouple K (NiCr-Ni) cable PTFE probe -40 up to +250°C cable -40 up to +250°C connection 2-wire probe ø3.2x100mm thread M12 cable length 1.9m handle ø 10mm handle length 100mm		




No.	379792 ¹	Ref. No.	76-30350717
description	core temperature probe thermocouple K (NiCr-Ni) cable PTFE probe -40 up to +250°C cable -40 up to +250°C connection grip connection probe ø3.2x100mm thread M16x2 cable length 1.9m handle ø 10mm handle length 40mm		
accessories for	379792		
	No.	510179	Ref. No. —
	flat gasket fibre ED ø 18mm ID ø 13mm thickness 1.5mm Qty 1 pcs		
	No.	560519	Ref. No. —
	nut thread M12x1 H 5mm WS 17 SS Qty 1 pcs		

¹ multipoint probe

accessories

screw connections



No.	550366	Ref. No.	76-30140163
description	screw for thermocouple		
accessories for	550366		
	No.	550365	Ref. No. 76-30140162
	gasket for thermocouple		

miscellaneous



No.	550365	Ref. No.	76-30140162
description	gasket for thermocouple		

electronics

PCBs



No.	400084	Ref. No.	76-30402050
description	control PCB		



No.	400100	Ref. No.	76-30402040
description	control PCB		



No.	400098	Ref. No.	76-30403000 76-30403001
description	control PCB combi-steamer CD 101/CM 101 without EPROM		



No.	400103	Ref. No.	76-30403020
description	control PCB combi-steamer CM 61-202 L 460mm W 154mm 61-202		



1

No.	400099	Ref. No.	76-30403010
description	control PCB combi-steamer CM101		



1

No.	400107	Ref. No.	76-30402030
description	control PCB combi-steamer CM101 edition CM v. 4.91-97		



1

No.	403319	Ref. No.	76-30403210
description	control PCB combi-steamer CPC-Linie CM 61-202/G model since 10/1997		



1

No.	400109	Ref. No.	76-30400110
description	control PCB regulation and control electronics		



1

No.	401490	Ref. No.	76-30400152
description	keypad PCB		



1

No.	400129	Ref. No.	76-30020407 76-30161201 76-84241202
description	level relay		

1

No.	400111	Ref. No.	76-30020400 76-30020408 76-30402060 76-30403100
description	PCB		

1

No.	401483	Ref. No.	76-30350601
description	PCB		



1

No.	401493	Ref. No.	76-30400121
description	PCB		



1

No.	401479	Ref. No.	76-30171001 76-30402602 76-87201293
description	PCB combi-steamer		



1

No.	400077	Ref. No.	76-30350660
description	PCB combi-steamer CCD 101/201 core temperature		



1

No.	401487	Ref. No.	76-30403040
description	PCB combi-steamer CD 101/CM 101 with axial flow fan for fan motor		



1

No.	400110	Ref. No.	76-30020400 76-30020408 76-30402060 76-30403100
description	PCB combi-steamer level control		



1

No.	361366	Ref. No.	62-215001
description	PCB dishwasher 11F suitable for DB2 type DB2/EV1/EKP-M		



1

No.	400033	Ref. No.	76-30370218
description	PCB for gas valve 240V 28V		

central units



1

No.	401013	Ref. No.	76-30310201
description	motor break electronic 50/60Hz for RATIONAL breaking duration 4s type ETBO 10 (AC3/380V) 0.5kW		

solenoid valves

solenoid valves (water)

ELBI

straight




1

No.	373021	Ref. No.	76-30020330
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm output 1x 4.7l/min DN10 ELBI		


spare parts for	373021		
No.	370467	Ref. No.	—



solenoid valve filter suitable for ELBI

spare parts for	373021			
	No.	371263	Ref. No.	—
reducer ELBI type EATON (INVENSYS) flow rate 4.7l/min pressure range 0 up to 10bar tolerance ±15/25% grey				

1


No.	373017	Ref. No.	76-30020331
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm DN10 ELBI		
spare parts for	373017		
	No.	370467	Ref. No. —
solenoid valve filter suitable for ELBI			

1






No.	370246	Ref. No.	62-240010
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm t.max. 90°C ELBI plastic output B 0.5l/min flow regulating valve outlet B red		






MÜLLER

medium temperature: 90°C
duty cycle: 100%




1











No.	370004	Ref. No.	026334
description	solenoid valve double straight 230VAC inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER		
For models:	B1100X, B650X		
spare parts for	370004		
	No.	370129	Ref. No. —
solenoid valve body double straight inlet 3/4" outlet 14.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V			
	No.	371002	Ref. No. —
solenoid valve holder MÜLLER flange support			
	No.	371009	Ref. No. —
compression spring for solenoid coil			
	No.	371011	Ref. No. —
spare parts kit membrane with long star star high 8mm MÜLLER			
	No.	371017	Ref. No. —
solenoid coil MÜLLER 230VAC connection male faston 6.3mm			












spare parts for	370004			
	No.	371122	Ref. No.	—
solenoid valve filter ø 19mm H 10mm suitable for MÜLLER				
	No.	501161	Ref. No.	—
tap head for solenoid valve holder for solenoid coils				
accessories for	370004			
	No.	371010	Ref. No.	76-30020324
solenoid coil 230VAC connection with cable cable length 2000mm				
	No.	371037	Ref. No.	—
solenoid coil 24VAC 50/60Hz connection male faston 6.3mm				
	No.	371038	Ref. No.	—
solenoid coil 230VAC connection appliance plug				





with cable connection



1

No.	370065	Ref. No.	76-30020327	
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER cable length 2000mm			
spare parts for	370065			
	No.	370195	Ref. No.	76-30020314
solenoid valve body double straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V				
	No.	371002	Ref. No.	—
solenoid valve holder MÜLLER flange support				
	No.	371009	Ref. No.	—
compression spring for solenoid coil				
	No.	371010	Ref. No.	76-30020324
solenoid coil 230VAC connection with cable cable length 2000mm				
	No.	371011	Ref. No.	—
spare parts kit membrane with long star star high 8mm MÜLLER				
	No.	371122	Ref. No.	—
solenoid valve filter ø 19mm H 10mm suitable for MÜLLER				
	No.	501161	Ref. No.	—
tap head for solenoid valve holder for solenoid coils				
accessories for	370065			
	No.	371017	Ref. No.	—
solenoid coil MÜLLER 230VAC connection male faston 6.3mm				
	No.	371037	Ref. No.	—
solenoid coil 24VAC 50/60Hz connection male faston 6.3mm				
	No.	371038	Ref. No.	—
solenoid coil 230VAC connection appliance plug				


			
No.	370368	Ref. No.	76-30020305
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER cable length 2000mm		
spare parts for	370368		
	No.	Ref. No.	76-30020301
			solenoid valve body single straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V
	No.	Ref. No.	—
			solenoid valve holder MÜLLER flange support
	No.	Ref. No.	—
			compression spring for solenoid coil
	No.	Ref. No.	76-30020324
			solenoid coil 230VAC connection with cable cable length 2000mm
	No.	Ref. No.	—
			spare parts kit membrane with long star star hight 8mm MÜLLER
	No.	Ref. No.	—
			solenoid valve filter ø 19mm H 10mm suitable for MÜLLER
	No.	Ref. No.	—
			tap head for solenoid valve holder for solenoid coils
accessories for	370368		
	No.	Ref. No.	—
			solenoid coil MÜLLER 230VAC connection male faston 6.3mm
	No.	Ref. No.	—
			solenoid coil 24VAC 50/60Hz connection male faston 6.3mm
	No.	Ref. No.	—
			solenoid coil 230VAC connection appliance plug


			
No.	370006	Ref. No.	76-30020328
description	solenoid valve triple straight 230VAC inlet 3/4" outlet 12.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER cable length 2000mm		
spare parts for	370006		
	No.	Ref. No.	76-30020315
			solenoid valve body triple straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V
	No.	Ref. No.	—
			solenoid valve holder MÜLLER flange support
	No.	Ref. No.	—
			compression spring for solenoid coil


spare parts for	370006		
	No.	Ref. No.	76-30020324
			solenoid coil 230VAC connection with cable cable length 2000mm
	No.	Ref. No.	—
			spare parts kit membrane with long star star hight 8mm MÜLLER
	No.	Ref. No.	—
			solenoid valve filter ø 19mm H 10mm suitable for MÜLLER
	No.	Ref. No.	—
			tap head for solenoid valve holder for solenoid coils
accessories for	370006		
	No.	Ref. No.	—
			solenoid coil MÜLLER 230VAC connection male faston 6.3mm
	No.	Ref. No.	—
			solenoid coil 24VAC 50/60Hz connection male faston 6.3mm
	No.	Ref. No.	—
			solenoid coil 230VAC connection appliance plug

spare parts and accessories

valve bodies

			
No.	370195	Ref. No.	76-30020314
description	solenoid valve body double straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V		

			
No.	370133	Ref. No.	76-30020301
description	solenoid valve body single straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V		

			
No.	370132	Ref. No.	76-30020315
description	solenoid valve body triple straight inlet 3/4" outlet 11.5mm DN10 t.max. 90°C duty cycle 100% MÜLLER 230V		

solenoid coils


No.	371010	Ref. No.	76-30020324
description	solenoid coil 230VAC connection with cable cable length 2000mm		

ROBERTSHAW/INVENSYS

medium temperature: 90°C 90°C 60°C
ambient temperature: 60°C 25°C 60°C
duty cycle: 40% 100% 100%



No.	370371	Ref. No.	76-30020304
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS) cable length 2000mm		



No.	370370	Ref. No.	76-30020305
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS) cable length 2000mm		



No.	370372	Ref. No.	76-30020311
description	solenoid valve triple straight 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS) cable length 2000mm		

with coded terminal


No.	370269	Ref. No.	76-30020330
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS)		



No.	370268	Ref. No.	76-30020331
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm DN10 EATON (INVENSYS)		

TP


No.	370017	Ref. No.	62-240011
description	solenoid valve single straight 230VAC inlet 3/4" outlet 11.5mm DN10 TP p max 10bar		

spare parts for 370017


No.	371013	Ref. No.	—
description	solenoid coil TP 230VAC 50/60Hz		

accessories for 370017


No.	371220	Ref. No.	—
description	reducer TP flow rate 3l/min red tolerance ±15%		



No.	371221	Ref. No.	—
description	reducer TP flow rate 5.5l/min yellow tolerance ±15%		



No.	371222	Ref. No.	—
description	reducer TP flow rate 6l/min grey tolerance ±15%		



No.	371223	Ref. No.	—
description	reducer TP flow rate 10l/min white tolerance ±15%		



No.	371224	Ref. No.	—
description	reducer TP flow rate 12l/min bronze tolerance ±15%		



No.	371225	Ref. No.	—
description	reducer TP flow rate 16l/min light brown tolerance ±15%		



No.	371226	Ref. No.	—
description	reducer TP flow rate 20l/min red tolerance ±15%		



No.	371230	Ref. No.	—
description	reducer TP flow rate 0.25l/min red tolerance ±25%		



No.	371231	Ref. No.	—
description	reducer TP flow rate 0.35l/min violet tolerance ±25%		



No.	371232	Ref. No.	—
description	reducer TP flow rate 0.5l/min orange tolerance ±25%		



No.	371233	Ref. No.	—
description	reducer TP flow rate 0.8l/min white tolerance ±25%		



No.	371234	Ref. No.	—
description	reducer TP flow rate 1l/min light blue tolerance ±25%		








No.	371235	Ref. No.	—
description	reducer TP flow rate 1.2l/min brown tolerance ±25%		




No.	371236	Ref. No.	—
description	reducer TP flow rate 1.5l/min light brown tolerance ±25%		

Table continues overleaf








accessories for 370017				
	No.	371237	Ref. No.	—
reducer TP flow rate 2.5l/min yellow tolerance $\pm 25\%$				
	No.	371238	Ref. No.	—
reducer TP flow rate 3.4l/min dark green tolerance $\pm 25\%$				
	No.	371239	Ref. No.	—
reducer TP flow rate 5l/min black tolerance $\pm 25\%$				
	No.	371240	Ref. No.	—
reducer TP flow rate 8l/min blue tolerance $\pm 20\%$				



componenti per elettrodomestici



1

No.	370018	Ref. No.	76-30020331	
description solenoid valve single straight 230VAC inlet 3/4" outlet 14mm DN10 TP				
spare parts for 370018				
	No.	371013	Ref. No.	—
solenoid coil TP 230VAC 50/60Hz				
accessories for 370018				
	No.	371220	Ref. No.	—
reducer TP flow rate 3l/min red tolerance ±15%				
	No.	371221	Ref. No.	—
reducer TP flow rate 5.5l/min yellow tolerance ±15%				
	No.	371222	Ref. No.	—
reducer TP flow rate 6l/min grey tolerance ±15%				
	No.	371223	Ref. No.	—
reducer TP flow rate 10l/min white tolerance ±15%				
	No.	371224	Ref. No.	—
reducer TP flow rate 12l/min bronze tolerance ±15%				
	No.	371225	Ref. No.	—
reducer TP flow rate 16l/min light brown tolerance ±15%				
	No.	371226	Ref. No.	—
reducer TP flow rate 20l/min red tolerance ±15%				
	No.	371230	Ref. No.	—
reducer TP flow rate 0.25l/min red tolerance ±25%				
	No.	371231	Ref. No.	—
reducer TP flow rate 0.35l/min violet tolerance ±25%				
	No.	371232	Ref. No.	—
reducer TP flow rate 0.5l/min orange tolerance ±25%				
	No.	371233	Ref. No.	—
reducer TP flow rate 0.8l/min white toleran				

accessories for 370018				
	No.	371234	Ref. No.	—
reducer TP flow rate 1l/min light blue tolerance $\pm 25\%$				
	No.	371235	Ref. No.	—
reducer TP flow rate 1.2l/min brown tolerance $\pm 25\%$				
	No.	371236	Ref. No.	—
reducer TP flow rate 1.5l/min light brown tolerance $\pm 25\%$				
	No.	371237	Ref. No.	—
reducer TP flow rate 2.5l/min yellow tolerance $\pm 25\%$				
	No.	371238	Ref. No.	—
reducer TP flow rate 3.4l/min dark green tolerance $\pm 25\%$				
	No.	371239	Ref. No.	—
reducer TP flow rate 5l/min black tolerance $\pm 25\%$				
	No.	371240	Ref. No.	—
reducer TP flow rate 8l/min blue tolerance $\pm 20\%$				

Solenoid valve - accessories

filters



1

No.	371323	Ref. No.	76-19000202
description solenoid valve filter \varnothing 19.5mm H 10.5mm suitable for RATIONAL coarse			

pressure switches

for warewashing


 \varnothing 58mm with male faston 6.3mm

with connection horizontal




1


No.	541003	Ref. No.	62-224003
description pressure control pressure range 55/35mbar connection 6mm \varnothing 58mm pressure connection horizontal warewashing pressure connection \varnothing 6mm			

			
1			
No.	541106	Ref. No.	62-224005
description	pressure control pressure range 90/56mbar connection 6mm ø 58mm pressure connection horizontal warewashing pressure connection ø 6mm		


for steam control


			
1			
No.	541016	Ref. No.	49-176197
description	pressure control ø 45mm pressure range 480/430mbar pressure connection vertical steam control pressure range 0.48/0.43bar connection 1/4" pressure connection 1/4"		

for combi-steamers



			
1			
No.	345218	Ref. No.	76-30171002
description	pressure control pressure range 0-3mbar connection 6mm pressure connection 6mm		

electrodes

			
1			
No.	400021	Ref. No.	76-30020401
description	level electrode PG9 total length 110mm probe L 70/47/24mm insulated probe length 62/38/16mm with 3 probes connection grip connection		




1

No.	400022	Ref. No.	76-30020402	
description	level electrode PG9 total length 135mm probe L 89/59/28mm insulated probe length 80mm with 3 probes connection grip connection			
accessories for	400022			
<div>  </div>	No.	379729	Ref. No.	—
	connection cable L 1230mm 4-pole for level electrode plug type coded			
<div>  </div>	No.	550574	Ref. No.	—
	nut thread PG9 H 3mm WS 28 nickel-plated brass Qty 1 pcs mounting ømm cable ømm			

flow meters and flow sensors

flow sensors



			
1			
No.	402256	Ref. No.	76-30171050
description	flow sensor inlet ø 10mm outlet ø 10mm L 110mm flow rate 1-25l/min		

fans

axial fans

import

1


No.	601080 ¹	Ref. No.	76-31011008	
description	axial fan L 119mm W 119mm H 38mm 230VAC 50/60Hz 23/20W bearing ball bearing connection male faston 2.8mm metal ADDA fan wheel ø 110mm temp.-resist. 70°C			
accessories for	601080			
	No.	550898	Ref. No.	—
	connecting cable cable length 2000mm connection F 2.8 connection distance 7.9mm for axial flow fan			
	No.	692519	Ref. No.	—
	guard L 120mm W 120mm plastic			

¹with ball bearings

cross flow fans

COPREL


with moulded coils

			
1			
No.	601456	Ref. No.	49-178463
description	cross flow fan roller ø 45mm roller length 180mm laminated core thickness 15mm motor position right 230V/50Hz 26W universal bearing silicone connection male faston 6.3mm -30 up to +100°C 230V 50/60Hz		


hot air motors




No.	510588	Ref. No.	76-20160875
description	counterflange for fan motor ED ø 60mm int. ø 1 32mm int. ø 2 26mm thickness 3mm steel		




No.	500158	Ref. No.	76-31001002
description	fan motor 200-240/346-415V 3 phase 50/60Hz 0.4kW 1400/1700rpm speeds 1 L1 160mm L2 30mm L3 35mm M10R IT 2.0/1.15A power input 560W at 50Hz 200-240/346-415V at 60Hz 200-277/346-480V at 50Hz 1400rpm at 60Hz 1700rpm type L7Cw4D-226 no. WN D1 ø 17mm D2 ø 13mm		




No.	500100	Ref. No.	76-30010400 76-30010426
description	fan motor 220-240/380-415V 3 phase 50/60Hz 0.25kW 1400rpm speeds 1 L1 150mm L2 32mm L3 40mm M10R IT at 50Hz 1400rpm at 60Hz 1700rpm type L7Aw4D-099 no. X3 D1 ø 17mm D2 ø 13mm mounting distance 180mm		




No.	500167	Ref. No.	76-31001021
description	fan motor 220-240/380-415V 3 phase 50Hz 0.45kW 1400rpm speeds 1 L1 150mm L2 24mm L3 35mm M10R IT 1.1/1.9A power input 650W at 50Hz 1400rpm type L9Cw4D1-304 no. X7 D1 ø 17mm D2 ø 13mm		




No.	601310	Ref. No.	76-30010441
description	fan motor 220-240V 1 phase 50/60Hz 0.16kW 1420/1720rpm speeds 1 L1 140mm L2 40mm L3 37mm M10R IT 1.3A suitable capacitor 16µF/280V power input 260W Cos(φ) 0.96 at 50Hz 1420rpm at 60Hz 1720rpm type L7zAw4D-199 no. W5 D1 ø 17mm D2 ø 13mm		



No.	500159	Ref. No.	76-31001000
description	fan motor 380-415/380-460V 3 phase 50Hz 0.04/0.37kW 710/1350rpm speeds 2 L1 170mm L2 30mm L3 35mm M10R IT 0.3/0.85A power input 100/550W at 50Hz 380-415V at 60Hz 380-460V at 50Hz 710/1350rpm at 60Hz 850/1680rpm Y/YY type L7rw84D-208 no. WN D1 ø 17mm D2 ø 13mm		



No.	500162	Ref. No.	76-31001020
description	fan motor 380-415V 3 phase 50Hz 0.08/0.45kW 700/1400rpm speeds 2 L1 147mm L2 35mm L3 35mm ø 125mm M10R IT 0.4/1.15A at 50Hz 700/1400rpm Y/YY type L9xw84D-393 no. V2 D1 ø 17mm D2 ø 13mm		


spare parts for	500162		
	No.	601730	Ref. No. —
fan wheel for motor cooling ED ø 180mm H 20mm ID ø 20mm			


No.	601312	Ref. No.	76-20120510
description	fan wheel		

			
1			
No.	601049	Ref. No.	76-20120602
description	fan wheel D1 ø 280mm H1 125mm blades 12 D2 ø 11mm D3 ø 16mm H2 37mm		

			
1			
No.	601311	Ref. No.	76-20120500
description	fan wheel D1 ø 350mm H1 125mm blades 12 D2 ø 13mm D3 ø 16.5mm H2 37mm		


			
1			
No.	601322	Ref. No.	76-20120507
description	fan wheel D1 ø 350mm H1 125mm blades 12 D2 ø 13mm D3 ø 16mm H2 37mm		


			
1			
No.	510587	Ref. No.	76-20160876
description	flange for fan motor ED ø 60mm int. ø 1 24mm int. ø 2 18.5mm thickness 3mm steel		

			
1			
No.	510573	Ref. No.	76-50010207
description	shaft seal ID ø 17mm ED ø 29mm thickness 4.5mm		

hot air fans

HANNING

			
1			
No.	601149	Ref. No.	49-174193
description	fan motor 230V L1 72mm L2 69mm L4 130mm HANNING type EMB-30-028		

			
1			
No.	601008	Ref. No.	49-174192
description	hot air fan 230V 45W L1 72mm L2 28mm L4 130mm HANNING type EMB-30-027 M6L		

miscellaneous

1

No.

601175

Ref. No.

AN72-65060030

description

hot air fan 230V 47W 50/60Hz L1 73mm L2 28mm L3 29mm L4 87mm fan wheel ø 154mm FIME type C30X0L13/05CLH



accessories

fan wheels for hot air fans



No.	601196	Ref. No.	49-788878002
description	fan wheel ø 150mm W 20mm shaft intake ø 6x5mm blades 6		

radial fans



No.	601114	Ref. No.	76-31011011
description	radial fan 24V voltage AC 50Hz 20W H1 141mm L1 130mm D1 ø 27mm W1 86mm W2 23mm H2 42.5mm W3 75.5mm H3 83mm gas burner		

accessories universal



No.	401013	Ref. No.	76-30310201
description	motor break electronic 50/60Hz for RATIONAL breaking duration 4s type ETBO 10 (AC3/380V) 0.5kW		

motors

gear motors

for ovens

for flues



No.	361999	Ref. No.	76-31011010
description	gear motor CROUZET type 82841042 12V voltage DC shaft ø 4mm L 65mm W 50mm H 51mm for oven		



No.	361565	Ref. No.	76-31011007
description	gear motor CROUZET type 82841056 24V voltage DCHz 4.2rpm shaft ø 4mm L 51mm W 66mm H 51mm		



No.	361564	Ref. No.	76-31011001
description	gear motor ESCAP type 22N28210E 24V shaft ø 5mm L 50mm W 32mm H 51mm for sliding valve		

motors

for combi-steamers



No.	401480	Ref. No.	76-31011002 76-86801006
description	motor for humidity measuring		

pumps

wash and rinse pumps

ALBA (C&A)

pumps



1

No.	500085	Ref. No.	602252
description	pump inlet ø 45mm outlet ø 40mm type C1001 230V 50Hz 1 phase 0.55kW 0.75HP L 200mm rotation direction right capacitor 16µF ALBA PUMPS (C&A)		
spare parts for	500085		
	No.	365014	Ref. No. —
	operating capacitor capacity 12.5µF 450V tolerance 5%Hz ambient temperature max. -25 to +85°C ø 35mm L 70mm M8 plastic connection male faston 6.3mm 45S.C3DS.12.5 protection		
	No.	509021	Ref. No. —
	impellor ø 102mm H 32mm shaft intake ø 9/8mm rotation direction right		
	No.	510693	Ref. No. 61-141002
	mechanical shaft seal for shaft ø 12mm slide ring ext. ø 24mm slide ring H 15.5mm slide ring int. ø 11mm counter ring mounting ø 24mm height counter ring 8mm counter ring int. ø 13.5mm		
	No.	521531	Ref. No. —
	pump cover ALBA PUMPS (C&A) inlet ø 45mm outlet ø 40mm turn direction right ø 153mm ID ø 127mm inner height 24mm		
	No.	521709	Ref. No. —
	O-ring EPDM thickness 3mm ID ø 126mm Qty 1 pcs		

FIR

pumps



1

No.	500558	Ref. No.	64-33542
description	pump inlet ø 33mm outlet ø 30/28mm type B266H1500 230V 50Hz 1 phase 0.22kW 0.3HP L 195mm rotation direction right capacitor 5µF FIR		
spare parts for	500558		
	No.	365017	Ref. No. —
	operating capacitor capacity 5µF 450V tolerance 5% 50/60Hz ambient temperature max. -25 to +85°C ø 28mm L 54mm M8 plastic connection male faston 6.3mm 16.10.08 protection		
	No.	510693	Ref. No. 61-141002
	mechanical shaft seal for shaft ø 12mm slide ring ext. ø 24mm slide ring H 15.5mm slide ring int. ø 11mm counter ring mounting ø 24mm height counter ring 8mm counter ring int. ø 13.5mm		
	No.	521545	Ref. No. —
	pump cover FIR type B226H inlet ø 33mm outlet ø 30/28mm		
	No.	521565	Ref. No. —
	pump cover gasket pump type B226H		
	No.	521566	Ref. No. —
	impellor ø 80mm H 15mm M7L pump type B226H		









1

No.	500127	Ref. No.	63-100399
description	pump inlet ø 37mm outlet ø 41mm type 4247.1900 230V 50Hz 1 phase 0.44kW 0.6HP L 200mm rotation direction right capacitor 10µF FIR		
spare parts for	500127		
	No. 365015	Ref. No.	—
operating capacitor capacity 10µF 400V tolerance 5%Hz ambient temperature max. -25 to +85°C ø 35.5mm L 59mm M8 plastic connection male faston 6.3mm protection			
	No. 510608	Ref. No.	—
impeller ø 93mm H 32mm shaft intake ø 9/8mm blades 6 inner height 11mm			
	No. 510692	Ref. No.	151021-2
mechanical shaft seal for shaft ø 11mm slide ring ext. ø 24mm slide ring H 13mm counter ring mounting ø 26mm height counter ring 8mm counter ring int. ø 14mm			
	No. 521505	Ref. No.	—
pump cover FIR inlet ø 37mm outlet ø 40mm turn direction right ø 160mm ID ø 125mm inner height 25mm			
	No. 521702	Ref. No.	151021-3
pump cover gasket thickness 3.5x4.5mm Qty 1 pcs			



1

No.	500058	Ref. No.	63-100717
description	pump inlet ø 63mm outlet ø 53mm type 2241.2500 230/400V 50Hz 3 phase 0.89kW 1.2HP L 305mm rotation direction left FIR		
spare parts for	500058		
	No. 510531	Ref. No.	—
pump cover FIR inlet ø 63mm outlet ø 53mm auxiliary pressure connection M16x1.5mm supporting pressure open turn direction left ø 185mm ID ø 150mm inner height 37mm			
	No. 510693	Ref. No.	61-141002
mechanical shaft seal for shaft ø 12mm slide ring ext. ø 24mm slide ring H 15.5mm slide ring int. ø 11mm counter ring mounting ø 24mm height counter ring 8mm counter ring int. ø 13.5mm			
	No. 510834	Ref. No.	63-631667
impeller ø 110mm H 29mm thread M8R suitable for FIR			
	No. 524416	Ref. No.	—
pump cover gasket thickness 4x4mm Qty 1 pcs			
accessories for	500058		
	No. 504329	Ref. No.	—
blind plug H 17.5mm thread M16x1.5 plastic WS 22 for pump			
	No. 524046	Ref. No.	—
vibration damper L 40mm W 25mm H 25mm for pump			

LGB


1

No.	500480	Ref. No.	63-100802
description	pump inlet ø 28mm outlet ø 28mm type ZF131DX 230V 50Hz 1 phase 0.29kW 0.4HP L 195mm rotation direction left capacitor 6.3µF LGB		
spare parts for	500480		
	No.	510690	Ref. No. —
mechanical shaft seal for shaft ø 8mm ED ø 24mm mounting ø 24/26mm			
	No.	521083	Ref. No. —
impellor ø 73mm H 13mm thread M7R blades 3 metal			
	No.	521084	Ref. No. —
pump cover LGB inlet ø 28mm outlet ø 25mm auxiliary pressure connection 13mm pump type ZF131DX ID ø 78mm			
	No.	528800	Ref. No. —
O-ring EPDM thickness 2.62mm ID ø 75.87mm Qty 1 pcs			
accessories for	500480		
	No.	365012	Ref. No. 400491 63-631216
operating capacitor capacity 6.3µF 450V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 30mm L 61mm M8 plastic connection male faston 6.3mm protection			



1

No.	500156	Ref. No.	62-130109
description	pump inlet ø 50mm outlet ø 50mm type ZF400SX 230V 50Hz 1 phase 0.6kW 0.8HP L 210mm rotation direction right capacitor 16µF LGB		
For models:	TX312		
spare parts for	500156		
	No.	509020	Ref. No. —
impellor ø 104mm H 25mm M8L			
	No.	510703	Ref. No. —
mechanical shaft seal for shaft ø 13mm slide ring H 13mm height counter ring 5.5mm ED ø 26mm			
	No.	521548	Ref. No. —
pump cover LGB inlet ø 50mm outlet ø 50mm			
	No.	521734	Ref. No. —
pump cover bottom part			
	No.	523509	Ref. No. —
deep-groove ball bearing type 6201-2RS shaft ø 12mm ED ø 32mm W 10mm with sealing discs deep-groove ball bearing DIN 625-1			
	No.	532623	Ref. No. —
O-ring EPDM thickness 2.62mm ID ø 120.32mm Qty 1 pcs			
accessories for	500156		
	No.	365021	Ref. No. —
operating capacitor capacity 16µF 425V tolerance 5% 50/60Hz ambient temperature max. -25 to +85°C ø 35mm L 73mm single M8 plastic connection male faston 6.3mm 416.10.99 protection			

OLYMPIA

pumps



1

No.	500003	Ref. No.	62-130008
description	pump inlet ø 45mm outlet ø 32mm type T30 230V 50Hz 1 phase 0.29kW 0.39HP L 190mm rotation direction right capacitor 8µF OLYMPIA		
spare parts for	500003		
	No.	365013	Ref. No. 62-206004
	operating capacitor capacity 8µF 400V tolerance 5%Hz ambient temperature max. -25 to +85°C ø 31.5mm L 55mm M8 plastic connection male faston 6.3mm protection		
	No.	510512	Ref. No. 62-116021
	pump cover OLYMPIA inlet ø 45mm outlet ø 31mm outlet 2 ø 24 turn direction right ø 130mm ID ø 124mm inner height 20mm		
	No.	510554	Ref. No. —
	O-ring EPDM thickness 2mm ID ø 120mm Qty 1 pcs		
	No.	510615	Ref. No. 61-124006
	impeller ø 90mm H 22mm rotation direction right thread M10L blades 4		
	No.	510693	Ref. No. 61-141002
	mechanical shaft seal for shaft ø 12mm slide ring ext. ø 24mm slide ring H 15.5mm slide ring int. ø 11mm counter ring mounting ø 24mm height counter ring 8mm counter ring int. ø 13.5mm		

drain pumps

ASKOLL




1

No.	500214	Ref. No.	62-130105
description	drain pump inlet ø 30mm outlet ø 22mm 230/240V 30W 50Hz ASKOLL type R113		

GRE




1

No.	500961	Ref. No.	63-100342
description	drain pump inlet ø 30mm outlet ø 23mm 100W 230V 50Hz GRE		
accessories for	500961		
	No.	524719	Ref. No. —
	formed hose hose ext. ø 40mm hose int. ø 30mm L 65mm warewashing black Qty 1		

HANNING



1

No.	500044	Ref. No.	76-30021000
description	drain pump inlet ø 30mm outlet ø 24mm 230V 100W 50Hz HANNING type BE28B4-017		
spare parts for	500044		
	No.	510168	Ref. No. —
	fan wheel shaft intake ø 5mm ø 62mm H 14mm		

booster pumps II

accessories



1

No.	365012	Ref. No.	400491 63-631216
description	operating capacitor capacity 6.3μF 450V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 30mm L 61mm M8 plastic connection male faston 6.3mm protection		

vibration pumps



1

No.	500580	Ref. No.	76-30021003
description	vibration pump 230V 60W 50/60Hz inlet ø 7 outlet ø 1/8" IT CEME type E512 with accessories duty cycle 1/2 ambient temperature max. 60°C medium temp max. 35°C overheating protection 110°C CleanJet		

pumps for ice machines



1

No.	500200	Ref. No.	151033
description	pump GRE 100W 230V 50Hz inlet ø 24mm outlet ø 23mm L 145mm rotation direction right		

condensators & interference suppression filters

operating capacitors

plastic



1

No.	365012	Ref. No.	400491 63-631216
description	operating capacitor capacity 6.3μF 450V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 30mm L 61mm M8 plastic connection male faston 6.3mm protection		



1

No.	365013	Ref. No.	62-206004
description	operating capacitor capacity 8μF 400V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 31.5mm L 55mm M8 plastic connection male faston 6.3mm protection		

filters

interference suppression filters



1

No.	365217	Ref. No.	76-31021000
description	interference suppression filter capacity 1.5μF 250V for combi-steamer CPC-Linie 61-202		



1

No.	365108	Ref. No.	76-30010455
description	interference suppression filter type 3001.0455 250/440V 50/60Hz conductor 3 with E connection male faston 6.3mm L 52mm ø 60mm Hmm Wmm M8 aluminium Qty 1 pcs		

RC circuits



1

No.	380179	Ref. No.	76-30350514
description	RC circuit		

1

No.	381487	Ref. No.	76-30350509
description	RC circuit 230V connection Faston 6.3mm L 35mm H 30mm W 30mm 470Ohm		



1

No.	380278	Ref. No.	76-30350517
description	RC circuit 72-250V voltage AC for contactors M series type AEG EB05 A60		



1

No.	380272	Ref. No.	76-30280562
description	RC circuit for contactors type 910-304-585-50 130-250V 50-60Hz conductor 2 connection cable plastic Qty 1 pcs for contactors LS4_LS15K type AEG LR2K A250 type GE B52R2R		



1

No.	380177	Ref. No.	76-30350508
description	RC circuit type 20002 110/220V 50/60/DCHz conductor 2 connection cable 230mm L 29mm ømm H 15mm W 20mm adhesive tape plastic Qty 1 pcs		



1

No.	380221	Ref. No.	76-30350515
description	RC circuit type LS4-37 230V voltage AC type AEG LS4-37		

fuses

fine fuses



1

No.	358597	Ref. No.	76-30190400
description	fine fuse size ø5x20mm 0.5A slow-acting rated 250V Qty 10 pcs		



1

No.	358603	Ref. No.	76-30190120
description	fine fuse size ø5x20mm 2A slow-acting rated 250V Qty 10 pcs		



1

No.	358607	Ref. No.	76-30190200
description	fine fuse size ø5x20mm 6.3A slow-acting rated 250V Qty 10 pcs		



1


No.	358735	Ref. No.	76-40010218
description	fine fuse size ø5x30mm 6.3A medium lag rated 500V Qty 10 pcs		



1

No.	358791	Ref. No.	76-40010224
description	fine fuse size ø6.3x32mm 6.3A slow-acting rated 250V Qty 10 pcs		

fine fuse holders



No.	550105	Ref. No.	76-40011228
description	rail-mounted terminal WIELAND type WK10/SIU 5X20 /V0 suitable fuse $\varnothing 5 \times 20 \text{ mm}$ 1.0-16mm ² 10A rated 250V		

screw locks

D0-system (NEOZED)



No.	358045	Ref. No.	76-30190403
description	fuse size D02 35A rated 250/400V E18 $\varnothing 15 \text{ mm}$ L 36mm Qty 10 pcs		



No.	358046	Ref. No.	76-30190404
description	fuse size D02 50A rated 250/400V E18 $\varnothing 15 \text{ mm}$ L 36mm Qty 10 pcs		

fuse holders



No.	358060	Ref. No.	76-40011234
description	fuse holder suitable fuse D02 3-pole-pole 63A rated 400V		



No.	358061	Ref. No.	76-40011235
description	fuse holder suitable fuse D02 $\varnothing 25 \text{ mm}$ mounting $\varnothing 18 \text{ mm}$ rated 400V L 30mm		

overload switches



No.	358524	Ref. No.	76-30140400 76-30140402
description	overload switch drop-away current 0.05A		

electric accessories

plugs - couplings - power sockets

CEE plugs



No.	550210	Ref. No.	841534
description	plug CEE straight 5-pole contacts 3P+N+E max. 16A max 400V protection IP44 clamps 1.0-2.5mm ²		

cables

accessories

cable glands

threaded cable glands

screw connections



No.	550303	Ref. No.	76-40070600
description	cable gland thread PG9 cable $\varnothing 6.0\text{-}8.0 \text{ mm}$ mounting $\varnothing 15.2 \text{ mm}$ nickel-plated brass Qty 5 pcs		
accessories for	550303		
	No.	550321	Ref. No. —
	nut thread PG9 WS 18 nickel-plated brass Qty 5 pcs thickness 2.9mm mounting $\varnothing \text{ mm}$ cable $\varnothing \text{ mm}$		

connection cables



No.	403815	Ref. No.	76-88171040
description	connection cable 9-pole RS232/USB L 790mm		



No.	403811	Ref. No.	76-87201302
description	connection cable L 525mm 7-pole for combi-steamer CPC-Linie CPC/CM 61-202 connection plug-in connection plug type coded for PCB		



No.	579005	Ref. No.	76-87201300
description	data cable L 550mm 4-pole for combi-steamer suitable for CPC-Linie CPC/CM 61-202 plug type USB		

terminals and connectors

not insulated

female fastons

iron nickel-plated



No.	550001	Ref. No.	76-40020100
description	female faston size 6.3x0.8mm 1.0-2.5mm² straight Fe gal Ni t.max. 340°C Qty 100 pcs		

terminals

PCB terminal blocks



No.	550809	Ref. No.	76-30400193 76-30400198
description	PCB terminal block 11-pole raster size 5mm		

rail-mounted terminals


WIELAND

rail-mounted terminals type 9700A



No.	550376	Ref. No.	76-40011206
description	rail-mounted terminal WIELAND type 9700A/16 S35 2.5-35mm² top-hat rail 35mm grey W 16mm L 59mm		

fuse terminal blocks



No.	550105	Ref. No.	76-40011228
description	rail-mounted terminal WIELAND type WK10/SIU 5X20 /V0 suitable fuse ø5x20mm 1.0-16mm² 10A rated 250V		

gas taps

PEL

21S series



No.	101913	Ref. No.	41-1031501300
description	gas tap PEL type 21S gas inlet M16x1.5 (tube ø 10mm) bypass nozzle ø 0.9mm gas outlet M16x1.5 (tube ø 10/8mm) thermocouple connection M8x1 pilot connection M10x1 shaft ø 6x4.6mm shaft L 35/28mm shaft flat right		
spare parts for	101913		
	No.	100528	Ref. No. —
bypass nozzle type PEL20/21 bore ø 0.9mm thread M5x0.5			
	No.	101060	Ref. No. 49-407088
magnet unit standard L 39mm D1 ø 15.4mm D2 ø 11mm suitable for PEL20-21/JUNKERS/EGA			
	No.	101230	Ref. No. —
thermocouple nut T1: M8x1 T2: M18x1 aluminium			
	No.	101877	Ref. No. —
gas tap front part shaft ø 6x4.6mm type PEL21			
accessories for	101913		
	No.	100908	Ref. No. —
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs			
	No.	100909	Ref. No. —
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs			
	No.	101246	Ref. No. —
olive for pipe ø 4mm Qty 1 pcs			
	No.	101278	Ref. No. —
olive for pipe ø 10mm Qty 1 pcs			
	No.	101286	Ref. No. —
olive ID ø 6mm Qty 1 pcs			
	No.	101300	Ref. No. —
union nut thread M16x1.5 tube ø 10mm			
	No.	101450	Ref. No. —
olive for pipe ø 8mm L 12.7mm Qty 1 pcs ED ø 10mm			
	No.	101451	Ref. No. —
union nut thread M16x1.5 tube ø 8mm			
	No.	110078	Ref. No. —
knob without symbol ø 70mm shaft ø 6x4.6mm shaft flat universal			
	No.	112206	Ref. No. —
knob dial plate silver gas tap PEL21/22/23 t.max.°C ED ø 63mm ID ø 45.5mm			








alternatives to EGA


GPEL21 series

with nozzle outlet



1

No.	101668	Ref. No.	01-231553
description	gas tap alternatives to EGA type GPEL21D with nozzle outlet (with nozzle) gas inlet M15x1 (tube ø 10mm) external nozzle ø 1.35mm internal nozzle ø 1.2mm bypass nozzle ø 0.35mm mixing pipe connection M17x1 thermocouple connection M10x1 pilot connection M10x1 shaft ø 8x7mm shaft L 34/15mm shaft flat lower tube ø 10mm shaft length knob 15mm		
spare parts for	101668		
	No.	100300	Ref. No. —
gas injector thread M12x1 WS 14 bore ø 1.35mm			
	No.	100313	Ref. No. —
internal nozzle bore ø 1.20mm suitable for EGA26400/26440			
	No.	100908	Ref. No. —
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs			
	No.	100927	Ref. No. —
torsion spring L 2.8-8.0mm for internal nozzle ø 3mm bore ømm			
	No.	101060	Ref. No. 49-407088
magnet unit standard L 39mm D1 ø 15.4mm D2 ø 11mm suitable for PEL20-21/JUNKERS/EGA			
	No.	101233	Ref. No. —
union nut thread M10x1 JUNKERS			
	No.	101246	Ref. No. —
olive for pipe ø 4mm Qty 1 pcs			
	No.	101526	Ref. No. —
O-ring Viton thickness 1.78mm ID ø 4.48mm Qty 1 pcs			
	No.	101593	Ref. No. —
adjusting screw for internal nozzle thread M8x0.75			
	No.	101806	Ref. No. —
gas tap front part shaft ø 8x7mm shaft L 34/15mm shaft flat upper/lower suitable for PEL21			
accessories for	101668		
	No.	100909	Ref. No. —
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs			
	No.	100926	Ref. No. —
centring piece thread M17x1			
	No.	100942	Ref. No. —
union nut thread M15x1 for pipe ø 10mm			
	No.	101278	Ref. No. —
olive for pipe ø 10mm Qty 1 pcs			

accessories for	101668		
	No.	101286	Ref. No. —
olive ID ø 6mm Qty 1 pcs			



1














No.	101633	Ref. No.	49-170882
description	gas tap alternatives to EGA type GPEL21D with nozzle outlet (with nozzle) gas inlet M15x1 (tube ø 10mm) external nozzle ø 1.4mm internal nozzle ø 0.8mm bypass nozzle ø 0.35mm mixing pipe connection M17x1 thermocouple connection M8x1 pilot connection M10x1 shaft ø 6x4.6mm shaft L 31/23mm shaft flat left		
spare parts for	101633		
	No.	100307	Ref. No. —
gas injector thread M12x1 WS 14 bore ø 1.40mm			
	No.	100311	Ref. No. 49-161791
internal nozzle bore ø 0.80mm suitable for EGA26400/26440			
	No.	100408	Ref. No. —
bypass nozzle type PEL20/21 bore ø 0.35mm thread M5x0.5			
	No.	100927	Ref. No. —
torsion spring L 2.8-8.0mm for internal nozzle ø 3mm bore ømm			
	No.	101060	Ref. No. 49-407088
magnet unit standard L 39mm D1 ø 15.4mm D2 ø 11mm suitable for PEL20-21/JUNKERS/EGA			
	No.	101230	Ref. No. —
thermocouple nut T1: M8x1 T2: M18x1 aluminium			
	No.	101526	Ref. No. —
O-ring Viton thickness 1.78mm ID ø 4.48mm Qty 1 pcs			
	No.	101593	Ref. No. —
adjusting screw for internal nozzle thread M8x0.75			
	No.	101802	Ref. No. —
gas tap front part shaft ø 6x4.6mm shaft L 30/23mm shaft flat right/left suitable for PEL21			
accessories for	101633		
	No.	100908	Ref. No. —
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs			
	No.	100909	Ref. No. —
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs			
	No.	100926	Ref. No. —
centring piece thread M17x1			
	No.	100942	Ref. No. —
union nut thread M15x1 for pipe ø 10mm			

Table continues overleaf



accessories for 101633				
	No.	101246	Ref. No.	—
olive for pipe ø 4mm Qty 1 pcs				
	No.	101278	Ref. No.	—
olive for pipe ø 10mm Qty 1 pcs				
	No.	101286	Ref. No.	—
olive ID ø 6mm Qty 1 pcs				
	No.	110078	Ref. No.	—
knob without symbol ø 70mm shaft ø 6x4.6mm shaft flat universal				
	No.	112206	Ref. No.	—
knob dial plate silver gas tap PEL21/22/23 t.max.°C ED ø 63mm ID ø 45.5mm				

1	No.	101634	Ref. No.	49-170883
description gas tap alternatives to EGA type GPEL21D with nozzle outlet (with nozzle) gas inlet M15x1 (tube ø 10mm) external nozzle ø 1.85mm internal nozzle ø 1.05mm bypass nozzle ø 0.5mm mixing pipe connection M17x1 thermocouple connection M8x1 pilot connection M10x1 shaft ø 6x4.6mm shaft L 31/23mm shaft flat left				
spare parts for 101634				
	No.	100302	Ref. No.	—
gas injector thread M12x1 WS 14 bore ø 1.85mm				
	No.	100312	Ref. No.	01-230735
internal nozzle bore ø 1.05mm suitable for EGA26400/26440				
	No.	100526	Ref. No.	—
bypass nozzle type PEL20/21 bore ø 0.5mm thread M5x0.5				
	No.	100927	Ref. No.	—
torsion spring L 2.8-8.0mm for internal nozzle ø 3mm bore ømm				
	No.	101060	Ref. No.	49-407088
magnet unit standard L 39mm D1 ø 15.4mm D2 ø 11mm suitable for PEL20-21/JUNKERS/EGA				
	No.	101230	Ref. No.	—
thermocouple nut T1: M8x1 T2: M18x1 aluminium				
	No.	101526	Ref. No.	—
O-ring Viton thickness 1.78mm ID ø 4.48mm Qty 1 pcs				
	No.	101593	Ref. No.	—
adjusting screw for internal nozzle thread M8x0.75				
	No.	101802	Ref. No.	—
gas tap front part shaft ø 6x4.6mm shaft L 30/23mm shaft flat right/left suitable for PEL21				
accessories for 101634				
	No.	100908	Ref. No.	—
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs				

accessories for 101634				
	No.	100909	Ref. No.	—
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs				
	No.	100926	Ref. No.	—
centring piece thread M17x1				
	No.	100942	Ref. No.	—
union nut thread M15x1 for pipe ø 10mm				
	No.	101246	Ref. No.	—
olive for pipe ø 4mm Qty 1 pcs				
	No.	101278	Ref. No.	—
olive for pipe ø 10mm Qty 1 pcs				
	No.	101286	Ref. No.	—
olive ID ø 6mm Qty 1 pcs				
	No.	110078	Ref. No.	—
knob without symbol ø 70mm shaft ø 6x4.6mm shaft flat universal				
	No.	112206	Ref. No.	—
knob dial plate silver gas tap PEL21/22/23 t.max.°C ED ø 63mm ID ø 45.5mm				

with pipe outlet

1	No.	101646 ¹	Ref. No.	49-170737
description gas tap alternatives to EGA type GPEL20RD with pipe outlet with throttle screw gas inlet M15x1 (tube ø 10mm) bypass nozzle ø 0.35mm gas outlet M17x1 (tube ø 10mm) thermocouple connection M8x1 pilot connection M10x1 shaft ø 6x4.6mm shaft L 31/23mm shaft flat upper				
spare parts for 101646				
	No.	100408	Ref. No.	—
bypass nozzle type PEL20/21 bore ø 0.35mm thread M5x0.5				
	No.	101060	Ref. No.	49-407088
magnet unit standard L 39mm D1 ø 15.4mm D2 ø 11mm suitable for PEL20-21/JUNKERS/EGA				
	No.	101230	Ref. No.	—
thermocouple nut T1: M8x1 T2: M18x1 aluminium				
	No.	101526	Ref. No.	—
O-ring Viton thickness 1.78mm ID ø 4.48mm Qty 1 pcs				
	No.	101552	Ref. No.	—
throttle screw thread M8x0.75				
accessories for 101646				
	No.	100908	Ref. No.	—
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs				







¹with reducer for main gas line




accessories for 101646				
	No.	100909	Ref. No.	—
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs				
	No.	100926	Ref. No.	—
centring piece thread M17x1				
	No.	100942	Ref. No.	—
union nut thread M15x1 for pipe ø 10mm				
	No.	101246	Ref. No.	—
olive for pipe ø 4mm Qty 1 pcs				
	No.	101278	Ref. No.	—
olive for pipe ø 10mm Qty 1 pcs				
	No.	101286	Ref. No.	—
olive ID ø 6mm Qty 1 pcs				
	No.	110078	Ref. No.	—
knob without symbol ø 70mm shaft ø 6x4.6mm shaft flat universal				
	No.	112206	Ref. No.	—
knob dial plate silver gas tap PEL21/22/23 t.max.°C ED ø 63mm ID ø 45.5mm				

MADEC (MP)

with nozzle outlet







1

No.	101632	Ref. No.	49-170881
description	gas tap MADEC type 170881 with nozzle outlet (with nozzle) gas inlet M12x1 (tube ø 8mm) external nozzle ø 2.2mm internal nozzle ø 1.4mm bypass nozzle ø 0.7mm mixing pipe connection M17x1 thermocouple connection M8x1 front fixing M12x1 shaft ø 6x4.6mm shaft L 37/17mm shaft flat lower		
spare parts for	101632		
	No.	100293	Ref. No. —
gas injector thread M12x1 WS 14 bore ø 2.20mm			
	No.	100423	Ref. No. —
internal nozzle MADEC bore ø 1.4mm			
	No.	100427	Ref. No. —
bypass nozzle MADEC bore ø 0.7mm thread M4.5x0.6			
	No.	101051	Ref. No. 49-160860
magnet unit L 27mm D1 ø 12.5mm D2 ø 8.5mm suitable for JUNKERS/EGA/MADEC/SABAF standard			
accessories for	101632		
	No.	101277	Ref. No. —
olive ID ø 8mm Qty 1 pcs			
	No.	101296	Ref. No. —
union nut thread M12x1 for pipe ø 8mm			

accessories for 101632				
	No.	101299	Ref. No.	—
nut thread M12x1				
	No.	101400	Ref. No.	—
air mixing tube thread M17x1 suitable for L350, L700				
	No.	110149	Ref. No.	—
knob gas tap without ignition flame t.max.°C temperature range°C ø 50mm shaft ø 6x4.6mm shaft flat right black				



1

No.	101631	Ref. No.	49-170880	
description	gas tap MADEC with nozzle outlet (with nozzle) gas inlet M12x1 (tube ø 8mm) external nozzle ø 2.2mm internal nozzle ø 1.2mm bypass nozzle ø 0.55mm mixing pipe connection M17x1 thermo-couple connection M8x1 front fixing M12x1 shaft ø 6x4.6mm shaft L 37/17mm shaft flat lower			
spare parts for	101631			
	No.	100293	Ref. No.	—
gas injector thread M12x1 WS 14 bore ø 2.20mm				
	No.	100422	Ref. No.	—
internal nozzle MADEC bore ø 1.2mm				
	No.	100426	Ref. No.	—
bypass nozzle MADEC bore ø 0.55mm thread M4.5x0.6				
	No.	101051	Ref. No.	49-160860
magnet unit L 27mm D1 ø 12.5mm D2 ø 8.5mm suitable for JUNKERS/EGA/MADEC/SABAF standard				
	No.	101234	Ref. No.	—
union nut T1: M8x1 T2: M15				
accessories for	101631			
	No.	100943	Ref. No.	—
union nut thread M17x1 tube ø 10mm				
	No.	101277	Ref. No.	—
olive ID ø 8mm Qty 1 pcs				
	No.	101296	Ref. No.	—
union nut thread M12x1 for pipe ø 8mm				
	No.	101299	Ref. No.	—
nut thread M12x1				
	No.	101394	Ref. No.	—
nut thread M17x1 H 3mm WS 19 brass Qty 1 pcs				
	No.	101400	Ref. No.	—
air mixing tube thread M17x1 suitable for L350, L700				
	No.	110149	Ref. No.	—
knob gas tap without ignition flame t.max.°C temperature range°C ø 50mm shaft ø 6x4.6mm shaft flat right black				




gas valves and ignition boxes











gas control valves

SIT

NOVASIT



1

No.	101163	Ref. No.	76-30390204 76-30390220
description	gas valve SIT series Novasit 827 230V 50Hz gas inlet 1/2" gas outlet 1/2" thermocouple connection pilot connection M10x1 ignition pressure 3-5mbar pressure range 2-20mbar pressure regulator connection standard equiv. no. 0.827.110 power supply for modulator 28VDC		
spare parts for	101163		
	No.	101313	Ref. No. —
solenoid coil 230V 50Hz			
accessories for	101163		
	No.	100006	Ref. No. —
piezoelectric igniter suitable for ELETROSIT body plastic blowing connection ø2.4mm ø 14mm			
	No.	101305	Ref. No. —
gas connection straight 1/2" flange 45x45mm ELETROSIT/V4400/4600/4605 suitable for SIT/HONEYWELL hole distance 36x36mm			
	No.	101306	Ref. No. —
gas connection angled flange 45x45mm hole distance 36x36mm 1/2" ELETROSIT/V4400/4600/4605 screw with O-ring suitable for SIT/HONEYWELL			
	No.	101307	Ref. No. —
gas connection straight flange 45x45mm hole distance 36x36mm 3/4" ELETROSIT/V4400/4600/4605 screw with O-ring suitable for SIT/HONEYWELL			
	No.	101308	Ref. No. —
gas connection angled flange 45x45mm hole distance 36x36mm 3/4" ELETROSIT/V4400/4600/4605 screw with O-ring suitable for SIT/HONEYWELL			
	No.	101312	Ref. No. —
microswitch			
	No.	101314	Ref. No. —
solenoid coil 24V 50Hz			
	No.	101317	Ref. No. —
plug with cable L 1000mm suitable for NOVASIT			
	No.	101318	Ref. No. —
cover cap for solenoid coil suitable for NOVASIT			

ignition boxes

HONEYWELL



1

No.	101166	Ref. No.	76-30390103
description	ignition box HONEYWELL type S4560B 1006 electrodes 1 waiting time 0s safety time 10s 220-240V 10VA 50Hz		



1

No.	101184	Ref. No.	76-30390105
description	ignition box HONEYWELL type S4565C 1033 equiv. no. S4565C 1033 electrodes 2 waiting times safety time 5s 220-240V 4VA 50/60Hz		

ignition parts

pilot burners

SIT

100 series

accessories

pilot burner nozzles



1

No.	100246	Ref. No.	42-5017208682
description	pilot burner nozzle natural gas bore ø 0.35mm Qty 1 pcs thread M8x0.75		

JUNKERS



CB 502 series

pilot burners






1

No.	100085	Ref. No.	49-161134
description	pilot burner JUNKERS type CB502031 natural gas nozzle no.6 gas connection 6mm with primary air		
spare parts for	100085		
	No.	100227	Ref. No. —
pilot burner nozzle natural gas gas pressure 25mbar code 6 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100704	Ref. No. 49-407123
ignition electrode D1 ø 9mm connection M4 D2 ø 11mm L1 17mm L2 17mm BL1 13mm BL2 4mm BL3 22mm			
	No.	100909	Ref. No. —
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs			
	No.	101287	Ref. No. —
olive for pipe ø 6mm Qty 1 pcs			
	No.	101292	Ref. No. —
union screw for igniter suitable for CB 502/505 Qty 1 pcs			
	No.	101295	Ref. No. —
clamping collet for thermocouple suitable for CB 502/505 Qty 1 pcs			
accessories for	100085		
	No.	100220	Ref. No. 49-161141
pilot burner nozzle LPG gas pressure 50mbar code 2 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100221	Ref. No. —
pilot burner nozzle LPG gas pressure 30mbar code 29 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100222	Ref. No. —
pilot burner nozzle LPG gas pressure 50mbar code 5 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100223	Ref. No. 49-161140
pilot burner nozzle natural gas gas pressure 20mbar code 3 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100224	Ref. No. —
pilot burner nozzle natural gas gas pressure 25mbar code 26 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100225	Ref. No. —
pilot burner nozzle LPG gas pressure 30mbar code 39 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100226	Ref. No. —
pilot burner nozzle LPG gas pressure 50mbar code 15 suitable for JUNKERS			
	No.	100228	Ref. No. —
pilot burner nozzle town gas gas pressure 8mbar code 4 Qty 1 pcs suitable for JUNKERS CB50203_			






accessories for	100085		
	No.	101281	Ref. No. —
olive for pipe ø 4mm L 8.7mm Qty 1 pcs suitable for CB 502/503			
	No.	101283	Ref. No. —
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs			



1

No.	100061	Ref. No.	49-161136
description	pilot burner JUNKERS type CB502031 natural gas nozzle no.6 gas pressure 25mbar gas connection 6mm with primary air code 6		
spare parts for	100061		
	No.	100227	Ref. No. —
pilot burner nozzle natural gas gas pressure 25mbar code 6 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100909	Ref. No. —
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs			
	No.	101287	Ref. No. —
olive for pipe ø 6mm Qty 1 pcs			
	No.	101295	Ref. No. —
clamping collet for thermocouple suitable for CB 502/505 Qty 1 pcs			
accessories for	100061		
	No.	100220	Ref. No. 49-161141
pilot burner nozzle LPG gas pressure 50mbar code 2 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100221	Ref. No. —
pilot burner nozzle LPG gas pressure 30mbar code 29 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100222	Ref. No. —
pilot burner nozzle LPG gas pressure 50mbar code 5 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100223	Ref. No. 49-161140
pilot burner nozzle natural gas gas pressure 20mbar code 3 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100224	Ref. No. —
pilot burner nozzle natural gas gas pressure 25mbar code 26 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100225	Ref. No. —
pilot burner nozzle LPG gas pressure 30mbar code 39 Qty 1 pcs suitable for JUNKERS CB503_			
	No.	100226	Ref. No. —
pilot burner nozzle LPG gas pressure 50mbar code 15 suitable for JUNKERS			
	No.	100228	Ref. No. —
pilot burner nozzle town gas gas pressure 8mbar code 4 Qty 1 pcs suitable for JUNKERS CB50203_			
	No.	100704	Ref. No. 49-407123
ignition electrode D1 ø 9mm connection M4 D2 ø 11mm L1 17mm L2 17mm BL1 13mm BL2 4mm BL3 22mm			




















accessories for 100061				
	No.	100851	Ref. No.	—
cover for pilot burner suitable for JUNKERS CB502_55				
	No.	100907	Ref. No.	—
screw connection thread M10x1 Qty 1 pcs type SEF 1 ømm for thermocouple				
	No.	101281	Ref. No.	—
olive for pipe ø 4mm L 8.7mm Qty 1 pcs suitable for CB 502/503				
	No.	101283	Ref. No.	—
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs				
	No.	101292	Ref. No.	—
union screw for igniter suitable for CB 502/505 Qty 1 pcs				

POLIDORO

pilot burners




No.	100079	Ref. No.	42-5024706878	
description	pilot burner POLIDORO 3 flames code gas connectionmm			
accessories for	100079			
	No.	100000	Ref. No.	—
pilot burner nozzle POLIDORO LPG code 22 bore ø 0.22mm Qty 1 pcs				
	No.	100208	Ref. No.	—
pilot burner nozzle POLIDORO LPG code 20 bore ø 0.2mm Qty 1 pcs				
	No.	100209	Ref. No.	—
pilot burner nozzle POLIDORO natural gas code 40 bore ø 0.4mm Qty 1 pcs				
	No.	100701	Ref. No.	—
ignition electrode connection M4 Qty 1 pcs				
	No.	100906	Ref. No.	—
screw connection thread M10x1 for ignition electrode brass Qty 1 pcs WS 10				
	No.	100907	Ref. No.	—
screw connection thread M10x1 Qty 1 pcs type SEF 1 ømm for thermocouple				
	No.	100908	Ref. No.	—
union screw thread M10x1 for pipe ø 4mm Qty 1 pcs				
	No.	100909	Ref. No.	—
union screw thread M10x1 for pipe ø 6mm Qty 1 pcs				
	No.	102110	Ref. No.	90-000183
pilot tube copper pipe ø 4mm thickness 1mm L 3000mm				
	No.	102111	Ref. No.	—
pilot tube copper pipe ø 6mm thickness 1mm L 3000mm				
	No.	102699	Ref. No.	—
pilot burner nozzle POLIDORO natural gas code 25.2 bore ø 2x0.25mm Qty 1 pcs 2 bores				

accessories for 100079				
	No.	102795	Ref. No.	—
olive for pipe ø 4mm Qty 1 pcs				
	No.	102797	Ref. No.	—
olive for pipe ø 6mm Qty 1 pcs				
	No.	106703	Ref. No.	—
pilot burner nozzle POLIDORO natural gas code 27.2 bore ø 2x0.27mm Qty 1 pcs				
	No.	106704	Ref. No.	—
pilot burner nozzle POLIDORO LPG code 16.2 bore ø 2x0.16mm Qty 1 pcs				
	No.	106763	Ref. No.	—
pilot burner nozzle POLIDORO natural gas code 27.2A bore ø 2x 0.27mm Qty 1 pcs				
	No.	106859	Ref. No.	—
pilot burner nozzle POLIDORO LPG code 24 bore ø 0.24mm Qty 1 pcs				

electrodes





No.	103301	Ref. No.	76-20680152
description	ignition electrode D1 ø 7mm L1 5mm L2 12mm BL1 63mm to clip connection ø 4mm		



No.	100720	Ref. No.	49-185217
description	ignition electrode D1 ø 8mm BL1 42mm connection F 2.8x0.8mm with spring		




			
No.	100704	Ref. No.	49-407123
description	ignition electrode D1 ø 9mm connection M4 D2 ø 11mm L1 17mm L2 17mm BL1 13mm BL2 4mm BL3 22mm		

			
No.	102166	Ref. No.	42-3562615504
description	ignition electrode flange length 23mm flange width 15mm D1 ø 7mm L1 85mm L2 40mm BL1 21mm BL2 25mm fixing dimensions ø5x4mm with flange connection ø 4mm		

ignition cables

pre-assembled cables



			
No.	100193	Ref. No.	42-5061005414
description	ignition cable cable length 1200mm connection ø2.4mm / ø4mm		


thermocouples



plug-in thermocouples

plug-in thermocouples standard

with barrel socket ø5mm - type Junkers with aluminised tip


			
No.	102202	Ref. No.	162111
description	thermocouple M8x1 L 320mm plug connection ø5.0mm		
accessories for	102202		
	No.	101260	Ref. No.
			—
thermocouple fitting thread M8x1 Qty 1 pcs			

			
No.	102204	Ref. No.	49-162112
description	thermocouple M8x1 L 600mm plug connection ø5.0mm		

			
No.	102205	Ref. No.	49-174413
description	thermocouple M8x1 L 750mm plug connection ø5.0mm		
accessories for	102205		
	No.	101260	Ref. No. —
thermocouple fitting thread M8x1 Qty 1 pcs			

threaded thermocouples

threaded thermocouples with cable link


			
No.	102088	Ref. No.	49-162153
description	thermocouple with two-conductors L 1500mm M8x1 M10x1		

gas burners

hob burners

accessories

pan supports

			
No.	210150	Ref. No.	41-1032101000
description	pan support W 340mm L 545mm		



bar burners

bar burners



1

No.	211029	Ref. No.	1829522
description	lava rock grid L 464mm W 310mm		

lava rock grids



1

No.	211029	Ref. No.	1829522
description	lava rock grid L 464mm W 310mm		

surface burners



1

No.	105948	Ref. No.	76-20680215
description	surface burner L 330mm W 140mm H 55mm firing range 320x130mm burner rows 18 convection oven		



1

No.	105951	Ref. No.	76-20721001
description	surface burner number of rows 14 nozzle ø 0.62mm		



1

No.	105952	Ref. No.	76-20721000
description	surface burner number of rows 14 nozzle ø 1.1mm		

1

No.	105950	Ref. No.	76-20680216
description	surface burner number of rows 18 nozzle ø 0.65mm LPG		

gas nozzles

pilot burner nozzles

pilot burner nozzles JUNKERS

CB 50203_/503_ series



1

No.	100220	Ref. No.	49-161141
description	pilot burner nozzle LPG gas pressure 50mbar code 2 Qty 1 pcs suitable for JUNKERS CB503_		



1

No.	100223	Ref. No.	49-161140
description	pilot burner nozzle natural gas gas pressure 20mbar code 3 Qty 1 pcs suitable for JUNKERS CB503_		

pilot burner nozzles SIT

100 series



1

No.	100246	Ref. No.	42-5017208682
description	pilot burner nozzle natural gas bore ø 0.35mm Qty 1 pcs thread M8x0.75		

internal nozzles

internal nozzles for EGA gas taps/nozzle holders

EGA 26400/26440/23268



1

No.	100310	Ref. No.	01-230733
description	internal nozzle bore ø 0.66mm suitable for EGA26400/26440		



1


No.	100319	Ref. No.	49161790
description	internal nozzle bore ø 0.75mm suitable for EGA26400/26440		




1

No.	100311	Ref. No.	49-161791
description	internal nozzle bore ø 0.80mm suitable for EGA26400/26440		





1			
No.	100315	Ref. No.	01-230734
description	internal nozzle bore ø 0.95mm suitable for EGA26400/26440		

1			
No.	100312	Ref. No.	01-230735
description	internal nozzle bore ø 1.05mm suitable for EGA26400/26440		

auxiliary gas parts

screw connections




union screws

1			
No.	101285	Ref. No.	90-000343
description	union screw thread M8x1 for pipe ø 4mm Qty 1 pcs JUNKERS		
accessories for	101285		
		No.	101284
		Ref. No.	—
	olive for pipe ø 4mm Qty 1 pcs		

gas lines

pilot tubes

universal


1			
No.	102110	Ref. No.	90-000183
description	pilot tube copper pipe ø 4mm thickness 1mm L 3000mm		
accessories for	102110		
		No.	100908
		Ref. No.	—
	union screw thread M10x1 for pipe ø 4mm Qty 1 pcs		
		No.	101246
		Ref. No.	—
	olive for pipe ø 4mm Qty 1 pcs		

equipment-specific units

for slicers

blades

standard

1			
No.	697365	Ref. No.	541117
description	slicing machine blade ED ø 250mm seat ø 40mm 3-hole ID ø 210mm H 17.5mm C45 standard		

for convection ovens/combi-steamers


drain units

drip rails

1			
No.	696533	Ref. No.	76-81000116
description	drip rail for combi-steamer L 600mm SS W 34mm hole ø 8mm		

1			
No.	694434	Ref. No.	76-84551315
description	drip rail with bezel L 465mm plastic for combi-steamer hose ø 15mm		

air filters

1			
No.	692695	Ref. No.	76-52141300
description	filter insert L 213mm W 60mm ømm H 90mm		



cleaning system

coupling bushings



1			
No.	694486	Ref. No.	76-20620348
description	coupling bush for cleaning system		



1			
No.	694487	Ref. No.	76-20620347
description	coupling bush for cleaning system		



1			
No.	694488	Ref. No.	76-20620350
description	coupling bush for cleaning system		



1			
No.	694489	Ref. No.	76-20620349
description	coupling bush for cleaning system		

cleaning arms



1			
No.	541433	Ref. No.	76-86552101
description	cleaning arm CleanJet suitable for RATIONAL _101-_202		

hoses



1			
No.	694362	Ref. No.	76-20220201
description	hose for combi-steamer		

service kits



1			
No.	530874	Ref. No.	76-87201521
description	conversion kit - for combi-steamer CPC-Linie 61-102E RATIONAL		
spare parts for	530874		



No.	692215	Ref. No.	—
description	conversion kit for tank inlet fitting		

door mechanics

miscellaneous



1			
No.	694934	Ref. No.	76-29401306
description	cover for door latch suitable for combi-steamer CPC-Linie 201/202 aluminium L 96.5mm W 65.5mm		

accessories



1			
No.	694656	Ref. No.	76-20390402
description	door bumper silicone ø 13mm L 19mm		

vibration pumps



1			
No.	500580	Ref. No.	76-30021003
description	vibration pump 230V 60W 50/60Hz inlet ø 7 outlet ø 1/8" IT CEME type E512 with accessories duty cycle 1/2 ambient temperature max. 60°C medium temp max. 35°C overheating protection 110°C CleanJet		

miscellaneous



1

No.	693526	Ref. No.	76-20601210
description	bush for spray gun		




1

No.	510558	Ref. No.	76-20220110
description	connection for pump		



1

No.	510559	Ref. No.	46-21181000 76-21181000
description	connection for pump		



1

No.	694320	Ref. No.	76-50120566
description	gasket for lid ø 145mm		



1

No.	512184	Ref. No.	76-86641301
description	hose connector plastic thread 3/4" Qty 1 pcs connection distance 60mm T-shape		



1

No.	694936	Ref. No.	76-50030300
description	insulating mat for combi-steamer CPC-Linie L 1078mm W 635mm H 11mm foam Qty 2 pcs		

for dishwashers

air traps

air traps



1

No.	510103	Ref. No.	61984004
description	air trap L 85mm W 20mm H 80mm hose ø 6mm plastic		

spare parts for



No.	505045	Ref. No.	—
description	O-ring EPDM thickness 1.78mm ID ø 5.28mm Qty 1 pcs		



No.	505094	Ref. No.	—
description	air trap		



No.	510016	Ref. No.	—
description	eye bolt for rinse aid container connection		



No.	510105	Ref. No.	—
description	hose connector for air trap		

air trap accessories



1

No.	510761	Ref. No.	63-200944-1
description	flat gasket rubber D1 ø 38mm D2 ø 25mm thickness 2mm Qty 1 pcs		

door mechanics

locks



1

No.	518244	Ref. No.	62-994011
description	door catch catch		


curtains

curtains



1

No.	533122	Ref. No.	610617
description	curtain W 660mm H 430mm warewashing für wash area/rinsing		



1


No.	533121	Ref. No.	610867
description	curtain W 660mm H 485mm warewashing für wash area/rinsing		



1

No.	533124	Ref. No.	602268
description	curtain W 660mm H 500mm warewashing for outlet		

EQUIPMENT-SPECIFIC UNITS KREFFT



1

No.	533120	Ref. No.	610616
description	curtain W 660mm H 550mm warewashing for inlet		

1


No.	533125	Ref. No.	500002
description	curtain W 690mm H 400mm warewashing for inlet		

1



No.	533126	Ref. No.	500003
description	curtain W 696mm H 330mm warewashing für wash area/rinsing		

1

No.	533123	Ref. No.	610945
description	curtain W 696mm H 450mm warewashing for drying		






h2>washing and rinsing systems



h2>knobs

h3>universal knobs



h2>handles and hand wheels

h3>bracket handles




h2>locks

h3>turning lever locks

h4>universal

h4>RAHRBACH







1

No.	690136	Ref. No.	76-20160605
description	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		

STUV



1

No.	700098	Ref. No.	76-20160603	
description	door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750			
spare parts for	700098			
	No.	690136	Ref. No.	76-20160605
	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm			
accessories for	700098			
	No.	514281	Ref. No.	—
	base plate L 110mm W 35mm for door catch thickness 10mm			

producer-specific

KREFFT



1

No.	693519	Ref. No.	76-20161412 76-20161430 76-20161450
description	door handle L 230mm W 55mm H 62mm flange 56mm		



1

No.	690102	Ref. No.	76-20161457
description	bearing block L 110mm H 63mm W 35mm mounting distance 1 30mm mounting distance 2 90mm hole ø 20mm type 1750		





1

No.	700072	Ref. No.	76-20161300
description	door catch H 17mm L 84mm W 53mm mounting distance 68mm zinc die cast with wedge heated units		



1

No.	700098	Ref. No.	76-20160603	
description	door catch mounting pos. right off-set 38mm L 110mm H 74mm W 33mm mounting distance 68/68mm series 1750			
spare parts for	700098			
	No.	690136	Ref. No.	76-20160605
	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm			
accessories for	700098			
	No.	514281	Ref. No.	—
	base plate L 110mm W 35mm for door catch thickness 10mm			



1

No.	693592	Ref. No.	76-20161453
description	plain washer for door latch plastic ø 56mm ID ø 40mm H 2.3mm		



1

No.	690103	Ref. No.	76-20161452
description	screw cap H 47mm ø 40mm hole ø 10mm type 1750		



1

No.	690136	Ref. No.	76-20160605
description	sliding plate mounting pos. right L 28mm H 3mm W 21mm H2 12.5mm		



1


No.	690101	Ref. No.	76-20160604
description	snap lock L 85mm W 40mm mounting distance 68mm heated units H 63mm type 1750 series		

edgemoat latches

handle latches


STUV

3.30.016x.x series



1

No.	693517	Ref. No.	76-20161110
description	catch		



1

No.	700063	Ref. No.	76-20161100
description	handle latch L 155mm mounting distance 124/138mm non lockable refrigeration units 3.30.0164		
accessories for	700063		
	No.	700064	76-20160606
	Ref. No.		76-20160610
door catch H 40mm L 28mm W 22mm			

door catches



1

No.	700064	Ref. No.	76-20160606 76-20160610
description	door catch H 40mm L 28mm W 22mm		

walk-in fridge catches

STUV

3.31.015x.x series



1

No.	700072	Ref. No.	76-20161300
description	door catch H 17mm L 84mm W 53mm mounting distance 68mm zinc die cast with wedge heated units		

hinges

door bearing



1

No.	693569	Ref. No.	76-21201254
description	bolt mounting pos. upper		



1

No.	693558	Ref. No.	76-21201009
description	bolt mounting pos. upper for hinge		



1

No.	693539	Ref. No.	76-20160801
description	bolt mounting pos. upper right		



1

No.	693568	Ref. No.	76-29401300
description	bush mounting pos. upper		



1

No.	693552	Ref. No.	76-84401001
description	hinge mounting pos. lower		



1

No.	693567	Ref. No.	76-29301307
description	hinge mounting pos. upper		

accessories

miscellaneous



1

No.	693570	Ref. No.	76-29401302
description	sleeve latching		



1

No.	693571	Ref. No.	76-29401303
description	spigot latching		

fittings for catering equipment

drain taps

accessories



1

No.	540083	Ref. No.	49-150301-1
description	pressure bolt for drain tap		

equipment feet and end caps

bullet feet

plastic



1

No.	701589	Ref. No.	76-20390100
description	equipment foot pipe type 35x35 thickness 1-1.5mm H 15-50mm plastic		

zamak/SS



1

No.	700112	Ref. No.	76-20390111
description	equipment foot pipe type 40x40 thickness 1mm H 33-60mm Zamak/SS Qty 1 pcs		

DERBY RUOTE

with bolt hole

chrome-plated steel



1

No.	700200	Ref. No.	76-20050401
description	swivel castor ø 100mm bolt hole bolt hole ø 12mm housing chrome-plated sheet steel capacity 80kg bearing ball bearing wheel body polypropylene tread TPE tyres H 132mm wheel width 30mm Qty 1 pcs		



1

No.	700201 ¹	Ref. No.	76-20050402
description	swivel castor with swivel brake ø 100mm bolt hole bolt hole ø 12mm housing chrome-plated sheet steel capacity 80kg bearing ball bearing wheel body polypropylene tread TPE tyres H 132mm wheel width 30mm Qty 1 pcs		

¹with swivel brake

baskets

fryer baskets

KREFFT



1

No.	970150	Ref. No.	242375
description	fryer basket L1 300mm W1 180mm H1 130mm		



1

No.	970159	Ref. No.	49-141427
description	fryer basket L1 305mm W1 175mm H1 125mm L2 515mm H2 195mm		



1

No.	970151	Ref. No.	01-242385
description	fryer basket L1 320mm W1 180mm H1 210mm		



1

No.	970149	Ref. No.	242402
description	fryer basket L1 340mm W1 310mm H1 125mm		

warewashing baskets

steel wire baskets square

glass basket



1

No.	970065	Ref. No.	503786
description	glass basket L 400mm W 400mm H 170mm number of rows 4 rows spacing 90mm		

system baskets GIADOS 500x500mm

universal baskets



1

No.	976030	Ref. No.	509552
description	tray rack L 500mm W 500mm H 116mm tablets 9		


gaskets

refrigeration gaskets

plug-in gaskets

profile 9048

We offer custom-made gaskets for this profile




1

No.	900733	Ref. No.	90-14416800759
description	refrigeration gasket profile 9048 W 684mm L 762mm plug size		


gaskets for heated units

window seals




1

No.	902233	Ref. No.	76-50120201
description	window gasket profile 1560 L 2800mm Qty 1		




1


No.	902234	Ref. No.	76-50120202
description	window gasket profile 1560 L 3800mm Qty 1		




No.	902235	Ref. No.	76-50120203
description	window gasket profile 1560 L 5400mm Qty 1		




No.	902218	Ref. No.	76-50120204
description	window gasket profile 1560 L 5900mm Qty 1		




No.	902236	Ref. No.	76-50120200
description	window gasket profile 1570 Qty supplied by meter		




No.	900088	Ref. No.	76-51051005
description	window gasket profile 1860 W 430mm L 1275mm Qty 1 20 x 1/1 external size		



No.	900183	Ref. No.	76-51051000
description	window gasket profile 1860 W 430mm L 485mm Qty 1 external size		




No.	900184	Ref. No.	76-51051003
description	window gasket profile 1860 W 430mm L 745mm Qty 1 external size		




No.	900193	Ref. No.	76-51051017
description	window gasket profile 1860 W 600mm L 715mm Qty 1 external size		


door seals




No.	900091	Ref. No.	76-51051021
description	door seal for profile 2720 W 473mm L 785mm external size Qty 1 size 10 x 1/1		





No.	902237	Ref. No.	76-50120701
description	door seal profile 2210 L 3800mm Qty 1		





No.	902238	Ref. No.	76-50120702
description	door seal profile 2210 L 4200mm Qty 1		


			
No.	902240	Ref. No.	76-50120703
description	door seal profile 2230 W 470mm L 485mm external size Qty 1		


			
No.	902241	Ref. No.	76-50120704
description	door seal profile 2230 W 480mm L 725mm external size Qty 1		


			
No.	902242	Ref. No.	76-51051001
description	door seal profile 2250 W 470mm L 520mm external size Qty 1 6 x 1/1		


			
No.	902243	Ref. No.	76-51051004
description	door seal profile 2250 W 470mm L 790mm external size 10 x 1/1		


			
No.	902244	Ref. No.	76-51051007
description	door seal profile 2530 W 520mm L 1400mm external size Qty 1		

			
No.	900087	Ref. No.	76-51101047
description	door seal profile 2530 W 710mm L 815mm external size Qty 1 10 x 2/1		


			
No.	902245	Ref. No.	76-51051008
description	door seal profile 2530 W 720mm L 1410mm external size Qty 1 20 x 2/1		

			
No.	902219	Ref. No.	76-51051020
description	door seal profile 2730 W 465mm L 520mm external size Qty 1		

			
No.	902247	Ref. No.	76-51051021
description	door seal profile 2730 W 470mm L 785mm suitable for RATIONAL for model CPC 101 outer plug size Qty 1		



No.	902220	Ref. No.	76-51051022
description	door seal profile 2730 W 685mm L 780mm suitable for RATIONAL for model SCC/CM102 edition since 11/2011 outer plug size		




No.	902223	Ref. No.	76-51051023
description	door seal profile 2732 W 485mm L 1495mm external size Qty 1		




No.	900147	Ref. No.	01-253241
description	door seal profile 2950 Qty supplied by meter		


gaskets for tray rack trolleys




No.	902225	Ref. No.	76-50120551
description	tray rack trolley gasket profile 4020 L 1100mm Qty 1 silicone foam		




No.	902226	Ref. No.	76-50120550
description	tray rack trolley gasket profile 4020 L 750mm Qty 1 silicone foam		



No.	902227	Ref. No.	76-51051009 76-51051015
description	tray rack trolley gasket profile 4060 W 450mm L 170mm Qty 1 3-sided (long side open)		



No.	902228	Ref. No.	76-51051010
description	tray rack trolley gasket profile 4060 W 675mm L 165mm outer plug size Qty 1 suitable for RATIONAL for model C202 3-sided (long side open)		



No.	902229	Ref. No.	76-51051025
description	tray rack trolley gasket profile 4090 L 615mm Qty 1		


gaskets for control panels




No.	900570	Ref. No.	76-51051012
description	gasket for control panel W 305mm L 1000mm external size suitable for RATIONAL short side open		


O-rings


EPDM





No.	532731	Ref. No.	76-50120565
description	O-ring EPDM thickness 2.5mm ID \varnothing 115mm Qty 5 pcs suitable for combi-steamer CPC-Linie		


			
1			
No.	502036	Ref. No.	63-200805-1
description	O-ring EPDM thickness 2.62mm ID ø 28.25mm Qty 1 pcs		


silicone			
			
1			
No.	512414	Ref. No.	76-50120560
description	O-ring silicone thickness 3mm ID ø 47.5mm Qty 5 pcs		


sealing washers			
rubber gaskets			
			
1			
No.	510761	Ref. No.	63-200944-1
description	flat gasket rubber D1 ø 38mm D2 ø 25mm thickness 2mm Qty 1 pcs		


			
1			
No.	560616	Ref. No.	76-51101024
description	gasket ED ø 24mm ID ø 15mm thickness 3mm Qty 5 pcs for model C-Line, CPC, SCC 61-202		


			
1			
No.	560617	Ref. No.	76-50120539
description	gasket rubber ED ø 19.5mm ID ø 12mm thickness 2.3mm Qty 5 pcs		


copper gaskets			
DIN-7603-A			
			
1			
No.	528197	Ref. No.	76-13150101
description	flat gasket copper ED ø 10mm ID ø 6mm thickness 1mm Qty 1 pcs		

DIN-7603-C			
			
1			
No.	510420	Ref. No.	76-30041404
description	gasket copper ED ø 19.9mm ID ø 14.3mm thickness 2mm Qty 1 pcs		

silicone gaskets			
			
1			
No.	510575	Ref. No.	76-20220100
description	flat gasket silicone ED ø 14.5mm ID ø 4mm thickness 4mm Qty 1 pcs		

			
1			
No.	359721	Ref. No.	76-30250003 76-50120509 76-50120535
description	gasket silicone ED ø 48mm ID ø 39.5mm thickness 5mm Qty 1 pcs		

sealing cords			
round			
			
1			
No.	510572	Ref. No.	76-50020300 76-50020301 76-80068008
description	sealing cord ø 10mm greased L 0.2m Qty 1		

shaft gaskets			
shaft gaskets			
			
1			
No.	510574	Ref. No.	76-50010211
description	shaft sealing type 20 for fan motor		



miscellaneous




1

No.	510573	Ref. No.	76-50010207
description	shaft seal ID ø 17mm ED ø 29mm thickness 4.5mm		

special gaskets

miscellaneous



1

No.	510571	Ref. No.	76-50120528 76-50120537
description	gasket suitable for KÜPPERSBUSCH equiv. no. 407308 level regulator		



1

No.	510566	Ref. No.	76-50120528 76-50120537
description	gasket suitable for RATIONAL equiv. no. 50120537 L 70mm W 70mm electrode thickness 4mm		



1

No.	510671	Ref. No.	76-50120525 76-50120555
description	gasket suitable for RATIONAL for drain Qty 1m ED ø 124mm ID ø 51mm rubber thickness 4mm hole distance 87mm		

GASKETS/EVAPORATORS/SPRINGS KREFFT

evaporators

for fridges

producer-specific




1

No.	750268	Ref. No.	90-14330312410
description	evaporator L 500mm W 70mm H 160mm		


springs

torsion springs



1

No.	700023	Ref. No.	01-245664
description	torsion spring ø 18.2mm L2 150mm wire gauge ø 3.2mm mounting pos. left L1 100mm L3 24mm		



1


No.	700022	Ref. No.	01-245663
description	torsion spring ø 18.6mm L2 93mm wire gauge ø 3.4mm mounting pos. right L1 133mm L3 24mm		


compression springs



1

No.	693541	Ref. No.	76-20010111
description	compression spring ø 11mm L 20mm		






1 			
No.	693591	Ref. No.	76-20010109 76-20010118
description compression spring ø 14mm L 27mm wire gauge ø 1.5mm			


1 			
No.	511323	Ref. No.	43-450232
description compression spring ø 41.3mm L 57mm wire gauge ø 2mm			


hose reels and spray guns


spray guns


1 			
No.	540673	Ref. No.	76-20600100
description spray gun for appliances 1/2" ET L 135mm conversion kit			


1 			
No.	540302	Ref. No.	76-20010110 76-20600215 76-20600218 76-20601000 76-20601002 76-50120559
description spray gun for appliances 1/2" ET L 135mm type RATIONAL			
spare parts for 540302			
	No.	517056	Ref. No. —
O-ring EPDM thickness 2mm ID ø 6.5mm Qty 1 pcs			
	No.	532535	Ref. No. —
O-ring EPDM thickness 5mm ID ø 10mm Qty 1 pcs			
	No.	548016	Ref. No. —
compression spring ø 10mm L 17mm wire gauge ø 0.9mm for hand spray			
	No.	548017	Ref. No. —
pressure bolt for hand spray			


1 			
No.	530604	Ref. No.	76-20670603
description shower hose connections 1/2" - M12x1 L 1500mm SS			


1 			
No.	520730	Ref. No.	76-20670600
description shower hose connections 1/2" L 2400mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW with flexible fabric			

1 			
No.	520729	Ref. No.	76-20670601
description shower hose connections 1/2" L 2800mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW with flexible fabric			

1 			
No.	520731	Ref. No.	76-20670602
description shower hose connections 1/2" L 3200mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW nominal-ø 8mm with flexible fabric			

1 			
No.	520094	Ref. No.	76-20670605 76-20670610
description shower hose connections ø12mm - 1/2" L 1500mm for combi-steamer type type 61/101			

1 			
No.	520099	Ref. No.	76-20670611
description shower hose connections ø12mm - 1/2" L 1800mm for combi-steamer			

1 			
No.	520108	Ref. No.	76-20670606 76-20670609
description shower hose connections ø12mm - 1/2" L 2080mm for combi-steamer			



1

No.	542364	Ref. No.	76-20670710
description	shower hose for combi-steamer CPC-Linie connection 1/2" connection 2: plug-in connection ED ø 12mm L 1345mm		



1

No.	693526	Ref. No.	76-20601210
description	bush for spray gun		



1

No.	540001	Ref. No.	76-20600110
description	screw connection T1: 1/2" T2: 1/2" for spray gun rotary		

hose reels

appliance hose reels



1

No.	541442	Ref. No.	76-86553000
description	hose reel complete		



1

No.	541443	Ref. No.	76-86553003
description	hose reel complete		



1

No.	540662	Ref. No.	76-84101013
description	hose reel complete with spray gun hose length 1.5m		



1

No.	540663	Ref. No.	76-86552006
description	hose reel complete with spray gun hose length 1.5m		



1

No.	541439	Ref. No.	76-84101016
description	hose reel complete with spray gun hose length 1.5m		



1

No.	541440	Ref. No.	76-86552000
description	hose reel complete with spray gun hose length 1.5m		



1

No.	540483	Ref. No.	76-86552020 76-86552021
description	hose reel without spray gun hose length 2.1m		

dosing pumps

peristaltic dosing pumps







GERMAC

built-in version

with frequency control



1

No.	361268	Ref. No.	63-440632
description	dosing pump GERMAC frequency control 3l/h 230VAC detergent hose ø 4x6mm hose thermoplastic type G300 built-in version dimensions 67x72x101mm		
spare parts for	361268		
	No.	361467	Ref. No. 63-200608/1
pump hose GERMAC detergent hose type thermoplastic hose ø 6x10mm for model G43/G45/G53/G54/G55/G300/G305			
	No.	361557	Ref. No. —
control PCB type G300/G302/G305 GERMAC			
	No.	361589	Ref. No. —
roller assembly GERMAC suitable for G42/43/45/53/54/55/300/302/305/705			
accessories for	361268		
	No.	361106	Ref. No. —
container filter with weight and non-return valve SS hose ø 4x6mm ø 21mm L 51mm non return valve lip valve			
	No.	520090	Ref. No. —
PVC hose ID ø 4mm ED ø 6mm L 2m thickness 1mm t.max. 60°C transparent			
	No.	520091	Ref. No. —
nylon hose ID ø 4mm ED ø 6mm L 2m thickness 1mm operating p. 10bar burst p. 50bar t.max. 100°C transparent			

spare parts



1

No.	361554	Ref. No.	63-200608
description	pump hose GERMAC detergent hose type thermoplastic hose ø 5x8mm for model G200/G250/G252		



1

No.	361467	Ref. No.	63-200608/1
description	pump hose GERMAC detergent hose type thermoplastic hose ø 6x10mm for model G43/G45/G53/G54/G55/G300/G305		






SEKO

wall-mounted version

with speed control



1

No.	361157	Ref. No.	150069
description	dosing pump SEKO speed control 1-7l/h 230VAC detergent hose ø 4x6mm hose type K hose Santoprene suction level 1.5m type PR without accessories dimensions 103x82x92mm		
spare parts for	361157		
	No.	361136	Ref. No. —
roller assembly for dosing pump hole ø 4.8x4mm			
	No.	361815	Ref. No. —
pump hose detergent hose ø 6x10mm hose ø 4x6mm hose type K hose Santoprene type SEKO			
accessories for	361157		
	No.	361142	Ref. No. —
mounting set detergent hose type 4x6mm hose length 2m PVC 2x hose/container filter/tank intake transparent			
	No.	520090	Ref. No. —
PVC hose ID ø 4mm ED ø 6mm L 2m thickness 1mm t.max. 60°C transparent			
	No.	520091	Ref. No. —
nylon hose ID ø 4mm ED ø 6mm L 2m thickness 1mm operating p. 10bar burst p. 50bar t.max. 100°C transparent			

built-in version

with frequency control




1



No.	361906 ¹	Ref. No.	64-34358
description	dosing pump SEKO frequency control 2.8l/h 230VAC detergent hose ø 4x6mm hose Santoprene type NBR 3 8W CODE NBR0003A1004		

¹with accessories

piston pumps

with solenoid coil



No.	361026	Ref. No.	62-987017
description	dosing pump inlet 5mm outlet 5mm 230V detergent duty cycle 30% type EV1		
spare parts for	361026		
	No.	361365	Ref. No. 62-201020
	solenoid coil 230VAC for type EV1		
	No.	510298	Ref. No. 62-144012
	lip valve dosing pump suitable for DB2/DS5		

spare parts



No.	361113	Ref. No.	62-201002
description	solenoid coil 230VAC for type DB2		



No.	361365	Ref. No.	62-201020
description	solenoid coil 230VAC for type EV1		



No.	510298	Ref. No.	62-144012
description	lip valve dosing pump suitable for DB2/DS5		







No.	361366	Ref. No.	62-215001
description	PCB dishwasher 11F suitable for DB2 type DB2/EV1/EKP-M		

membrane dosing pumps

self-priming

LANG





No.	361032	Ref. No.	62-026292 62-400220
description	dosing pump type N6 membrane dosing pump rinse aid pressure connection ø angled, 4x6mm suction connection ø angled, 4x6mm		
spare parts for	361032		
	No.	361079	Ref. No. —
	spring for type N5/N6 for ball		
	No.	361080	Ref. No. —
	O-ring EPDM thickness 2mm ID ø 16mm Qty 1 pcs		
	No.	361085	Ref. No. —
	O-ring EPDM thickness 2mm ID ø 8mm Qty 1 pcs		
	No.	361309	Ref. No. —
	ball for type N5/N6		
	No.	361310	Ref. No. —
	bracket for type N6 ball guide		
	No.	361311	Ref. No. —
	O-ring EPDM thickness 2mm ID ø 6mm Qty 1 pcs for type N6		
	No.	361314	Ref. No. —
	valve ring for type N6 holder for O-ring		
	No.	361317	Ref. No. —
	sealing disc for type N6		
	No.	361886	Ref. No. —
	non-return valve inletmm outletmm outlet ø 12.4mm L 12.7mm		

various



1

No.	361015	Ref. No.	63-620120
description	dosing pump membrane dosing pump rinse aid inlet 6x8mm outlet 4x6mm pressure connection ø 4x6mm suction connection ø 6x8mm		
spare parts for	361015		
	No.	361132	Ref. No. —
membrane dosing pump			
	No.	510298	Ref. No. 62-144012
lip valve dosing pump suitable for DB2/DS5			



1

No.	361002	Ref. No.	63-620120
description	dosing pump rinse aid inlet 6x8mm outlet 4x6mm pressure connection ø 4x6mm suction connection ø 6x8mm		
spare parts for	361002		
	No.	510297	Ref. No. —
membrane for dosing pump ED ø 83mm thickness 1mm dosing pump equiv. no. 630614 suitable for COMENDA			
	No.	510298	Ref. No. 62-144012
lip valve dosing pump suitable for DB2/DS5			
	No.	510299	Ref. No. —
hose connector for dosing pump			
	No.	510338	Ref. No. —
union nut dosing pump thread 1/2" ø 32mm H 15mm for dosing pump			
	No.	510847	Ref. No. —
gasket polishing agent dosing ID ø 22mm ED ø 32mm external height 5mm			
	No.	510870	Ref. No. —
filter support for dosing pump			
	No.	510916	Ref. No. —
filter for dosing pump			

spare parts



1

No.	510298	Ref. No.	62-144012
description	lip valve dosing pump suitable for DB2/DS5		

self-priming with supporting pressure

ELETTROBAR



1

No.	510298	Ref. No.	62-144012
description	lip valve dosing pump suitable for DB2/DS5		

GERMAC

spare parts



1

No.	510298	Ref. No.	62-144012
description	lip valve dosing pump suitable for DB2/DS5		

accessories

container filters with non-return valve



1

No.	361058	Ref. No.	802065
description	container filter with non-return valve SS hose ø 4x6mm ø 20mm L 56mm		

hoses

pre-rinse hoses


stainless steel flexi hoses



No.	520730	Ref. No.	76-20670600
description	shower hose connections 1/2" L 2400mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW with flexible fabric		




No.	520729	Ref. No.	76-20670601
description	shower hose connections 1/2" L 2800mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW with flexible fabric		



No.	520731	Ref. No.	76-20670602
description	shower hose connections 1/2" L 3200mm SS operating p. 10bar burst p. 90bar t.max. 90°C approval DVGW nominal-ø 8mm with flexible fabric		

drain hoses




No.	530616	Ref. No.	64-27078
description	drain hose L 1500mm A int. ø 25mm B int. ø 25mm outer hose ø 32mm		

industrial hoses

silicone hoses

with fabric

with monofilament braid



No.	530652	Ref. No.	76-20670112
description	silicone hose with monofilament braid ID ø 10mm ED ø 17mm L 1.42m thickness 3.5mm Qty 1.42m		

No.	530693	Ref. No.	76-20670050 76-20670100
description	silicone hose with monofilament braid ID ø 10mm ED ø 17mm L 1m thickness 3.5mm operating p. 4bar t.max. 200°C Qty 1m		

No.	530696	Ref. No.	76-20670302
description	silicone hose with monofilament braid ID ø 13mm ED ø 20mm L 0.29m thickness 4mm Qty 0.29m		

No.	530694	Ref. No.	76-20670300
description	silicone hose with monofilament braid ID ø 13mm ED ø 21mm L 1m thickness 4mm Qty 1m		

No.	530695	Ref. No.	76-20670301
description	silicone hose with monofilament braid ID ø 13mm L 0.15m thickness 4mm		

formed hoses

straight




No.	530708	Ref. No.	76-20670202
description	steam hose ID ø 42mm ED ø 58mm L 150mm for combi-steamer		




No.	530709	Ref. No.	76-20670203
description	steam hose ID ø 42mm ED ø 58mm L 200mm for combi-steamer		

			
1			
No.	530602	Ref. No.	76-20670201
description	steam hose ID ø 42mm ED ø 60mm L 60mm Qty 1 for combi-steamer		

			
1			
No.	530706	Ref. No.	76-20670200
description	steam hose ID ø 42mm L 1000mm for combi-steamer		

			
1			
No.	530710	Ref. No.	76-20670205
description	steam hose ID ø 42mm L 580mm		

			
1			
No.	530603	Ref. No.	76-20670401
description	steam hose ID ø 60mm ED ø 68mm L 120mm Qty 1 for combi-steamer		

			
1			
No.	530605	Ref. No.	76-20670400
description	steam hose ID ø 60mm L 1000mm steam		

miscellaneous

			
1			
No.	530066	Ref. No.	76-21121302
description	formed hose ID ø 24mm ED ø 30mm L 380mm		

fittings, hose and pipe connectors

hose connectors

without screw connection

			
1			
No.	361683	Ref. No.	76-20620301
description	hose connector plastic hose ø 10-10mm 2-way		

hose connectors

producer-specific

			
1			
No.	698612	Ref. No.	76-84641300
description	T-piece thread 3/4" ET - 1/2" ET - 3/4" IT plastic		

ancillary products

silicone

food-grade silicones



1

No.	890106	Ref. No.	76-50060200
description	silicone TB40 transparent tube 90g -40 up to +160°C		
description	<p>Tomabond - TB40 - tube 90g - transparent</p> <p>For flexible sealing in drinking water, food, water and industrial kitchen areas. Securely joins glass, metal, wood-based materials, ceramic and plastics with high adhesion (1.1 N/mm²). Fungicide-, algicide- and solvent-free, ageing-resistant. Temperature-resistant from -40 °C to +160 °C. Tested and approved by KTW / KSW.</p>		

clamps

hose clamps

DIN 3017 - W2



1

No.	520112	Ref. No.	76-20660202
description	hose clamp ø 12-20mm width 9mm Qty 10 pcs DIN 3017		



1

No.	520114	Ref. No.	76-20660506
description	hose clamp ø 20-32mm width 9mm Qty 10 pcs DIN 3017		



1

No.	520118	Ref. No.	081599 76-20660300
description	hose clamp ø 50-70mm width 9mm Qty 5 pcs DIN 3017		



1

No.	520119	Ref. No.	76-20660516
description	hose clamp ø 60-80mm width 9mm Qty 5 pcs DIN 3017		



1

No.	520454	Ref. No.	76-20660505
description	hose clamp ø 70-90mm width 9mm Qty 5 pcs DIN 3017		



1

No.	520117	Ref. No.	76-20660504
description	hose clamp stainless steel ø 40-60mm width 9mm Qty 5 pcs DIN 3017		

DIN 3017 - W4



1

No.	520120	Ref. No.	81594
description	hose clamp SS W4 ø 12-20mm width 9mm Qty 1 pcs DIN 3017		

double wire clamps



1

No.	520916	Ref. No.	76-20660518
description	hose clamp ø 30mm wire gauge ø 2.7mm chrome-plated steel Qty 1 pcs		



1


No.	560570	Ref. No.	76-20660519
description	hose clamp ø 35.6mm wire gauge ø 3mm Qty 1 pcs		

tools

cleaning tools

descaling pumps


descaling pumps



fastening material


rivets/rivet nuts

sealed blind rivets









screws

countersunk screws




hexagonal screws



nuts

cap nuts





hexagonal nuts

hexagonal nuts metric (without norm)



1

No.	530881	Ref. No.	76-11060220
-----	--------	----------	-------------

description	hexagonal nut thread M6 H 3mm WS 10 SS Qty 25 pcs for combi-steamer CPC-Linie
-------------	---



1

No.	520230	Ref. No.	76-30041406
-----	--------	----------	-------------

description	nut thread M14x1.5 H 5mm WS 19 zinc-coated steel Qty 1 pcs
-------------	--

washers

spring rings



1

No.	560122	Ref. No.	76-12050360
-----	--------	----------	-------------

description	lock washer ID ø 5.2mm ED ø 9mm SS DIN127 Qty 20 pcs for thread M5
-------------	--

spring washers



1

No.	696429	Ref. No.	76-20161455
-----	--------	----------	-------------

description	spring washer ID ø 20.5mm ED ø 40mm steel Qty 1 pcs
-------------	---

washers

DIN 125A



1

No.	560312	Ref. No.	76-13100160
-----	--------	----------	-------------

description	plain washer ID ø 10.5mm ED ø 20mm thickness 2mm SS Qty 1 pcs DIN 125A for thread M10
-------------	---



1

No.	560113	Ref. No.	76-13060120
-----	--------	----------	-------------

description	plain washer ID ø 6.4mm ED ø 12mm thickness 1.6mm SS Qty 20 pcs DIN 125A for thread M6
-------------	--



1

No.	560114	Ref. No.	76-13080160
description	plain washer ID ø 8.4mm ED ø 16mm thickness 1.6mm SS Qty 20 pcs DIN 125A for thread M8		

tooth lock washers

miscellaneous



1

No.	520228	Ref. No.	76-30041405
description	tooth lock washer ID ø 15.3mm ED ø 24mm steel Qty 1 pcs for thread M14		

fasteners

clamps

hose clamps

DIN 3017 - W2



1

No.	520112	Ref. No.	76-20660202
-----	--------	----------	-------------

description	hose clamp ø 12-20mm width 9mm Qty 10 pcs DIN 3017		
-------------	--	--	--



1

No.	520114	Ref. No.	76-20660506
-----	--------	----------	-------------


description	hose clamp ø 20-32mm width 9mm Qty 10 pcs DIN 3017		
-------------	--	--	--



1

No.	520118	Ref. No.	081599 76-20660300
-----	--------	----------	-----------------------

description	hose clamp ø 50-70mm width 9mm Qty 5 pcs DIN 3017		
-------------	---	--	--

			
1			
No.	520119	Ref. No.	76-20660516
description	hose clamp ø 60-80mm width 9mm Qty 5 pcs DIN 3017		

			
1			
No.	520454	Ref. No.	76-20660505
description	hose clamp ø 70-90mm width 9mm Qty 5 pcs DIN 3017		


			
1			
No.	520117	Ref. No.	76-20660504
description	hose clamp stainless steel ø 40-60mm width 9mm Qty 5 pcs DIN 3017		

DIN 3017 - W4

			
1			
No.	520120	Ref. No.	81594
description	hose clamp SS W4 ø 12-20mm width 9mm Qty 1 pcs DIN 3017		

double wire clamps


			
1			
No.	520916	Ref. No.	76-20660518
description	hose clamp ø 30mm wire gauge ø 2.7mm chrome-plated steel Qty 1 pcs		

			
1			
No.	560570	Ref. No.	76-20660519
description	hose clamp ø 35.6mm wire gauge ø 3mm Qty 1 pcs		

consumables


sealants and adhesives


food-grade silicones


			
1			
No.	890106	Ref. No.	76-50060200
description	silicone TB40 transparent tube 90g -40 up to +160°C		
description	<p>Tomabond - TB40 - tube 90g - transparent</p> <p>For flexible sealing in drinking water, food, water and industrial kitchen areas. Securely joins glass, metal, wood-based materials, ceramic and plastics with high adhesion (1.1 N/mm²).</p> <p>Fungicide-, algicide- and solvent-free, ageing-resistant.</p> <p>Temperature-resistant from -40 °C to +160 °C</p> <p>Tested and approved by KTW / KSW.</p>		

fuses


fine fuses

			
1			
No.	358597	Ref. No.	76-30190400
description	fine fuse size ø5x20mm 0.5A slow-acting rated 250V Qty 10 pcs		

			
1			
No.	358603	Ref. No.	76-30190120
description	fine fuse size ø5x20mm 2A slow-acting rated 250V Qty 10 pcs		

			
1			
No.	358607	Ref. No.	76-30190200
description	fine fuse size ø5x20mm 6.3A slow-acting rated 250V Qty 10 pcs		

ø5x30mm 500V

			
1			
No.	358735	Ref. No.	76-40010218
description	fine fuse size ø5x30mm 6.3A medium lag rated 500V Qty 10 pcs		



ø6.3x32mm 250V



1

No.	358791	Ref. No.	76-40010224
description	fine fuse size ø6.3x32mm 6.3A slow-acting rated 250V Qty 10 pcs		

screw locks

D0-system (NEOZED)



1

No.	358045	Ref. No.	76-30190403
description	fuse size D02 35A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		



1

No.	358046	Ref. No.	76-30190404
description	fuse size D02 50A rated 250/400V E18 ø 15mm L 36mm Qty 10 pcs		