Professionale pentru echipamente profesionale



heating elements

heating elements for coffee machine



1			
No.	417241	Ref. No.	C-0353
description	hole distance 58m L3 40mm H1 34mr sleeves ø 4.5mm le sleeve eccentric, n	m L 140mm W 32m m H2 26mm hole ø ength thermostat sl	g circuits 3 mounting ø 40mm Im H 60mm L1 45mm L2 60mm 10mm tube ø 8mm thermostat eeves 126mm thermostat r of thermostat sleeves 1 con- lange

1		!-	
No.	417360	Ref. No.	C-0527
description	hole distance 58m L3 75mm H1 34mr sleeves ø 4.5mm le sleeve eccentric, n	m L 180mm W 32m n H2 26mm hole ø ength thermostat sl	g circuits 3 mounting ø 40mm Im H 60mm L1 45mm L2 60mm 10mm tube ø 8mm thermostat eeves 130mm thermostat r of thermostat sleeves 1 con- lange

No.	417242	Ref. No.	C-0356
description	hole distance 58m L3 230mm H1 33m thermostat sleeve mostat sleeve ecce	m L 340mm W 35m nm H2 25mm windi s ø 5mm length the	g circuits 3 mounting ø 39mm nm H 58mm L1 46mm L2 64mm ngs 3 hole ø 10mm tube ø 8mm ermostat sleeves 144mm ther- number of thermostat sleeves 1 ole flange

1					
No.	417243	Ref. No.	C-0358		
description	hole distance 58m L3 450mm H1 35m thermostat sleeve mostat sleeve ecce	nm L 550mm W 34m nm H2 25mm windi s ø 5mm length the	g circuits 3 mounting ø 39mm nm H 60mm L1 50mm L2 50mm ngs 3 hole ø 10mm tube ø 8mm rmostat sleeves 142mm ther- number of thermostat sleeves 1 ole flange		

accessories

flange gaskets



No.	528740	Ref. No.	C-0361
description			mm hole ø 9.5mm hole distance EM for heating element coffee

thermostats

control and safety thermostats

EGO

safety thermostats



IVO.	3/3302	rei. No.	C-0457
	probe L 130mm ca		77°C 3-pole 20A probe ø 4mm m capillary pipe isolated

switches and momentary switches

rocker/momentary rocker switches



30x22mm

1			
No.	347813	Ref. No.	C-0474
description		nnection male fast	nts 30x22mm orange 2CO 250V on 6.3mm ambient temperature

No.	301188	Ref. No.	C-0479
escription		nection male fasto	nts 30x22mm black 2NO/2NO n 6.3mm ambient temperature
cessories for	301188		

301036

	measurement	smm	
1			
No.	346110	Ref. No.	C-0418

Ref. No.

protective cover internal size 30x22mm for rocker switch mounting

	3 .0 0		
lescription		connection male fa	nts 30x22mm red 2NO 250V 16A aston 6.3mm ambient tempera-



accessories

blank elements



No.	347281	Ref. No.	C-0470
escription	hlank external size	30x30mm black	

microswitches

pin-plunger actuated

M12



1					
No.	345350	Ref. No.		C-0465	
description	M12x0.75 th 6.3mm strok	microswitch with plunger mounting distance 22mm thread M12x0.75 thread L 16mm 250V 16A 1CO connection male faston 6.3mm stroke 4mm ambient temperature max. 125°C type EF83161.3 actuating force: 66g			
accessories for	345350	345350			
	No.	345351	Ref. No.	_	
\bigcirc	nut thread N	И12x0.75 H 1.6mr	n WS 14 chrome-pl	ated brass Qty 1 pcs	


system switches (ROLD)



No.	345536	Ref. No.	C-0486
description	element holder m	ounting ø 16mm fl	at black



No.	345538	Ref. No.	C-0481
description	push button ø 11.	9mm black	



key lock switches

1		-		
	No.	400297	Ref. No.	C-0135
desc	ription	key lock switch 1 group thread M12x1 1NO mounting ø 12mm cable length 300mm		

rotary switches

BREMAS

A3200 series



No.	345114	Ref. No.	C-0121
			5 type CS0325832 600V 32A uare connection screw

A4000 series



No.	347712	Ref. No.	— C-0154
description	rotary switch 3 1-0-2 sets of contacts 5 690V 40A shaft ø 5x5mm shaft L 21mm shaft square with knob connection screw		

accessories



No.	527259	Ref. No.	C-0130
description	knob push-in ø 3	4/60mm shaft ø 5x5	mm black H 21.4mm L 49mm

lamps

indicator lights

indicator lights 2-piece (lens and indicator lamp)

indicator light lenses

ø10mm (type SRZ-3



'					
No.	359123 Ref. No. C-0254				
description	indicator light housings mounting measurements ø10mm green round Qty 1 pcs				
accessories for	359123				
	No.	359132	Ref. No.	C-0262	
1		green 250V connect t temperature max		5.3mm protecti-	



No. 359125 Ref. No. C-0253 description indicator light housings mounting measurements Ø10mm red round Qty 1 pcs

indicator lamps for socket type SRZ / SDK / SDY / SFK				
description indicator lamp 230V clear connection male faston 6.3mm ø 8mm				

1	To the last of the		
No.	359132	Ref. No.	C-0262
		reen 250V connection temperature max. 85	on male faston 6.3mm protecti- 5°C

relays

level relays



electronics

PCBs



central units



No.	402501	Ref. No.	C-0147
description	central unit 240V 5	50/60Hz type DOS I	RL2 3GR+3THE+RL/ON-OFF/C



No.	402500	Ref. No.	C-0148
description	central unit 240V	50/60Hz type DOS	RL2 3GR+RL+THE/C voltage AC

dosing electronics

GICAR



No.	401066	Ref. No.	C-0015/24N
description	level relay 230V vo Manuale DELUXE F	_	connection F6.3 type Dosatura





keypads

front foils



No.	526422	Ref. No.	C-0141
description	keypad foil_black/silver1_75mm W 70mm buttons 2		




No.	526423	Ref. No.	C-0140
description	kevpad foil black/	silver L 75mm W 70	mm buttons 8

keypad units



No.	402722	Ref. No.	C-0603
description		e machine BUTTERF	FLY/MARINA buttons 5 black/







solenoid valves

solenoid valves (water

metal

ODE

solenoid valves steam (water

21A serie




No.	370703	Ref. No.	C-0207
description	nection 1/4" L 40m	nm DN 2.5mm t.ma: I type BDA membra	nlet 1/4" IT outlet 1/4" IT con- x. 140°C -10 up to 140°C ODE anes FKM (water/steam) p max

21A1 series



No.	370093	Ref. No.	C-	0403	
description	solenoid valve 2/2-ways 230VAC body 25-F39 DN 2.5mm slide-on receptacle DIN -10 up to 140°C ODE type series 21A1 coil type BDA membranes FKM p max 14bar 50/60Hz silicone flange 32x32mm				
spare parts for	370093				
	No.	371150	Ref. No.	_	
	solenoid coil ODE 230VAC 16VA coil type BDV seat ø 13.5mm 750Ohm				
accessories for	370093				
SYCastel Co.	No.	371090	Ref. No.	_	
	power socket plu	ug type DIN 43650	OA screw		






pressure switches

for coffee machines



electrodes



flow meters and flow sensors

flow meters



pumps

booster pumps II

pump heads

FLUID-O-TECH




No.	500064	Ref. No.	C-	0521		
description	pump head PO204 FLUID-O-TECH L 82mm 200l/h connection 3/8" GAS with bypass brass clip connection for coffee machine shaft ø 4.8x11mm					
accessories for	500064	500064				
	No.	520126	Ref. No.	_		
\hookrightarrow	clamp for pun	np/motor				

electric accessories

cables

ribbon cables

group 3



equipment-specific units

for espresso machines

filter holders

filter holders standard

filter holders (complete)



No.	526453	Ref. No.	C-0532N	
description	filter holder double complete ID ø 61.7mm outlet distance 47.6mm mounting ø 82.6			





The filter holders short No. 529058 Ref. No. N/A filter holder mounting ø 83mm outlet 3/8" ID ø 61.5mm handle M12x1.75 wedge hight 10mm wedge position horizontal number of wedges 2 lever inclined chrome-plated, polished

for 1 cup No. 526479 Ref. No. C-0499 coffee filter Ø 69.5mm mounting Ø 60mm H 24mm cups 1 amount of coffee 7g perforation Ø 0.3mm
























springs 1 WWWWW No. 526442 Ref. No. C-0311 description compression spring Ø 10.8mm L 57.2mm wire gauge Ø 1mm






expansion valves						
with hose	with hose connection					
1	1					
No.	526452	Ref. No.	C-0379			
description	expansion valve T1: 1/4" ET hose ø 9.5mm BL 42mm					









































gaskets				
1				
No.	526439	Ref. No.	C-0424	
description gasket ED ø 13mm ID ø 4mm H 4mm for filling valve				






level gla	level glasses					
level glas	level glasses					
pressure r	ings					
10	10					
No.	526434	Ref. No.	C-0258			
description	press ring D1 ø 14.7mm D2 ø 11.6mm thickness 3.7mm conical					






knobs

steam/water taps steam/water taps No. 111318 Ref. No. C-0280 description knob ø 50mm thread Tr18x2 black





accessories					
1 ~					
No.	111273	Ref. No.	C-0282		
description	cotter pin ø 1.3mm L 25mm				




knob push-in ø 34/60mm shaft ø 5x5mm black H 21.4mm L 49mm




description






















sealing washers


fibre gaskets						
C						
No.	528210	Ref. No.	C-0272			
description	flat gasket FIBER ED ø 21mm ID ø 16.5mm thickness 2mm Qty 1 pcs					


copper gaskets							
DIN-7603-A							
No.	527961	Ref. No.	C-0430				
description	flat gasket copper ED ø 21mm ID ø 17.2mm thickness 1.5mm						




DIN-7603-C						
No.	526433	Ref. No.	C-0256			
description	gasket coppe	gasket copper ED ø 18mm ID ø 14mm thickness 2mm				











springs








, MM	MMM	1		
No.	527992	Ref. No.	C-0429	
description	compression spring ø 8mm L 32mm wire gauge ø 0.5mm			

manometers



valves and tank inlets



fastening material





