

Professionall

Solutii profesionale pentru echipamente profesionale



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

ROSSI

switches and momentary switches

rocker/momentary rocker switches

30x22mm



No.	301002	Ref. No.	3253
description	rocker switch mounting measurements 30x22mm orange 2NO 250V 16A illuminated 0-I connection male faston 6.3mm ambient temperature max. 85/125°C protection IP65		
accessories for	301002		
	No.	301036	Ref. No. 3253
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		



No.	301036	Ref. No.	3253
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

labelled



No.	346142	Ref. No.	3253
description	rocker switch mounting measurements 30x22mm orange 2NO 250V 16A illuminated 0-I connection male faston 6.3mm ambient temperature max. 85°C protection IP65 with cover cap		
For models:	MC6665, RR45A6666, RR45PST4519, RR45S6672		
accessories for	346142		
	No.	301036	Ref. No. 3253
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

push/momentary push switches

30x22mm



No.	301036	Ref. No.	3253
description	protective cover internal size 30x22mm for rocker switch mounting measurementsmm		

microswitches

pin-plunger actuated



No.	345105	Ref. No.	00751.2.00.08 3202
description	microswitch with plunger 250V 16A 1CO connection male faston 6.3mm L 28mm ambient temperature max. 125°C mounting distance 22mm type SM-51 actuating force: 280g black		
For models:	MC6665, RR45A6666		

relays


power relays

with male contacts

female contact 2.0mm





No.	380358	Ref. No.	01955.2.00.08
description	power relays connection 2.0 plug-in connection		
accessories for	380358		
	No.	380378	Ref. No. —
	relay socket 2-pole 55/85 dimensions 70.5x30x27mm 250V voltage AC 10A FINDER manuf. no. 94.72		
	No.	380384	Ref. No. —
	relay socket 2-pole contacts male faston 2.8mm 250V voltage AC 10A W 23mm for		
	No.	380399	Ref. No. —
	relay socket 4-pole dimensions 76.2x27x86.1mm 250V voltage AC 1A FINDER manuf. no. 94.94.3		



No.	380377	Ref. No.	3068.10
description	power relays FINDER 220-240VAC 10A 2CO connection F2 plug-in connection manuf. no. 55.32.8.230.0000 94.92.3 250V		
accessories for	380377		
	No.	380341	Ref. No. —
	relay socket 4-pole contacts 12 300V voltage AC 6A Italiana Relè manuf. no. ZMD4		
	No.	380378	Ref. No. —
	relay socket 2-pole 55/85 dimensions 70.5x30x27mm 250V voltage AC 10A FINDER manuf. no. 94.72		

Table continues overleaf



accessories for 380377				
	No.	380384	Ref. No.	—
relay socket 2-pole contacts male faston 2.8mm 250V voltage AC 10A W 23mm for				
	No.	380399	Ref. No.	—
relay socket 4-pole dimensions 76.2x27x86.1mm 250V voltage AC 1A FINDER manuf. no. 94.94.3				

motors

gear motors

for ice-cube maker

miscellaneous



1

No.	499175	Ref. No.	HBM 63C
description	gear motor ROSSI type HBM 63C 230V voltage AC 50Hz shaft ø 24mm L 350mm W 190mm H 160mm for flake ice maker 180W		

pumps

booster pumps II

pump heads

ROSSI



1

No.	504238	Ref. No.	RF140S
description	pump RF140SO9E ROSSI L 82mm 100l/h connection 3/8" NPT with bypass brass clip connection for coffee machine shaft ø 4.8x11mm		

equipment-specific units for coffee grinders

grinding burrs

grinding burrs straight

standard



1

No.	527213	Ref. No.	5198
description	grinding burrs pair turn direction left D1 ø 50mm ID ø 30mm H 8mm tooth spacing 2.5mm hole ø 4.5mm bore ø 7.5mm mounting ø 40 straight suitable for BRASILIA		



1

No.	527201	Ref. No.	5185
description	grinding burrs pair turn direction left D1 ø 50mm ID ø 30mm H 8mm tooth spacing 2.5mm hole ø 4.5mm bore ø 7.5mm mounting ø 40 straight suitable for BRASILIA, ROSSI equiv. no.		



1

No.	526518	Ref. No.	M4433.64
description	grinding burrs pair turn direction left D1 ø 63.3mm ID ø 38mm H 9mm tooth spacing 2.5mm hole ø 5mm bore ø 8.5mm mounting ø 50 suitable for BRASILIA, ROSSI teeth 12/60		




1

No.	531206	Ref. No.	N/A
description	grinding burrs pair turn direction left D1 ø 63.3mm ID ø 38mm H 9mm tooth spacing 2.5mm hole ø 5mm bore ø 8.5mm mounting ø 50 suitable for BRASILIA, ROSSI teeth 16/60		

			
1			
No.	527202	Ref. No.	4433
description	grinding burrs pair turn direction left D1 ø 63.3mm ID ø 38mm H 9mm tooth spacing 3mm hole ø 5.5mm bore ø 8.5mm mounting ø 50 straight suitable for BRASILIA, ROSSI equiv. no. 00058/BRASILIA, 4433/ROSSI		
For models:	RR45A6666, RR45PST4519, RR45S6672		

			
1			
No.	527215	Ref. No.	N/A
description	grinding burrs pair turn direction left D1 ø 83mm ID ø 45mm H 10mm tooth spacing 3.5mm hole ø 6.5mm bore ø 10.5mm mounting ø 65 straight suitable for BRASILIA, ROSSI		


grinding burrs conical

			
1			
No.	527237	Ref. No.	5585
description	grinding burrs pair turn direction right D1 ø 68mm D2 ø 49mm H 25mm shaft ø 13mm with flute suitable for ROSSI		
For models:	MC6665		

grinding burrs holders

			
1			
No.	527268	Ref. No.	4984
description	grinding burr holder type RR45, CC45 suitable for ROSSI equiv. no. 4984		
For models:	RR45A6666, RR45PST4519, RR45S6672		

screws


			
1			
No.	560365	Ref. No.	1256
description	flat-headed bolt thread M4 thread L 8mm SS DIN 7985/ISO 7045 Qty 1 pcs intake Phillips head ø 8mm head thickness 3mm		
For models:	MC6665, RR45A6666, RR45PST4519, RR45S6672		

dosing containers

dosing container lids


			
1			
No.	527306	Ref. No.	01430.0.00.02 2746
description	lid for dosing container ø 118mm		
For models:	MC6665, RR45PST4519, RR45S6672		


adjusting screws

			
1			
No.	527551	Ref. No.	09610.0.00.02 3907 3907.10
description	adjusting screw for dosing container thread M8 L 40mm plastic		

springs

group 1

			
1			
No.	526509	Ref. No.	2020
description	compression spring ø 8.5mm L 95mm wire gauge ø 0.8mm right		

			
1			
No.	526513	Ref. No.	2049
description	tension spring ø 11mm total length 44mm wire gauge ø 0.9mm L1 35mm for lever		
For models:	MC6665, RR45A6666, RR45S6672		

glass cylinders

			
1			
No.	527305	Ref. No.	2652
description	glass cylinder for dosing container ø 125mm H 60mm plexiglas		
For models:	MC6665, RR45A6666, RR45S6672		



coffee presses

coffee presses



1

No.	527549	Ref. No.	2673
description	coffee press ø 57mm H 98mm plastic		

sector plates



1

No.	527553	Ref. No.	01772.0.00.01 3321
description	sector plates SS		
For models:	MC6665, RR45A6666, RR45S6672		

miscellaneous



1

No.	526541	Ref. No.	S2631.10
description	frame for lid L 73.5mm W 44mm H 8mm mounting pos. lower plastic		

stars

upper



1

No.	527552	Ref. No.	01485.0.00.02 2727
description	star mounting pos. upper ø 112mm H 19mm		
For models:	MC6665, RR45A6666, RR45S6672		

adjustment mechanism

lockable adjustment



1

No.	526536	Ref. No.	2635
description	pressure pin for setting ring L 20mm W 17mm shaft ø 5mm shaft length 26mm		
For models:	RR45PST4519, RR45S6672		

setting rings



1

No.	527415	Ref. No.	2720
description	setting ring		
For models:	RR45PST4519, RR45S6672		



1

No.	527400	Ref. No.	28371
description	setting ring mounting ø 76mm ø 99mm ID ø 51mm H 34mm suitable for ROSSI for RR45A equiv. no. 28371		

coffee beans containers

coffee beans containers



1

No.	527355	Ref. No.	13808.4.00.09 2675 S2675.500.1
description	container complete ø 210mm H 290mm seat ø 51mm		

supports



1

No.	531168	Ref. No.	N/A
description	support for coffee beans container intake conical seat ø 52.5-51.5mm suitable for ROSSI		



1

No.	531169	Ref. No.	N/A
description	support for coffee beans container intake conical seat ø 52.5-51mm suitable for ROSSI		

support for filter holder



1

No.	527891	Ref. No.	2722
description	filter holder support for dosing unit L 71mm W 98mm H 25mm plastic		
For models:	RR45A6666, RR45PST4519, RR45S6672		

equipment feet and end caps

equipment feet with stem



1

No.	526537	Ref. No.	M2740
description	equipment foot ø 29mm H 24mm bore ø 5.5mm		

springs

compression springs



1

No.	526509	Ref. No.	2020
description	compression spring ø 8.5mm L 95mm wire gauge ø 0.8mm right		



1

No.	527555	Ref. No.	00898.0.00.03 2029
description	compression spring ø 9.9mm L 80mm wire gauge ø 0.8mm		
For models:	MC6665, RR45A6666, RR45S6672		

tension springs



1

No.	526513	Ref. No.	2049
description	tension spring ø 11mm total length 44mm wire gauge ø 0.9mm L1 35mm for lever		
For models:	MC6665, RR45A6666, RR45S6672		

fastening material

screws

flat-headed bolts



1

No.	560365	Ref. No.	1256
description	flat-headed bolt thread M4 thread L 8mm SS DIN 7985/ISO 7045 Qty 1 pcs intake Phillips head ø 8mm head thickness 3mm		
For models:	MC6665, RR45A6666, RR45PST4519, RR45S6672		

washers

washers

DIN 9021



1

No.	560117	Ref. No.	M1605
description	plain washer ID ø 6.4mm ED ø 18mm thickness 1.5mm SS Qty 20 pcs DIN 9021 for thread M6		



fasteners

retaining rings

DIN 6799



No.	516198	Ref. No.	1623
description	retaining ring E D1 ø 6mm D2 ø 12mm SS DIN 6799 thickness 0.7mm for shaft ø 7-9mm		
For models:	MC6665, RR45A6666, RR45S6672		