
# Professionale pentru echipamente profesionale



## 4

#### heating elements

#### heating elements for coffee machine



1			
No.	417276	Ref. No.	5050100
description		8mm tube ø 8.3mm cor	ng circuits 1 thread 1¼" L 145mm nection M4 immersion heater

1		幸	
No.	417273	Ref. No.	5050710
description	hole distance 74m mostat sleeves ø 7 thermostat sleeves	m L 210mm W 35m mm length thermo	g circuits 2 mounting ø 42mm im H 27mm hole ø 9.5mm ther- stat sleeves 195mm number of ve bottom/centre tube ø 8.3mm ble flange

1		###	
No.	417275	Ref. No.	5050205
description	W 35mm H 24m thermostat sleev mostat sleeve ce	m tube ø 8.3mm ther ves 160mm number o	g circuits 2 thread 1¼" L 285mm mostat sleeves ø 7mm length of thermostat sleeves 1 ther- immersion heater connection 37

1		訓	
No.	417274	Ref. No.	5050220
description	W 35mm H 24mm thermostat sleeve	n tube ø 8.3mm ther es 160mm number o	g circuits 2 thread 1¼" L 370mm mostat sleeves ø 7mm length of thermostat sleeves 1 ther- mmersion heater flange with

1		<b>#</b>	
No.	417272	Ref. No.	5050720 5050720+2001010
description	hole distance 74m L3 250mm H1 27m stat sleeves ø 7mm	m L 335mm W 35m nm H2 23mm hole on length thermostar ber of thermostat s	g circuits 2 mounting ø 42mm nm H 60mm L1 25mm L2 60mm ø 9.5mm tube ø 8.3mm thermo- t sleeves 195mm thermostat eleeves 1 connection M6 immer-



1			
No.	417271	Ref. No.	5050730
			240V heating circuits 2 mounting


description

L2 60mm L3 430mm H1 27mm H2 23mm hole ø 9.5mm tube ø
8.3mm thermostat sleeves ø 7mm length thermostat sleeves 195mm
thermostat sleeve centre number of thermostat sleeves 1 connection
M6 immersion heater 2 hole flange



#### accessories

# PTFE gaskets No. 528022 Ref. No. 2001001 description flat gasket PTFE ED ø 52mm ID ø 41mm thickness 2mm size 1¼" Qty 1 pcs suitable for CARIMALI, FAEMA, MARZOCCO, PAVONI







#### thermostats

#### bi-metal thermostats

#### safety bi-metal thermostats



No. 390690 Ref. No. 5013030

bi-metal thermostat switch-off temp. 200°C 1NC 1-pole 10A connection F6.3 thread M4 mounting ø 16mm

#### bi-metal thermostats



1			
No.	390323	Ref. No.	5013025
description		mostat hole distancem	m switch-off temp. 145°C 1NC

#### control and safety thermostats

#### PRODIGY / FIRT

#### control thermostats



1/			
No.	390691	Ref. No.	5013010
description		pe 360mm shaft ø 6	16A probe ø 6mm probe L 6x4.6mm shaft L 6mm shaft

#### various

description

#### safety thermostats



6mm probe L 92mm capillary pipe 980mm capillary pipe isolated

#### switches and momentary switches

#### rocker/momentary rocker switches


#### 30x22mm




No.	347207	Ref. No.	5003240
escription	20A illuminated 0-	I connection male f	nts 30x22mm white 2NO 250V faston 6.3mm ambient tempera-
	ture max 120/55°0	nrotection IP65 w	ith rubber collar

## 1

1				
No.	301001	Ref. No.	500	03080
description		nnection male fa	nents 30x22mm re ston 6.3mm ambie	
accessories for	301001			
	No.	301036 internal size 30x2	Ref. No.	— vitch mounting





#### push/momentary push switches

measurementsmm

#### 20.6x16.4mm




No.	347205	Ref. No.	5003035
escription		ion male faston 6.3	ts 20.6x16.4mm chrome 2NO mm ambient temperature max.



# 28.5x28.5mm

en 2NO ire max.




#### ø25mm No. 345160<sup>1</sup> Ref. No. 5003210 push switch mounting ø 25mm red 2NO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 85°C description protection IP40

<sup>1</sup>illuminated

#### toggle switches

#### M12x0.75 No. 346520 Ref. No. 5003100 toggle switch thread M12x0.75 2CO 250V 15A ON-OFF-ON male description faston 6.3mm with neutral position t.max. 85/55°C




#### microswitches

#### pin-plunger actuated



	No.	347211	Ref. No.	5003301	
I	description	microswitch with plunger thread M10x0.75 250V 16A 1CO connecti-			
	uescription	on male faston 6.3	erature max. 125°C		



#### roller actuated

#### roller 0°



No.	345639	Ref. No.	5003310
escription	screw connection l	L1 49mm ambient t	16A 1CO connection solder/ temperature max. 125°C thread ce 25mm actuating force: 300g

#### rotary switches


#### **BREMAS**

#### A1700 series




No.	347198 <sup>1</sup>	Ref. No.	5005105		
description rotary switch 2 0-1 sets of contacts 4 type CA0200004V 400 shaft ø 5x5mm shaft L 19mm shaft square connection screw					

incl. rubber protective sleeve









#### **KRAUS & NAIMER**

#### rotary switches




No.	347209¹	Ref. No.		5005020 5005025		
description	rotary switch 3 0-1-2 sets of contacts 6 type CA20-ATX12X018 400V 25A shaft ø 22.5mm connection screw code 97/000400 marking I-3461*06					
accessories for	347209					
- mells	No.	347214	Ref. No.	5005200		
A.A.	knob shaft ø 6mm shaft L 20mm complete mounting ø 22mm lever length 35mm					
	No.	347215	Ref. No.	5005210		
16	knob complete 2 shaft ø 6mm shaft L 20mm complete L 48mm mounting ø 22mm W 48mm mounting distance 36mm					

#### <sup>1</sup>incl. collar



1				
<b>No.</b> 347210 <b>Ref. No.</b> 5005028				05028
description rotary switch sets of contacts 6 type CA25-AT09X016 490V connection screw code I-3461*05			5 490V 30A	
accessories for	347210			
-	No.	347214	Ref. No.	5005200
All	knob shaft ø 6mm shaft L 20mm complete mounting ø 22mm lever length 35mm			
	No.	347215	Ref. No.	5005210
T	•		oft L 20mm comple nting distance 36m	

#### 1 No. 347215 Ref. No. 5005210 knob complete 2 shaft ø 6mm shaft L 20mm complete L 48mm description mounting ø 22mm W 48mm mounting distance 36mm




#### lamps


indicato	indicator lights					
indicato	indicator lights (complete)					
ø10mm	ø10mm					
with screv	w socket					
1						
<b>No.</b> 359476 <b>Ref. No.</b> 5010030						
description indicator light ø 10mm 110/250V red connection male faston 6.3mm						

1	<b>(1)</b>		
No.	359475	Ref. No.	5010003
description indicator light ø 10mm 125V green connection			connection male faston 6.3mm

ø16mm				
with plug-	in socket			
1				
No.	<b>No.</b> 359474 <b>Ref. No.</b> 5010006			
description	indicator light ø	16mm 230V gree	n connection male	faston 6.3mm
spare parts for 359474				
all.	No.	345601	Ref. No.	_
750	indicator lamp holder V ø 11mm			
_	No.	359132	Ref. No.	_
No.	indicator lamp green 250V connection male faston 6.3mm protection IP54 ambient temperature max. 85°C			5.3mm protecti-
_	No.	359247	Ref. No.	_
3	indicator light ler	ns ø 12.2mm gree	en	







### solid state relays

#### miscellaneous




### relays

#### level relays



No.	402103	Ref. No.	5030363
	level controller 23 NRL30/1E-2C/F	0/240V voltage AC	50/60Hz connection F6.3 type



#### electronics

#### **PCBs**













#### central units













#### dosing electronics








### keypads

#### keypad units





















# 1 electric component

#### solenoid valves

#### solenoid valves (water)

#### metal

#### LUCIFER

spare parts and accessories

#### valve bodies



No.	370061	Ref. No.	BFC01 BFC02	
description	solenoid valve body LUCIFER-PARKER 3-ways outer cone			

#### ODE

solenoid valves steam (water)

#### 21A1 series



No.	370093	Ref. No.		5020115	
description	solenoid valve 2/2-ways 230VAC body 25-F39 DN 2.5mm slide-on receptacle DIN -10 up to 140°C ODE type series 21A1 coil type BDA membranes FKM p max 14bar 50/60Hz silicone flange 32x32mm				
spare parts for	370093				
	No.	371150	Ref. No.	_	
	solenoid coil ODE 230VAC 16VA coil type BDV seat ø 13.5mm 7500hm				
accessories for	r 370093				
SPCnotel	No.	371090	Ref. No.	_	
1	power socke	t plug type DIN 43	650A screw		

# 1 No. 370572 Ref. No. 5020055 description solenoid valve brass 3-ways 230VAC DN 1.5mm -10 up to 140°C coil type ADA membranes ruby p max 15bar p min 0bar flange 32x32mm



#### pressure switches


#### for coffee machines

#### miscellaneous



No.	541690	Ref. No.	5006070	
description pressure control pressure type 250V pressure conne			ar connection 1/4" 16A 1-pole	

#### electrodes





### 0

#### equipment-specific units

#### for espresso machines

#### filter holders

#### filter holders standard

#### filter holder without spout



filter holder suitable for BFC/ROYAL1 without outlet mounting ø

description
83mm outlet 3/8" ID ø 62mm wedge hight 10mm wedge position
horizontal number of wedges 2 lever inclined



position horizontal number of wedges 2 lever straight

# filter holders short No. 526528 Ref. No. 4650100 filter holder mounting ø 82mm outlet 3/8" ID ø 62mm handle M12x1.75 wedge hight 10mm wedge position horizontal number of wedges 2 lever straight chrome-plated brass





wedges 2 lever inclined chrome-plated brass














# brewing units shower screens flat No. 529084 Ref. No. 4630033 description shower screen ø 52mm hole ø 6.4mm













brewing units manual

componer	11.3					
drain units						
drain pipe:	drain pipes					
1						
No.	527931	Ref. No.	0530060			
description	drain pipe tl 26	hread 1/2" int. ø 1 11.5m	m int. ø 2 15mm L 35.5mm WS			









































Table continues overleaf







































































bushes				
10				
No.	526010	Ref. No.	054	10060
description	bush steam/wate brass	er tap D1 ø 10.5m	m D2 ø 9mm ID ø	6.3mm H 4.6mm
accessories for	526010			
	No.	526005	Ref. No.	_
77	shaft steam tap o	ข 14.8mm L 92.5m	nm thread M6 bras	S




















































































union nuts					
1					
No.	529706	Ref. No.	0540135		
description	union nut thread 3/8" L 21mm hole ø 12.5mm brass				














levers				
1				
No.	526500	Ref. No.	0510152	
description	lescription lever ø 12mm L 48mm brass			




miscellane	eous		
No.	526503	Ref. No.	0510120
description piston D1 ø 9mm D2 ø 16mm int. ø 1 13mm H 13mm brass			
















level glasses						
level glass	level glasses					
gaskets						
1	1					
<b>No.</b> 529408 <b>Ref. No.</b> 2003010						
description	gasket D1 ø 16mm D2 ø 10mm H 8mm water level glass					








pipes	pipes					
pipes	pipes					
1	1					
No.	527950	Ref. No.	2502006			
description	aspiration tube ø 8mm L 98mm					



















#### knobs

#### steam/water taps

#### steam/water taps



No.	111274	Ref. No.	4001010
description	turning handle ø	41mm thread M18 k	olack

#### knob dial plates




No.	111275	Ref. No.	4001020
description	symbol steam ø 3°	2mm   28mm	



No.	111276	Ref. No.	4001025
description	symbol water ø 32	2mm L 28mm	


#### accessories

No.	528762	Ref. No.	0540020
description	cotter pin ø 1.8mm L 17mm		



#### handles and hand wheels

#### cone handles




#### star handles



### fittings for catering equipment

#### drain taps







#### gaskets

#### O-rings


#### EPDM
















































	)		
No.	527993	Ref. No.	0510190
description	flat gasket PTFE ED ø 18mm ID ø 13mm thickness 2mm Qty 1 pcs		


No.	528314	Ref. No.	0540120	
description flat gasket PTFE ED ø 20mm ID ø 17mm thickness 2mm Qty 1 pcs suitable for Astoria/Azkoyen/Espressa/Wega				





No.	527970	Ref. No.	0541060
<b>description</b> flat gasket PTFE ED ø 24mm ID ø 18mm thickness 2mm Qty 1 pcs			



No.	526014	Ref. No.	0520050	
	flat gasket PTFE ED ø 35mm ID ø 30mm thickness 2mm Qty 1 pcs			











#### springs









## WWW

 No.
 528493
 Ref. No.
 0510110

 description
 compression spring ø 12.6mm L 30mm wire gauge ø 1.9mm

No. 527963 Ref. No. 0540100

description compression spring Ø 12mm L 16.5mm wire gauge Ø 1.5mm steel for steam/water pipes

 No.
 527933
 Ref. No.
 0530045

 description
 compression spring ø 14.2mm L 21mm wire gauge ø 1.8mm SS

 No.
 527934
 Ref. No.
 0530030

 description
 compression spring ø 14.2mm L 45mm wire gauge ø 1.5mm SS

No. 527935 Ref. No. 0530095

description compression spring ø 14.6mm L 33mm wire gauge ø 2mm


 No.
 527969
 Ref. No.
 0541055


 description
 compression spring ø 8mm L 21mm wire gauge ø 0.4mm


 No.
 527992
 Ref. No.
 0510160


 description
 compression spring Ø 8mm L 32mm wire gauge Ø 0.5mm

#### manometers




















#### dosing pumps

### membrane dosing pumps

# self-priming LANG spare parts No. 361311 Ref. No. 0540050 description O-ring EPDM thickness 2mm ID ø 6mm Qty 1 pcs for type N6

#### hoses

#### industrial hoses




## fittings, hose and pipe connectors fittings













#### valves and tank inlets

#### ball valves

#### universal

#### mini hall valves



No. 520722 Ref. No. 3501001

ball valve connection 1/4" IT - 1/4" ET DN8 total length 39mm chrome-plated brass

#### fastening material

#### screws

#### cylinder head bolts

#### DIN 912/ISO 4762



No.	560316	Ref. No.	1103210
description	cylinder head bolt 912/ISO 4762	thread M8 thread	L 25mm WS 6 SS Qty 20 pcs DIN

#### nuts

#### hexagonal nuts

#### hexagonal nuts inch thread



No.	503042	Ref. No.	0510146
description	nut thread 3/8" H 6mm brass WS 22 Qty 1 pcs		

#### washers

#### washers

#### miscellaneous



No.	527955	Ref. No.	0540030
description	plain washer ID ø 6.1mm ED ø 20mm pcs for coffee machine tap		thickness 1.6mm brass Qty 1

#### fasteners

#### cotter pins



#### screw caps



No.	520706	Ref. No.	3530005
description	screw cap thread 1/4" WS 17		



No.	520705	Ref. No.	3530022
description	screw cap thread 1/8" WS 16		

