Professionale pentru echipamente profesionale



Spare parts suitable for

THUNDERBIRD

switches and momentary switches

push/momentary push switches

27.2x22.2mm



No.	345092 ¹	Ref. No.	ARM02182
description	momentary push switch mounting measurements 27.2x22.2mm green 2NO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 85°C protection IP40		

¹illuminated



No.	345090 ¹	Ref. No.	ARM02181
description	momentary push switch mounting measurements 27.2x22.2mm red 2NO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 85°C protection IP40		

¹illuminated

overload switches



No.	347815	Ref. No.	ARM0119
	5 .7 0 .5		7 11 11 11 11 11 11
description	push switch KJD17 mounting measurements 45x22mm red/green 2NO 250V 10A 0-I connection male faston 6.3mm ambient tempera- ture max. 85°C protection IP54		

microswitches

lever actuated



No.	347021	Ref. No.	ARM-02-164
description	microswitch with lever 250V 5A 1CO connection soldering connection L 15mm ambient temperature max. 85°C mounting distance 10mm actuating force: 13g lever length 17mm		

roller-lever actuated

microswitche



description

•	346137	Ref. No.	ARM.01.132
n	soldering connecti	on L 14mm L1 16.5 stance 9mm type S	h 250V 5A 1CO connection imm ambient temperature max. SS-5GL2 actuating force: 20g

contactors

TELEMECANIQUE (Schneider Electric)

power contactors



No.	380967	Ref. No.	ARM01121 ARM02175
description	power contactor resistive load 20A 230VAC (AC3/400 contacts 3NO auxiliary contacts 1NO connection scretype LC1K0910M7		

equipment-specific units

for dough mixers

agitators



·			
No.	692120	Ref. No.	ARM0101
description	beater for dough i	mixer shaft ø 20 H 2	30mm W 170mm

