
Professionale pentru echipamente profesionale





heating elements

immersion heating elements









with roun	d flange ø4	7.5mm	_	_
1		=		
No.	416306	Ref. No.	2	010
description	L 270mm W 38m sleeves ø 7.5mm	m H 22mm conne number of therm	ting circuits 1 mou ection M4 tube ø 6 ostat sleeves 1 len eccentric, non clin	mm thermostat gth thermostat
accessories for	416306			
	No.	510408	Ref. No.	4011
\circ	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	510562	Ref. No.	_
O	O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs			
400	No.	520235	Ref. No.	_
	3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			
	No.	520236	Ref. No.	_
0	flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes			
	No.	550002	Ref. No.	3136
3	tension strap H	10mm L 21mm W	10mm hole ø 6.5n	nm for heating
	No.	550362	Ref. No.	_
	blind flange ø 64	1mm mounting ø	47.5mm	






accessories for	416319					
	No.	550002	Ref. No.	3136		
1	tension strap element	tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element				
	No.	550362	Ref. No.	_		
	blind flange ø 64mm mounting ø 47.5mm					

1				
No.	416327	Ref. No.	4	552
description		: 3000W 230V hea nm H 60mm conne		
accessories for	416327			
	No.	510408	Ref. No.	4011
\bigcirc	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs			
	No.	510562	Ref. No.	_
O-ring silicone thickness 5.34mm ID ø 47mm Qty 1 pcs				ocs
400	No.	520235	Ref. No.	_
	3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			
	No.	520236	Ref. No.	_
0	flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes			
	No.	550002	Ref. No.	3136
13	tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element			nm for heating
	No.	550362	Ref. No.	_
	blind flange ø 64mm mounting ø 47.5mm			

		To any			
1					
No.	416317	Ref. No.		4	551
description	L 400mm W 3 stat sleeves ø	ent 6000W 230V 6mm H 36mm co 7mm number of 35mm thermosta	onnectio thermos	n M4 tube ø 6 stat sleeves 1 l	ength thermo-
spare parts for	416317				
	No.	510408	Ref	No.	4011
\bigcirc	O-ring EPDM thickness 5.34mm ID ø 47mm Qty 1 pcs				
accessories for	416317				
	No.	510562	Ref	. No.	_
\circ	O-ring silicon	e thickness 5.34r	mm ID ø	47mm Qty 1 բ	ocs
400	No.	520235	Ref	. No.	_
	3 hole flange hole distance 70.5mm perforation ø 6.5mm ID ø 53.5mm			5mm ID ø	
	No.	520236	Ref	. No.	_
O	flange for heating element ID ø 50mm ED ø 90mm hole ø 6.5mm 3 holes				
	No.	550002	Ref	. No.	3136
1	tension strap H 10mm L 21mm W 10mm hole ø 6.5mm for heating element				
	No.	550362	Ref	. No.	_
	blind flange ø 64mm mounting ø 47.5mm				







thermostats

bi-metal thermostats

safety bi-metal thermostats



No.	390455	Ref. No.	4751
escription	bi-metal safety the 100°C 2NC 2-pole		nce 40mm switch-off temp. 3 2 hole fixing



control and safety thermostats

IMIT / TEMPOMATIC / ARTHERMO

control thermostats



No.	375920	Ref. No.	4044
escription	probe ø 6.5mm pro	obe L 98mm capilla and nut shaft ø 6x4	range 0-90°C 1-pole 1CO 16A ıry pipe 1030mm capillary pipe I.6mm shaft L 16mm rotation

accessories

plunger sockets



·			
No.	507462	Ref. No.	1503
description	thermowell thread	d M10x1 ID ø 7.7mr	n L 115mm for probe 100mm

switches and momentary switches

rocker/momentary rocker switches

Tocker/momentary tocker switch

30x22mm




description

No.	345317	Ref. No.	1519 1520
description	2NO 230V 16A illu	minated connectio	measurements 30x22mm green n male faston 6.3mm ambient on IP65 with rubber collar


MARQUARDT 1			
No.	347531	Ref. No.	4069
	rocker switch mou	ınting measuremer	nts 30x22mm green 2NO 250V

ture max. 125/55°C protection IP65 with rubber collar

20A illuminated 0-I connection male faston 6.3mm ambient tempera-



blank				
No.	345982	Ref. No.	1	521
description	rocker switch mounting measurements 30x22mm green 2CO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 125/55°C protection IP65 with cover cap			
accessories for	345982			
1	No.	301036	Ref. No.	_
	protective cover measurementsm		2mm for rocker sv	vitch mounting




microswitches

lever actuated





No.	346067	Ref. No.	4074
description		lever 250V 16A 1CC ture max. 125°C leve) connection male faston 6.3mm er length 30mm











lamps



indicator lights (complete)

ø 6mm




1			
No.	359434	Ref. No.	1513
description	indicator light ø 6	mm 230V green	

timers

programme timers








contactors

ALLEN BRADLEY



relays


power relays

with flange mounting



No.	380020	Ref. No.	4360
description	power relays FIND 6.3mm manuf. no.		O connection male faston 062.10 2-pole







electronics

PCBs








solenoid valves

solenoid valves (water)



	370021	accessories for 370021			
	No.	371220	Ref. No.	_	
	reducer TP flow	rate 3l/min red to	erance ±15%		
	No.	371221	Ref. No.	_	
	reducer TP flow	rate 5.5l/min yello	w tolerance ±15%		
	No.	371222	Ref. No.	_	
	reducer TP flow	rate 6l/min grey to	olerance ±15%		
0	No.	371223	Ref. No.	_	
		rate 10l/min white			
	No.	371224	Ref. No.	_	
			ze tolerance ±15%		
d'à	No.	371225	Ref. No.	_	
	reducer TP flow	rate 16l/min light	brown tolerance ±	15%	
616	No.	371226	Ref. No.	_	
	reducer TP flow	rate 20I/min red to	olerance ±15%		
	No.	371230	Ref. No.	_	
		rate 0.25I/min red			
	No.	371231	Ref. No.	_	
			let tolerance ±25%		
	No.	371232	Ref. No.	_	
	reducer TP flow	rate 0.5l/min oran	ge tolerance ±25%		
-					
<u>.</u>	No.	371233	Ref. No.	_	
			e tolerance ±25%	_	
				_	
•	No.	rate 0.8I/min whit 371234 rate 1I/min light b	e tolerance ±25% Ref. No. lue tolerance ±259		
	reducer TP flow No.	rate 0.8l/min whit	e tolerance ±25% Ref. No.	— — %	
	No. reducer TP flow of the total of t	371234 rate 1l/min light b 371235	e tolerance ±25% Ref. No. lue tolerance ±259	_	
	No. reducer TP flow of the total of t	371234 rate 1l/min light b 371235	e tolerance ±25% Ref. No. lue tolerance ±259 Ref. No.	_	
	No. reducer TP flow in No. reducer TP flow in No. reducer TP flow in No.	371234 371235 rate 1.2l/min brov 371236	e tolerance ±25% Ref. No. lue tolerance ±259 Ref. No. vn tolerance ±25%	_	
	No. reducer TP flow in No. reducer TP flow in No. reducer TP flow in No.	371234 371235 rate 1.2l/min brov 371236	Ref. No. Ref. No. Ref. No. Ref. No. rn tolerance ±25% Ref. No.	_	
	reducer TP flow in No.	arate 0.8l/min white 371234 arate 1l/min light be 371235 arate 1.2l/min brow 371236 arate 1.5l/min light arate 1.5l/min light arate 2.5l/min yello	Ref. No. Ref. No. Ref. No. rn tolerance ±25% Ref. No. brown tolerance ± Ref. No. w tolerance ± Ref. No. w tolerance ± Ref. No.		
	No. reducer TP flow in No.	371234 arate 1.2l/min brov 371236 arate 1.5l/min light 1.371237	e tolerance ±25% Ref. No. lue tolerance ±259 Ref. No. vn tolerance ±25% Ref. No. brown tolerance ±		
	reducer TP flow in No.	rate 0.8l/min whit 371234 rate 1l/min light b 371235 rate 1.2l/min brov 371236 rate 1.5l/min light 371237 rate 2.5l/min yello 371238 rate 3.4l/min dark	Ref. No. Ref. No. Ref. No. What tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. What tolerance ±25% Ref. No. What tolerance ±25% Ref. No. Ref. No. Green tolerance ±25%		
	No. reducer TP flow in No.	371234 371235 371235 rate 1.2l/min brov 371236 rate 1.5l/min light 371237 rate 2.5l/min yello	Ref. No. Ref. No. Ref. No. In tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. Ref. No. Ref. No. Ref. No. Ref. No. Ref. No.	- 	
	reducer TP flow in No.	arate 0.8l/min white 371234 arate 1l/min light be 371235 arate 1.2l/min brow 371236 arate 1.5l/min light 371237 arate 2.5l/min yello 371238 arate 3.4l/min dark 371239 arate 5l/min black	Ref. No. Ref. No. Ref. No. In tolerance ±25% Ref. No. Brown tolerance ± Ref. No. We tolerance ±25% Ref. No. We tolerance ±25% Ref. No. Ref. No. Green tolerance ± Ref. No. Ref. No. Solerance ±25%		
	reducer TP flow in No.	arate 0.8l/min white 371234 arate 1l/min light be 371235 arate 1.2l/min brow 371236 arate 1.5l/min light 371237 arate 2.5l/min yello 371238 arate 3.4l/min dark 371239	Ref. No. Ref. No. Ref. No. Ref. No. Ref. No. brown tolerance ±25% Ref. No. brown tolerance ±25% Ref. No. green tolerance ±25% Ref. No.		
	reducer TP flow in No.	arate 0.8l/min white 371234 arate 1l/min light be 371235 arate 1.2l/min brow 371236 arate 1.5l/min light 371237 arate 2.5l/min yello 371238 arate 3.4l/min dark 371239 arate 5l/min black	Ref. No. Ref. No. Ref. No. In tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. Brown tolerance ±25% Ref. No. Ref. No. Green tolerance ±25% Ref. No. Ref. No.	- 	





371237

reducer TP flow rate 2.5l/min yellow tolerance ±25%

No.

Ref. No.

accessories for	370017				
-	No.	371238	Ref. No.	_	
	reducer TP flo	reducer TP flow rate 3.4l/min dark green tolerance ±25%			
	No.	371239	Ref. No.	_	
	reducer TP flow rate 5l/min black tolerance ±25%				
	No.	371240	Ref. No.	_	
	reducer TP flow rate 8I/min blue tolerance ±20%				







accessories for	370016				
	No.	371234	Ref. No.	_	
	reducer TP flow r	ate 1l/min light b	lue tolerance ±25°	%	
-	No.	371235	Ref. No.	_	
	reducer TP flow r	rate 1.2l/min brow	n tolerance ±25%)	
-	No.	371236	Ref. No.	_	
	reducer TP flow r	ate 1.5l/min light	brown tolerance :	±25%	
2	No.	371237	Ref. No.	_	
	reducer TP flow rate 2.5I/min yellow tolerance ±25%				
	No.	371238	Ref. No.	_	
	reducer TP flow rate 3.4l/min dark green tolerance ±25%				
	No.	371239	Ref. No.	_	
	reducer TP flow rate 5I/min black tolerance ±25%				
	No.	371240	Ref. No.	_	
	reducer TP flow r	rate 8I/min blue to	olerance ±20%		
	No.	503139	Ref. No.	_	
U	solenoid valve fil	ter ø 19.5mm H 1	6mm		

solenoid valves with reducers



No.	370142	Ref. No.	1542		
description	solenoid valve double straight 230VAC inlet 3/4" outlet 11.5mm output B 0.6l/min				

pressure switches

for warewashing

ø 58mm with male faston 6.3mm

with connection horizontal



No.	541140	Ref. No.	4054		
description	pressure control pressure range 55/30mbar connection 6mm @ 58mm pressure connection horizontal warewashing				

compressors

SECOP DANFOSS

R404a/R507

LBP monophase

Lower evaporation temperature below -20°C



No.	605056	Ref. No.	T21	78GK	
description	compressor coolant R404a/R507 type SC18CLX.2 220-240V 50Hz LBP fully hermetic 13.7kg 5/8HP cylinder capacity 17.69cm³ CSR H 219mm 562W 691W 881W 1095W 1332W 1593WWWW test method ASHRAE				
spare parts for	605056				
	No. 381548 Ref. No. —				
	start relay DANFOSS				

pumps

wash and rinse pumps

FIR

pumps



140.	300437	itel. ito.	,	023
description		ım outlet ø 26mm t HP L 198mm rotatio	, i	
spare parts for	500457			

365012




operating capacitor capacity $6.3\mu F$ 450V tolerance 5% 50Hz ambient temperature max. -25 to +85°C ø 30mm L 61mm M8 plastic connection male faston 6.3mm protection

Ref. No.










1					
No.	500683	Ref. No.		4718	
description		pump inlet ø 60mm outlet ø 50mm type 2223.U150 230V 50Hz 1 phase 0.89kW 1.2HP L 260mm rotation direction right capacitor 16μF FIR			
spare parts for	500683				
	No.	365021	Ref. No.	_	
4	ent temperat	ure max25 to +8		5% 50/60Hz ambi- m single M8 plastic on	
	No.	510552	Ref. No.	_	
0	pump cover gasket pump type 1292-2/3942/3981/3911/3983				
court).	No.	510600	Ref. No.	_	
impellor ø 102mm H 29mm shaft intake ø 9/8mm rotation dire right blades 6			rotation direction		
	No.	510692	Ref. No.	_	
90	mechanical shaft seal for shaft ø 11mm slide ringext. ø 24mm slide ring H 13mm counter ring mounting ø 26mm height counter ring 8mm counter ring int. ø 14mm				
	No.	521511	Ref. No.	_	
-000-0					

pump cover inlet ø 60mm outlet ø 50/30mm supporting pressure M12x1.75 supporting pressure open pump type 2233 turn direction

right ø 160mm ID ø 120mm inner hight 23mm





521257

12mm shaft length 7.5mm blades 6

Ref. No. impellor $\,$ ø 80mm H 12mm rotation direction left thread M10R shaft ø

No.

	No.	500476	Ref. No.	1	808
descr	iption	pump inlet ø 50mm outlet ø 30mm type T45 230V 50Hz 1 phase 0.33kW 0.45HP L 215mm rotation direction left capacitor 8μF OLYMPIA			
spare	parts for	500476			
120		No.	365013	Ref. No.	_
G	operating capacitor capacity 8μF 400V tolerance 5%Hz ambient tem- perature max25 to +85°C ø 31.5mm L 55mm M8 plastic connection				

male faston 6.3mm protection



spare parts for	500476			
	No.	501312	Ref. No.	_
	O-ring EPDM thickness 1.78mm ID ø 88.62mm Qty 1 pcs			
	No.	510693	Ref. No.	_
90	mechanical shaft seal for shaft ø 12mm slide ringext. ø 24mm slide ring H 15.5mm slide ring int. ø 11mm counter ring mounting ø 24mm height counter ring 8mm counter ring int. ø 13.5mm			
0	No.	521258	Ref. No.	_
	impellor ø 80mm H 13mm thread M10R shaft ø 12mm shaft length 7.5mm blades 6			





drain pumps







electric accessories

terminals

connection boxes



No.	550300	Ref. No.	4752
description	power terminal blo	ock 3-pole contacts	P+N+E

equipment-specific units

for dishwashers

drain and intake components

UNIVERBAR

drain /intake hodies



No.	507449	Ref. No.	1536
description	drain fitting thread 1" hose ø 30mm		



overflow pipes 1 No. 507466 Ref. No. 1534 description overflow pipe L 107mm ø 28mm








containers


salt tanks



' ·						
No.	510929 Ref. No. 4333					
description		salt tank ø 120mm H 117mm hose ø 10mm mounting ø 70mm overall height 157mm				
spare parts for	510929	510929				
	No.	506015	Ref. No.	_		
\bigcirc	O-ring EPDM thickness 3.53mm ID ø 39.69mm Qty 1 pcs					
	No.	510018	Ref. No.	_		
Q	nut ø 92mm	H 10.5mm for salt	tank ID ø 64mm			
	No.	524177	Ref. No.	_		
	lid ø 69mm H 20mm for salt tank ID ø 50mm					








27.15-				
boilers				
boilers for	r dishwashe	ers		
1				
No.	507465	Ref. No.	3326	
description	boiler without h outlet ø 2x 10mi	•	0mm L 415mm inlet ø 12mm	














EQUIPMENT-SPECIFIC UNITS UNIVER-BAR







washing and rinsing systems (sorted by produc-


UNIVERBAR No. 507502 Ref. No. 2540 wash and rinse arm wash arm L 385mm rinse arm L 385mm w. jets 12 r. jets 4 mounting ø 10/32mm mounting pos. upper/lower L 390mm W 390mm




spare parts for	507581				
spare parts rei	No.	510893	Ref. No.		
0	11101		m ID ø 9.92mm Qty 1	pcs	
1	No.	517092	Ref. No.	_	
2	guide for rins	se arm shaft			
	No.	517101	Ref. No.	_	
	gasket PTFE I	ED ø 16mm ID ø	10mm thickness 2.5m	m Qty 1 pcs	
	No.	517102	Ref. No.	_	
	rinse arm sha	ft			
	No.	517103	Ref. No.		
0	cover				
	No.	517104	Ref. No.	_	
\bigcirc	O-ring EPDM	thickness 2.62m	m ID ø 31.42mm Qty	1 pcs	
1	No.	517408	Ref. No.	_	
1	pipe for wash arm ED ø 42mm L 150mm plastic mounting ø 28mm ID ø 10mm				
	No.	517609	Ref. No.	2528	
	bush for rinse 10mm	e arm PTFE L 10.6	imm D1 ø 14mm D2 ø	16.5mm ID ø	
	No.	560536	Ref. No.	2535	
	Thumb screw	thread M8 threa	ad L 5mm ø 20mm H 1	0mm SS Qty 1	



1			
No.	507468	Ref. No.	4080
description	end cap for ri	nse arm thread M10x1	H 8mm chrome-plated brass







wash and rinse arm wash arm L 485mm rinse arm L 470mm w. jets 6


r. jets 6 mounting ø 10/43mm mounting pos. upper/lower



1			
No.	507468	Ref. No.	4080
description	end cap for rinse arm thread M10x1 H 8mm chrome-plated brass		


description


1			
No.	503317	Ref. No.	4022
description	rinse jet H 13mm thread M6x1 WS 10 conical seal		







1				
No.	507468	Ref. No.	4080	
description	end cap for rinse arm thread M10x1 H 8mm chrome-plated brass			









knobs

producer-specific knobs UNIVERBAR








accessories rosettes No. 112195 Ref. No. 3322 description rosette knob knob ø 42mm ø 56mm


gaskets


description

O-rings EPDM No. 517035 Ref. No. 3285




O-ring EPDM thickness 1.78mm ID ø 4.48mm Qty 1 pcs






rubber gaskets No. 517181 Ref. No. 1535 description flat gasket rubber ED ø 44mm ID ø 32mm thickness 3mm Qty 1 pcs



dosing pumps

peristaltic dosing pumps







1 1916 No. 361767¹ Ref. No. dosing pump SEKO 3I/h 230VAC detergent hose ø 4x6mm hose type description K hose Santoprene suction level 1.5m type NBR 3 8W built-in version peristaltic pump spare parts for 361767 No. 361815 pump hose detergent hose ø 6x10mm hose ø 4x6mm hose type K hose Santoprene type SEKO incl. inlet and conveyor hose

accessories for 361535 361701 Ref. No. hose connector thread M10x1 grommet ø 7.5mm 361703 Ref. No. No. hose connector thread M10x1 brass pipe connection ø 4x6mmmm Ref. No. hose connector brass straight thread M12x1 hose ø 11mm Qty 1 pcs 510296 Ref. No. membrane silicone 520090 Ref. No. PVC hose ID ø 4mm ED ø 6mm L 2m thickness 1mm t.max. 60° C transparent 520091 Ref. No. nylon hose ID ø 4mm ED ø 6mm L 2m thickness 1mm operating p. 10bar burst p. 50bar t.max. 100°C transparent

membrane dosing pumps

self-priming with supporting pressure

GERMAC

type 2000



1					
No.	361535	Ref. No.	4	096	
description		rpe 2000 rinse aid i 6mm supporting p CODE VNR/U3			
spare parts for	361535				
	No.	361550	Ref. No.	_	
	hose connector	hose ø 4x6mm			
Om	No.	361551	Ref. No.	_	
WILLIO .	compression spi	ring wire gauge ø	1mm		
*	No.	361702	Ref. No.	_	
	hose connector brass hose ø 4x6mm				
	No.	361705	Ref. No.	_	
O	gasket for hose connector M12x1				
	No.	510298	Ref. No.	_	
	lip valve dosing	g pump suitable fo	r DB2/DS5		
accessories for	361535				
	No.	361142	Ref. No.	_	
00h	mounting set detergent hose type 4x6mm hose length 2m PVC 2x hose/container filter/tank intake transparent				
	No.	361553	Ref. No.	_	
	membrane EPD	М			
~~	No.	361700	Ref. No.	_	
A STATE OF THE PARTY OF THE PAR					

hose connector rotary hose ø 4x6mm plastic connection M10x1

accessories

container filters



Ref. No. description container filter plastic hose ø 5mm detergent

1040

hoses

supply hoses

PVC supply hoses




No.	520010	Ref. No.	3	204	
description	supply hose PVC straight-curved DN13 connections 3/4" L 1500mm operating p. 10bar burst p. 32bar t.max. 90°C blue approval VDE flat seal				
accessories for	520010				
	No.	520053	Ref. No.	_	
	screen connection 3/4" D1 ø 26mm D2 ø 15mm Qty 10 pcs rubber thickness 8mm				
0	No.	520054	Ref. No.	_	
	flat gasket rubber ED ø 23.5mm ID ø 14mm thickness 2.3mm Qty 10				






No. 511205 Ref. No. 1604 drain hose DN19 L 1500mm A int. Ø 23mm A ext. Ø 29mm B int. Ø 29mm outer hose Ø 29mm B ext. Ø 35mm



measuring equipment

thermometers



fastening material



